## View NSN Online: https://aerobasegroup.com/nsn/5970-01-223-0782

## DEXTER CORP DEXTER ELECTRONI -- PO0011, HYSOL PC18M (SEE SUPPL)

MSDS Safety Information

FSC: 5970 NIIN: 01-223-0782 MSDS Date: 04/17/1997 MSDS Num: CLCJM Product ID: PO0011, HYSOL PC18M (SEE SUPPL) MFN: 02 Responsible Party Cage: 04347 Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV. Address: 211 F RANKLIN ST. City: OLEAN NY 14760-1297 Info Phone Number: 716-372-6300/6309 Emergency Phone Number: 716-372-6300
Item Description Information
Item Manager: S9G Item Name: INSULATING VARNISH,ELECTRICAL Unit of Issue: EA UI Container Qty: 1 Type of Container: CAN
Ingredients
======================================
Health Hazards Data
LD50 LC50 Mixture: NOT PROVIDED Route Of Entry Inds - Inhalation: YES Skin: YES Ingestion: NO Carcinogenicity Inds - NTP: YES IARC: YES OSHA: NO Effects of Exposure: TARGET ORGANS: EYES, SKIN, RESPIRATORY TRACT. EYE CONTACT: MAY CAUSE IRRITATION. SKIN CONTACT: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE I

RRITATION. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES (> 150C) CAN RESULT IN THERMAL BURNS. INHALATION: HARMFUL IF INHALED, MAY CAUSE ALLERGIC RESPIRATORY REACTION SUCH AS ASTHMA. INGESTION: MODERATELY TOXIC, MAY CAUSE VOMITING.

Explanation Of Carcinogenicity: BENZENE, 2,4-DIISOCYANATE-1-ME, BENZENE, 1,3-DIISOCYANATE-2-ME (IARC= 2B; NTP= GP2).

Signs And Symptions Of Overexposure: EYE/SKI: IRRITATION. CONTACT WITH PRODUCT

AT ELEVATED TEMPERATURES (>150C) CAN RESULT IN THERMAL

BURNS. HARMFUL IF

INHALED, MAY CAUSE ALLERGIC RESPIRATORY REACTION SUCH AS ASTHMA. MODERATELY TOXIC BY INGESTION. MAY CAUSE VOMITING.

Medical Cond Aggravated By Exposure: PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT. PRE-EXISTING SKIN OR LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGIC SYMPTOMS TO THIS PRODUCT.

First Aid: EYE CONTACT: IMMEDIATELY WASH/ FLUSH EYES WITH WATER FOR MINUMUM 10 MINUTES. SEEK MEDICAL ATTENTION. SKI

N CONTACT: WASH OFF IN FLOWING WATER OR

SHOWER. REMOVE CONTAMINATED CLOTHING AND SHOES. SEEK MED ICAL ATTENTION, IF IRRITATION DEVELOPS. INHALATION: MOVE TO FRESH AIR. IF NOT BREATHING, GIVE MOUTH TO MOUTH RESUSCITATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SEEK MEDICAL ATTENTION. INGESTION: I F SWALLOWED, DO NOT INDUCE VOMITING. SEEK PROMPT MEDICAL ATTENTION. NOTE TO PHYSICIAN: TREATMENT SHOULD BE DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL CONDITIONS. THERE ARE NO SPECI FIC

ANTIDO TES.

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_

Spill Release Procedures: CLEAN-UP: CONTAIN SPILL IN NATURAL FORM OR WITH SAND OR DIRT. ELIMINATE ALL IGNITION SOURCES. PREVENT RUNOFF TO STORM SEWERS, DITCHES AND WATERWAYS. SHOVEL OR SCRAPE (NON-METALLIC) ABSORBED WASTE MATE RIAL INTO DISPOSAL CONTAINER. SEAL LID TIGHTLY WITH TAPE AND LABEL PROPERLY. CLEAN UP SPILL IMMEDIATELY. OBSERVE

PRECAUTIONS INCLUDING VENTILATION AND/ OR

PERSONAL PROTECTIVE EQUIPMENT.

Neutralizing Agent: NOT RELEVANT.

Waste Disposal Methods: LEGAL DISPOSTION OF WASTE IS THE RESPONSIBILITY OF THE OWNER/ GENERATOR OF THE WASTE. APPLICABLE FEDERAL, STATE, AND/ OR LOCAL REGULATIONS MUST BE FOLLOWED DURING TREATMENT, STORAGE, OR DISPOSAL OF WA STE CONTAINING THIS PRODUCT. DO NOT DISPOSE OF IN AN UNCONTROLLED MANNER. Handling And Storage Precautions: STORE AT LESS THAN TWENTY FIVE DEGREE CENTIGRADE ( &It;25C) (77F) FOR OPTIMUM SHELF LIFE. DRY ATMOSPHERIC CONDITIONS. KEEP CONTAINERS CLOSED AND TIGHTLY SEALED. PLASTIC CONTAINER MAY BE SLIPPERY WHEN HAND LING.

Other Precautions: DO NOT EXPOSE TO DIRECT SUNLIGHT. ONCE CONTAINER IS OPEN, USE NITROGEN BLANKET ON MATERIAL AND RESEAL.

\_\_\_\_\_

Fire and Explosion Hazard Information

Flash Point Method: CC Flash Point: =31.7C, 89.F Extinguishin g Media: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures: RECOMMENDED USE OF SELF CONTAINED BREATHING APPARATUS (SCBA). Unusual Fire/Explosion Hazard: NO UNUSUAL FIRE OR EXPLOSION HAZARDS. \_\_\_\_\_ Control Measures \_\_\_\_\_ Respiratory Protection: NO RESPIRATOR IS REQUIRED IF INGREDIENT EXPOSURE LIMITS ARE NOT EXCEEDED. AN OSHA APPROVED (29CFR1910.134USA DEPT OF LABOR), AI R-PURIFYING RESPIRATOR WITH APPROPRIATE CARTRIDGE SHOULD BE USED IF EXPOS URE LIMITS ARE EXCEEDED. Ventilation: USE LOCAL EXHAUST VENTILATION NEAR THE SOURCE. Protective Gloves: PVC, RUBBER (LATEX, NITRILE, BUTYL) Eye Protection: SAFETY GLASSES WITH SIDE SHIELD OR GOGGLES. Other Protective Equipment: A SAFETY SHOWER AND EYE WASH STATION SHOULD BE WITHIN REASONABLE DISTANCE TO THE WORK AREA. Work Hygienic Practices: NOT PROVIDED Supplemental Safety and Health: CONTD FROM PRODUCT ID: CONTRACTO **R'S (CAGE:** 7B953) PART NUMBER: MIL-I-46058C \_\_\_\_\_ Physical/Chemical Properties \_\_\_\_\_ HCC: F3 NRC/State LIC No: NOT RELEVANT. **B.P. Text: NOT PROVIDED** M.P/F.P Text: NOT PROVIDED Decomp Text: NOT PROVIDED Vapor Pres: 9.5 Vapor Density: 3.7 Spec Gravity: 1.0

Spec Gravity: 1.0 VOC Pounds/Gallon: 4.6 PH: NOT PROVIDED VOC Grams/Liter: 550 Viscosity: NOT PROVIDED. Evaporation Rate & amp; Reference: 0.5 NO REF Solubility in Water: SOLUBLE Appearance and Odor: LIQUID, MEDIUM VISCOSITY, AMBER COLOR, AROMATIC ODOR Corrosion Rate: NOT PROVIDED \_\_\_\_\_ **Reactivity Data** \_\_\_\_\_ Stability Indicator: YES Stability Condition To Avoid: HIGH TEMPERATURES; OPEN FLAMES Materials To Avoid: NONE IDENTIFIED Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE; OXIDES OF NITROGEN, POSSIBLE ORGANICS Hazardous Polymerizat ion Indicator: YES Conditions To Avoid Polymerization: EXOTHERMIC. \_\_\_\_\_ **Toxicological Information** \_\_\_\_\_ Toxicological Information: TESTING HAS NOT BEEN PERFORMED ON THIS PRODUCT. FOR DATA ON COMPONENTSM PLEASE PHONE 716-372-6300. Ecological Information \_\_\_\_\_ Ecological: NO SPECIFIC STUDIE S HAVE BEEN CONDUCTED BY DEXTER. RELEASE OF VOLATILE COMPOPNENTS TO THE ATMOSPHERE ARE NOT BELIEVED TO ENTAIL SIGNIFICANT ECOLOGICAL CONSEQUENCES PROVIDED SUCH RELEASES ARE WITHIN THE EXPOSURE LIMITS. **MSDS Transport Information** \_\_\_\_\_ Transport Information: PSN: RESIN SOLUTION, 3, UN1866. FLAMMABLE LIQUID LABLE. \_\_\_\_\_ **Regulatory Inform** ation \_\_\_\_\_ Sara Title III Information: FOLLOWING COMPONENTS ARE SUBJECT TO SEC 311/312:

URETHANE COPLOYMER, 2-PROPANOL, 1-METHOX. COMPONENT BENZENE DIMETHYL- IS SUBJECT TO SEC 302, 304 AND CERCLA LISTS. COMPONENT BENZENE ETHYL- AND BENZENE METHYL- AND BENZENE 1,3-DIISICYANTE ARE SUBJECT TO SEC 302/304, 311/312 AND 313.

State Regulatory Information: LISTED ON CALIFORNAI PORP 65: BENZENE DIISOCYANATE, BENZENE METHYL-,

\_\_\_\_\_

Other Information \_\_\_\_\_ Other Information: CLASSIFICATION: HEALTH =2; FLAMMABILITY=2; REACTIVITY=0. \_\_\_\_\_ Transportation Information \_\_\_\_\_ Responsible Party Cage: 04347 Trans ID NO: 156862 Product ID: PO0011, HYSOL PC18M (SEE SUPPL) MSDS Prepared Date: 04/17/1997 Review Date: 04/30/2001 **MFN: 2** Tech Entry NOS Shipping Nm: CONTAINS BENZENE DIMETHYLDIISOCYANATES (1,3 & amp; 2,4) Net Unit Weight: 2.1 LB/QT Multiple KIT Number: 0 Unit Of Issue: EA Container QTY: 1 Type Of Container: CAN \_\_\_\_\_ **Detail DOT Information** \_\_\_\_\_ DOT PSN QS DOT Proper Shipping Name: RESIN SOLUTION DOT PSN Modifier: FLAMMABLE Hazard Class: 3 UN ID Num: UN1866 DOT Packaging Group: III Label: FLAMMABLE LIQUID **Special Provision:** B1, B52, T7, T30 Packaging Exception: 150 Non Bulk Pack: 173 Bulk Pack: 242 Max Qty Pass: 60 L Max Qty Cargo: 220 L Vessel Stow Reg: A \_\_\_\_\_ Detail IMO Information \_\_\_\_\_ IMO PSN Code: NBJ IMO Proper Shipping Name: RESIN, SOLUTION IMO PSN Modifier: FLAMMABLE o IMDG Page Number: 3379 UN Number: 1866 UN Hazard Class: 3.3 IMO Packaging Group: III Subsidiary Risk Label: -EMS Number: 3-05 MED First Aid G

\_\_\_\_\_\_

```
uide NUM: 310
```

Detail IATA Information \_\_\_\_\_ IATA PSN Code: VSA IATA UN ID Num: 1866 IATA Proper Shipping Name: RESIN SOLUTION IATA PSN Modifier: ,FLAMMABLE IATA UN Class: 3 IATA Label: FLAMMABLE LIQUID UN Packing Group: III Packing Note Passenger: 309 Max Quant Pass: 60L Max Quant Cargo: 220L Packaging Note Cargo: 310 \_\_\_\_\_ Detail AFI Inform ation \_\_\_\_\_ AFI PSN Code: VSA AFI Proper Shipping Name: RESIN SOLUTION AFI PSN Modifier: ,FLAMMABLE AFI Hazard Class: 3 AFI UN ID NUM: UN1866 AFI Packing Group: III **Special Provisions: P5** Back Pack Reference: A7.3 \_\_\_\_\_\_ HAZCOM Label \_\_\_\_\_\_ Product ID: PO0011, HYSOL PC18M (SEE SUPPL) Cage: 04347 Company Name: DEXTER CORP THE DEXTER ELECTRONIC MAT **ERIAL DIV** Street: 211 FRANKLIN ST. City: OLEAN NY Zipcode: 14760-1297 Health Emergency Phone: 716-372-6300 Label Required IND: Y Date Of Label Review: 04/30/2001 Status Code: A Year Procured: 2001 Origination Code: F Chronic Hazard IND: Y Eye Protection IND: YES Skin Protection IND: YES Signal Word: WARNING Respiratory Protection IND: YES Health Hazard: Moderate Contact Hazard: Moderate Fire Hazard: Moderate Reactivity Hazard: None

Hazard And Precautions: TARGET ORGANS: EYES, SKIN, RESPIRATORY T

## RACT. MAY

CAUSE IRRITATION TO EYES, SKIN, AND RESPIRATORY TRACT. HARMFUL IF INHALED, MAY CAUSE ALLERGIC RESPIRATORY REACTION SUCH AS ASTHMA. INGESTION: MODERAT ELY TOXIC, MAY CAUSE VOMITING. FIRST AID: EYE: IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES. CALL PHYSICIAN. SKIN: FLUSH WITH PLENTY OF WATER. REMOVE CONTAMINATED CLOTHINGS. WASH CLOTHING BEFORE REUSE. INHALATION: MOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. INGESTION: DO NOTINDUCE VOMITING, CALL A PHYSICIAN. THERE ARE N O SPECIFIC ANTIDOTES.

O SPECIFIC ANTIDOTES.

\_\_\_\_\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contrac

ting with any instrumentality of the United

States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.