

FISKE BROTHERS REFINING CO -- LUBRIPLATE NO. 130-A, NO. 130-AA -- 9150-00-857-9079

===== Product Identification =====

Product ID:LUBRIPLATE NO. 130-A, NO. 130-AA

MSDS Date:01/01/2000

FSC:9150

NIIN:00-857-9079

MSDS Number: CLDCY

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE, STATION A

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Nu

m:419-691-2491

Emergency Phone Num:(800) 255-3924 CHEM-TEL (24 HOUR)

Preparer's Name:JAMES R. KONTAK

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

Company Name:SALATHE OIL CO INC

Address:2226 PETERS RD

Box:City:HARVEY

S

tate:LA  
ZIP:70058  
Country:US  
Phone:504-366-4542  
Contract Num:SP0450-01-M-LP43  
CAGE:0T5C6  
Company Name:SDB CONSULTANTS LTD  
Address:401 WHITNEY AVE SUITE 120  
Box:City:GRETNA  
State:LA  
ZIP:70056  
Country:US  
Phone:504-366-9105  
Contract Num:SP0450-01-M-LG43  
CAGE:0PGK2

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NON-HAZARDOUS  
OSHA PEL:5 MG/M3 (OIL MIST)  
ACGIH TLV:5 MG/M3 (OIL MIST)

=====  
Hazards Identification  
=====

Reports of Ca

rcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION. EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY

Explanation of Carcinogenicity:NO DATA PROVIDED BY MANUFACTURER.

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION. EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE

PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.  
SKIN: REMOVE ANY CONTAMINATED CLOTHING AND WASH WITH SOAP AND WARM WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF THE APPEARANCE OR ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW AND INHALATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE AND CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:204.4C, 400.F  
Lower Limits:0.9%  
Upper Limits:7.0%  
Extinguish  
ing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY(FOG).  
Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.  
Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.  
Other Precautions:REMOVE

OIL-SOAKED CLOTHING AND LAUNDRER BEFORE REUSE.  
CLEANSE SKIN THOROUGHLY AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED.

Ventilation:LOCAL EXHAUST- MECHANICAL (GENERAL) USED TO CAPTURE FUMES  
AND VAPORS.

Protective Gloves:USE OIL RESISTANT GLOVES, IF NEEDED.

Eye Protection:IF CHANCE OF EYE CONTACT, WEAR GOGGLES.

Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:REMOVE OIL-SO  
AKED CLOTHING AND LAUNDRER BEFORE

REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

Supplemental Safety and Health

FORMULA: CALCIUM SOAP, MINERAL OIL, ADDITIVES.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:>287.8C, 550.F

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.94 - 0.95

Evaporation Rate & Reference: