

DISTEC INC -- 60133, TFL 50 DRY LUBE -- 9150-01-344-7080

===== Product Identification =====

Product ID:60133, TFL 50 DRY LUBE  
MSDS Date:02/01/2001  
FSC:9150  
NIIN:01-344-7080  
Status Code:A  
MSDS Number: CLDSP  
=== Responsible Party ===  
Company Name:DISTEC INC  
Address:914 ARTIC STREET BLDG #777  
City:BRIDGEPORT  
State:CT  
ZIP:06608  
Country:US  
Info Phone Num:203-334-0383 / 800-643-6735  
Emergency Phone Num  
:800-424-9300  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:0TGR5  
=== Contractor Identification ===  
Company Name:DISTEC INC  
Address:914 ARTIC STREET BLDG #777  
Box:City:BRIDGEPORT  
State:CT  
ZIP:06608  
Country:US  
Phone:203-334-0383 / 800-643-6735  
Contract Num:SP0450-01-M-LG83  
CAGE:0TGR5

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA, LIGHT ALIPHATIC.  
CAS:64742-89-8  
&lt; Wt:30.

Ingred Name:FLUOROCARBON TELOMER  
&lt; Wt:10.

Ingred Name:PROPELLANT (CONSISTS

OF PROPANE AND ISOBUTANE)

&lt; Wt:70.

Ingred Name:PROPANE (20% OF PROPELLANT)

CAS:74-98-6

RTECS #:TX2275000

&lt; Wt:14.

OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:ISOBUTANE (80% OF PROPELLANT)

CAS:75-28-5

RTECS #:TI4300000

&lt; Wt:56.

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION OF  
RESPIRATORY TRACT, NAUSEA, DIZZINESS, HEADACHE AND DEPRESSION OF

THE CENTRAL NERVOUS SYSTEM AND IRREGULAR HEARTBEAT. INTENTIONAL  
MISUSE OF THIS PRODUCT BY DELIBERATELY CONCENTRATING AND INHALING  
CAN BE HARMFUL OR FATAL. INGESTION: MAY CAUSE GASTROINTESTINAL  
IRRITATION AND DEPRESSION OF THE CENTRAL NERVOUS SYSTEM. SKIN  
CONTACT: MAY CAUSE IRRITATION. EYE CONTACT: MAY CAUSE IRRITATION.  
PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS. MAY CAUSE SKIN  
IRRITATION ON PROLONGED OR REPEATED CONTACT.

Effects of Overexposure:INHALATION:

IRRITATION OF RESPIRATORY TRACT,

NAUSEA, DIZZINESS, HEADACHE, AND DEPRESSION OF THE CENTRAL NERVOUS  
SYSTEM, IRREGULAR HEARTBEAT. MISUSE OF THIS PRODUCT BY DELIBERATELY  
CONCENTRATING AND INHALING CAN BE HARMFUL OR FATAL. INGESTION:  
GASTROINTESTINAL IRRITATION AND DEPRESSION OF THE CENTRAL NERVOUS  
SYSTEM. SKIN: IRRITATION. EYE CONTACT: IRRITATION. PROLONGED OR  
REPEATED CONTACT MAY CAUSE DERMATITIS. MAY CAUSE SKIN IRRITATION  
ON PROLONGED OR REPEATED CONTACT.

Medical Con

d Aggravated by Exposure:NONE RECOGNIZED.

=====  
===== First Aid Measures =====

First Aid:INHALATION: IF USER EXPERIENCES BREATHING DIFFICULTY, MOVE TO  
AIR FREE OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION  
UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. INGESTION: DO NOT INDUCE  
VOMITING. CALL POISON CONTROL CENTER, HOSPITAL, EMERGENCY ROOM OR  
PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH WITH SOAP AND WATER. EYE  
CONTACT: FLUSH WITH LARGE QUANT

TITLES OF WATER FOR AT LEAST 15  
MINUTES. IF IRRITATION FROM CONTACT PERSISTS, GET MEDICAL  
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:FLAMMABLEAEROSOL

Extinguishing Media:USE CARBON DIOXIDE, DRY POWDER OR FOAM.

Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD  
BE PROVIDED FOR FIREFIGHTERS FIGHTING FLAMES IN BUILDINGS OR  
CONFINED AREAS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT  
COOL WITH WATER SPRAY  
TO PRE VENT PRESSURE BUILD-UP.

Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. DO NOT PUNCTURE,  
INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED  
EXPOSURE TO SUN MAY CAUSE BURSTING. ISOLATE FROM HEAT, ELECTRICAL  
EQUIPMENT, SPARKS, OPEN FLAME S AND HOT SURFACES. EXTREMELY  
FLAMMABLE AEROSOL - DOT CONSUMER COMMODITIES ORM-D.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS, VENTILATE AREA. FLUS  
H

LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS  
WITH LARGE QUANTITIES OF WATER. SMALL SPILL CAN BE ABSORBED BY  
APPROPRIATE INERT ABSOR BENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR FLAMES OR AT  
ELEVATED TEMPERATURES.

Other Precautions:READ CAREFULLY ALL CAUTIONS AND DIRECTIONS ON PRODUCT  
LABEL BEFORE USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL  
LABEL WARNING EV  
EN AFTER CONTAINER IS EMPTY. DISPOSE OF EMPTY  
CONTAINER ACCORD ING TO LOCAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH  
ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED  
TO PROVIDE MAXIMUM APPROPRIATE TLV. FOR OCCASIONAL USE WHERE  
ENGINEERED AIR CONTROL IS NOT FEASIBLE, USE NIOSH APPROVED  
RESPIRATORS. FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ADEQUATE

VENTILATION.

Ventilation:PROVIDE ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE MAXIMUM APPROPRIATE TLV.

Protective Gloves:USE IMPERMEABLE GLOVES TO PREVENT SKIN IRRITATION.

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES &/OR FACE SHIELDS ARE RECOMMENDED

Other Protective Equipment:USUALLY NONE REQUIRED.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE. BEFORE REUSE, THOROUGHLY CLEAN ANY CLOTHING OR PROTECTIVE EQUIPMENT WHICH HAS BEEN CO

NTAMINATED BY PRIOR USE.

Supplemental Safety and Health

MSDS COVERS PRODUCT NUMBERS #60132 - 5 OZ. / #60133 - 10 OZ.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:=85.C, 185.F

B.P. Text:185F TO 230F

Vapor Density:>AIR

Spec Gravity:7.058 LBS / GAL

Evaporation Rate & Reference:SLOWER THAN ETHER.

Appearance and Odor:10 OZ AEROSOL CAN.

Percent Volatiles by Volume:95%

===== Stability and Reactivity Data =====

Stability Indicat

or/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE

HYDROGEN CHLORIDE, HYDROGEN FLUORIDE AND SMALL AMOUNTS OF PHOSGENE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information:AEROSOL FLAMMABILITY CLASSIFICATION ACCORDING

TO ASTM D-3065-77 AND FHSA 1500.45 OSHA: EXTREMELY FLAMMABLE

AEROSOL - DOT CONSUMER COMMODITIES ORM-D.

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:AEROSOL FLAMMABILITY CLASSIFICATION ACCORDING TO ASTM D-3065-77 AND FHSA 1500 45 OSHA: EXTREMELY FLAMMABLE AEROSOL - DOT CONSUMER COMMODITIES ORM-D.

===== Regulatory Information =====

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.