

DISTEC INC -- 60133, TFL 50 DRY LUBE -- 9150-01-344-7080

===== Product Identification =====

Product ID:60133, TFL 50 DRY LUBE
MSDS Date:02/01/2001
FSC:9150
NIIN:01-344-7080
Status Code:A
MSDS Number: CLDSP
=== Responsible Party ===
Company Name:DISTEC INC
Address:914 ARTIC STREET BLDG #777
City:BRIDGEPORT
State:CT
ZIP:06608
Country:US
Info Phone Num:203-334-0383 / 800-643-6735
Emergency Phone Num
:800-424-9300
Chemtrec Ind/Phone:(800)424-9300
CAGE:0TGR5
=== Contractor Identification ===
Company Name:DISTEC INC
Address:914 ARTIC STREET BLDG #777
Box:City:BRIDGEPORT
State:CT
ZIP:06608
Country:US
Phone:203-334-0383 / 800-643-6735
Contract Num:SP0450-01-M-LG83
CAGE:0TGR5

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT NAPHTHA, LIGHT ALIPHATIC.
CAS:64742-89-8
< Wt:30.

Ingred Name:FLUOROCARBON TELOMER
< Wt:10.

Ingred Name:PROPELLANT (CONSISTS

OF PROPANE AND ISOBUTANE)

< Wt:70.

Ingred Name:PROPANE (20% OF PROPELLANT)

CAS:74-98-6

RTECS #:TX2275000

< Wt:14.

OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:ISOBUTANE (80% OF PROPELLANT)

CAS:75-28-5

RTECS #:TI4300000

< Wt:56.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION OF
RESPIRATORY TRACT, NAUSEA, DIZZINESS, HEADACHE AND DEPRESSION OF

THE CENTRAL NERVOUS SYSTEM AND IRREGULAR HEARTBEAT. INTENTIONAL
MISUSE OF THIS PRODUCT BY DELIBERATELY CONCENTRATING AND INHALING
CAN BE HARMFUL OR FATAL. INGESTION: MAY CAUSE GASTROINTESTINAL
IRRITATION AND DEPRESSION OF THE CENTRAL NERVOUS SYSTEM. SKIN
CONTACT: MAY CAUSE IRRITATION. EYE CONTACT: MAY CAUSE IRRITATION.
PROLONGED OR REPEATED CONTACT MAY CAUSE DERMATITIS. MAY CAUSE SKIN
IRRITATION ON PROLONGED OR REPEATED CONTACT.

Effects of Overexposure:INHALATION:

IRRITATION OF RESPIRATORY TRACT,

NAUSEA, DIZZINESS, HEADACHE, AND DEPRESSION OF THE CENTRAL NERVOUS
SYSTEM, IRREGULAR HEARTBEAT. MISUSE OF THIS PRODUCT BY DELIBERATELY
CONCENTRATING AND INHALING CAN BE HARMFUL OR FATAL. INGESTION:
GASTROINTESTINAL IRRITATION AND DEPRESSION OF THE CENTRAL NERVOUS
SYSTEM. SKIN: IRRITATION. EYE CONTACT: IRRITATION. PROLONGED OR
REPEATED CONTACT MAY CAUSE DERMATITIS. MAY CAUSE SKIN IRRITATION
ON PROLONGED OR REPEATED CONTACT.

Medical Con

d Aggravated by Exposure:NONE RECOGNIZED.

=====
===== First Aid Measures =====

First Aid:INHALATION: IF USER EXPERIENCES BREATHING DIFFICULTY, MOVE TO
AIR FREE OF VAPORS. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION
UNTIL MEDICAL ASSISTANCE CAN BE RENDERED. INGESTION: DO NOT INDUCE
VOMITING. CALL POISON CONTROL CENTER, HOSPITAL, EMERGENCY ROOM OR
PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH WITH SOAP AND WATER. EYE
CONTACT: FLUSH WITH LARGE QUANTITIES OF WATER.

TITLES OF WATER FOR AT LEAST 15
MINUTES. IF IRRITATION FROM CONTACT PERSISTS, GET MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:FLAMMABLEAEROSOL

Extinguishing Media:USE CARBON DIOXIDE, DRY POWDER OR FOAM.

Fire Fighting Procedures:SELF-CONTAINED RESPIRATORY PROTECTION SHOULD
BE PROVIDED FOR FIREFIGHTERS FIGHTING FLAMES IN BUILDINGS OR
CONFINED AREAS. STORAGE CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT
COOL WITH WATER SPRAY
TO PRE VENT PRESSURE BUILD-UP.

Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESSURE. DO NOT PUNCTURE,
INCINERATE OR STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED
EXPOSURE TO SUN MAY CAUSE BURSTING. ISOLATE FROM HEAT, ELECTRICAL
EQUIPMENT, SPARKS, OPEN FLAME S AND HOT SURFACES. EXTREMELY
FLAMMABLE AEROSOL - DOT CONSUMER COMMODITIES ORM-D.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS, VENTILATE AREA. FLUS
H

LARGE SPILLS OF MATERIAL INTO SUITABLE RETAINING AREA OR CONTAINERS
WITH LARGE QUANTITIES OF WATER. SMALL SPILL CAN BE ABSORBED BY
APPROPRIATE INERT ABSOR BENT.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE NEAR FLAMES OR AT
ELEVATED TEMPERATURES.

Other Precautions:READ CAREFULLY ALL CAUTIONS AND DIRECTIONS ON PRODUCT
LABEL BEFORE USE. SINCE EMPTY CONTAINER RETAINS RESIDUE, FOLLOW ALL
LABEL WARNING EV
EN AFTER CONTAINER IS EMPTY. DISPOSE OF EMPTY
CONTAINER ACCORD ING TO LOCAL REGULATIONS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR OSHA CONTROLLED WORK PLACE, USE ONLY WITH
ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED
TO PROVIDE MAXIMUM APPROPRIATE TLV. FOR OCCASIONAL USE WHERE
ENGINEERED AIR CONTROL IS NOT FEASIBLE, USE NIOSH APPROVED
RESPIRATORS. FOR OCCASIONAL CONSUMER USE, USE ONLY WITH ADEQUATE

VENTILATION.

Ventilation:PROVIDE ADEQUATE VENTILATION UNDER ENGINEERED AIR CONTROL SYSTEMS DESIGNED TO PROVIDE MAXIMUM APPROPRIATE TLV.

Protective Gloves:USE IMPERMEABLE GLOVES TO PREVENT SKIN IRRITATION.

Eye Protection:SAFETY GLASSES, CHEMICAL GOGGLES &/OR FACE SHIELDS ARE RECOMMENDED

Other Protective Equipment:USUALLY NONE REQUIRED.

Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER USE. BEFORE REUSE, THOROUGHLY CLEAN ANY CLOTHING OR PROTECTIVE EQUIPMENT WHICH HAS BEEN CO

NTAMINATED BY PRIOR USE.

Supplemental Safety and Health

MSDS COVERS PRODUCT NUMBERS #60132 - 5 OZ. / #60133 - 10 OZ.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:=85.C, 185.F

B.P. Text:185F TO 230F

Vapor Density:>AIR

Spec Gravity:7.058 LBS / GAL

Evaporation Rate & Reference:SLOWER THAN ETHER.

Appearance and Odor:10 OZ AEROSOL CAN.

Percent Volatiles by Volume:95%

===== Stability and Reactivity Data =====

Stability Indicat

or/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY PRODUCE HYDROGEN CHLORIDE, HYDROGEN FLUORIDE AND SMALL AMOUNTS OF PHOSGENE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Toxicological Information =====

Toxicological Information:AEROSOL FLAMMABILITY CLASSIFICATION ACCORDING TO ASTM D-3065-77 AND FHSA 1500.45 OSHA: EXTREMELY FLAMMABLE AEROSOL - DOT CONSUMER COMMODITIES ORM-D.

=====

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Information:AEROSOL FLAMMABILITY CLASSIFICATION ACCORDING TO ASTM D-3065-77 AND FHSA 1500 45 OSHA: EXTREMELY FLAMMABLE AEROSOL - DOT CONSUMER COMMODITIES ORM-D.

===== Regulatory Information =====

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.