Product ID: EPOXY COATING KIT MSDS Date:04/02/1991 FSC:8010 NIIN:01-368-5447 Status Code:A MSDS Number: CLFGV === Responsible Party === Company Name: CANTOL, INC. Address:2211 NORTH AMERICAN STREET City:PHILADELPHIA State:PA ZIP:19133-3306 Country:US Info Phone Num:215-425-1966 Emergency Phone Num: (800) 424-9300 Ρ reparer's Name: HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300 CAGE:58380 === Contractor Identification === Company Name: CANTOL, INC. Address:2211 NORTH AMERICAN STREET Box:City:PHILADELPHIA State:PA ZIP:19133-3306 Country:US Phone:215-425-1966 CAGE:58380

Ingred Name:TETRAETHYLENEPENTAMINE CAS:112-57-2 RTECS #:KH8585000 > Wt:1.

Ingred Name:2,4,6-TRIS.(.(DIMETHYLAMINO)METHYL.).PHENOL CAS:90-72-2 RTECS #:SN3500000 &It; Wt:1. Ingred Name:REACTION PRODUCTS OF EPICHLOROHYDRIN & BISPHENOL A & gt; Wt:1.

Ingred Name:EPICHLOROHYDRIN - POLYGLYCOL REACTION PRODUCT > Wt:1.

Ingred Name:TETRAETHYLENEPENTANINE, TALL OIL FATTY ACID AMIDO AMINE > Wt:1.

Routes of Entry: Inhalation:YES Skin:UNKNOWN Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: CAUSES EYE AND SKIN IRRITATION. INGESTION: HA

RMFUL IF SWALLOWED. INHALATION: PROLONGED INHALATION CAN CAUSE DIZZINESS, NAUSEA.

Effects of Overexposure:EYES: IRRITATION, REDNESS. SKIN: REDNESS. INHALATION: PROLONGED INHALATION CAN CAUSE DIZZINESS, NAUSEA. Medical Cond Aggravated by Exposure:NONE KNOWN

First Aid:EYES: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.
SEEK MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR.
INGESTION: DO NOT INDUCE VOMITING. DRINK LARGE QUANTI TIES OF WATER. CALL A PHYSICIAN. CONTAINS ALKALINE AMINES AND EPOXY RESINS.

Flash Point:NONE Extinguishing Media:WATER, FOG, FOAM, CARBON DIOXIDE, DRY CHEMICAL Fire Fighting Procedures:TOXIC VAPOR SUCH AS CARBON MONOXIDE MAY BE RELEASED DURING FIRE; RESPIRATORY PROTECTION SHOULD BE PROVIDED. Unusual Fire/Explosion Hazard:NONE

====== Accidental Re

lease Measures ================

Spill Release Procedures: SCOOP UP AND RECOVER FOR REUSE OR MIX OIL ABSORBENT MATERIAL AND DISPOSE.

Handling and Storage Precautions: KEEP CONTAINER CLOSED. AVOID CONTACT
 WITH EYES, SKIN, AND CLOTHING. KEEP OUT OF THE REACH OF CHILDREN.
 Other Precautions: FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY. READ AND
 FOLLOW ALL LABEL DIRECTIONS AND PRECAUTIONS BEFORE USING.

Respiratory Protection:USE WITH ADEQUATE VENTILATION Ventilation:NORMAL VENTILATION Protective Gloves:RUBBER, NEOPRENE, PLASTIC Eye Protection:EYE GOGGLES Other Protective Equipment:NONE Work Hygienic Practices:WASH THOROUGHLY BEFORE HANDLING. Supplemental Safety and Health

Spec Gravity:1.4 Solubility in Water:SLIGHT Appearance and Odor:WHITE RESIN BASE AND BLACK HARDENER WIT H AMINE ODOR

Stability Indicator/Materials to Avoid:YES ACIDS. DO NOT MIX WITH OTHER CHEMICALS. Stability Condition to Avoid:NONE Hazardous Decomposition Products:BURNING MAY YIELD CARBON MONOXIDE, CARBON DIOXIDE.

Waste Disposal Methods:DISPOSE OF USED ABSORBENT IN PROPER RECEPTACLE FOR LANDFILL. THIS MATERIAL IS NOT AN EPA HAZARDOUS WASTE.

Disclai

mer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.