

3M CO, ELECTRICAL PRODUCTS DIV. -- SCOTCHCAST BRAND ELECTRICAL RESIN 251, PART B
(SEE SUPPL) -- 5970-00-900-4414

===== Product Identification =====

Product ID:SCOTCHCAST BRAND ELECTRICAL RESIN 251, PART B (SEE SUPPL)

MSDS Date:08/24/1992

FSC:5970

NIIN:00-900-4414

Status Code:A

Kit Part:Y

MSDS Number: CLFLB

=== Responsible Party ===

Company Name:3M CO, ELECTRICAL PRODUCTS DIV.

Address:3M CENTER OF

FICES, 3M CENTER

Box:2963

City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

Resp. Party Other MSDS Num.:10-2596-4

CAGE:75037

=== Contractor Identification ===

Company Name:DUTCH VALLEY SUPPLY CO

Address:970 PROGRESS CTR AVE

Box:City:LAWRENCEVILLE

State:GA

ZIP:30043

Country:US

Phone:(404-513-0612)

CAGE:31068

Company Name:LAMINATED MATERIALS CORP.

Address:162 W LIPPINCOTT ST

Box:6710

City:PHILADELPHIA

State:PA

ZIP:19133-4221

Country:US

Pho

ne:215-425-4100
Contract Num:SP0430-99-M-TK42
CAGE:20200
Company Name:MINNESOTA MINING AND MFG CO ELECTRICAL PRODUCTS DIV
Address:3M AUSTIN CTR
Box:City:AUSTIN
State:TX
ZIP:78769-2963
Country:US
Phone:512-984-1800
CAGE:75037

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC (CONTAINING ASBESTOS)
CAS:14807-96-6
RTECS #:MW2700000
Minumum % Wt:35.
Maxumum % Wt:45.
Other REC Limits:NONE RECOMMENDED
OSHA PEL:0.2 FIBERS/CC
ACGIH TLV:0.2 FIBERS/CC; 9394

Ingred Nam
e:HEXAHYDROPTHALIC ANHYDRIDE
CAS:85-42-7
Minumum % Wt:25.
Maxumum % Wt:30.
Other REC Limits:NONE RECOMMENDED

Ingred Name:ORGANIC ACIDS ANHYDRIDE
Minumum % Wt:20.
Maxumum % Wt:30.
Other REC Limits:NONE RECOMMENDED

Ingred Name:2,4,6-TRIS(DIMETHYLAMINO METHYL) PHENOL
CAS:90-72-2
RTECS #:SN3500000
Minumum % Wt:.1
Maxumum % Wt:1.
Other REC Limits:NONE RECOMMENDED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health H

azards Acute and Chronic: EYES: CORROSIVE. SKIN: ALLERGIC SKIN REACTION, MODERATE SKIN IRRITATION. MAY BE ABSORBED THROUGH THE SKIN. INHALATION: ALLERGIC RESPIRATORY REACTION, CENTRAL NERVOUS SYSTEM DEPRESSION, IRRITATION OF THE UPPER RESPIRATORY TRACT. INGESTION: IRRITATION OF GASTROINTESTINAL TISSUES.

Effects of Overexposure: SKIN: REDNESS, SWELLING, BLISTERING, & ITCHING. DRYNESS. INHALATION: DIFFICULTY BREATHING, WHEEZING, TIGHTNESS OF CHEST & RESPIRATORY FAILURE.

HEADACHE, DIZZINESS, DROWSINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS & UNCONSCIOUSNESS. SORENESS OF THE NOSE & THROAT, COUGHING & SNEEZING. INGESTION: PAIN, VOMITING, ABDOMINAL TENDERNESS, NAUSEA, BLOOD IN VOMITUS, AND BLOOD IN FECES.

=====
First Aid Measures
=====

First Aid: EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET IMMEDIATE MEDICAL ATTENTION. SKIN

: FLUSH

SKIN WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION: IF SIGNS/SYMPTOMS OCCUR, REMOVE PERSON TO FRESH AIR, IF SIGNS/SYMPTOMS CONTINUE, CALL A PHYSICIAN. INGESTION: DRINK TWO GLASSES OF WATER. CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point Method: CC

Flash Point: >148.9C, 300.F

Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: WEAR FULL PROTECTIVE CL

OTHING, INCLUDING

HELMET, SELF-CONTAINED, POSITIVE PRESSURE OR PRESSURE DEMAND BREATHING APPARATUS, BUNKER COAT AND PANTS, BANDS AROUND ARMS, WAIST & LEGS, FACE MASK, & PROTECTIVE COVERING FOR EXPOSED AREAS OF THE HEAD.

Unusual Fire/Explosion Hazard: NONE KNOWN.

=====
Accidental Release Measures
=====

Spill Release Procedures: OBSERVE ALL PRECAUTIONS GIVEN. APPLY ABSORBENT MATERIAL TO SPILL AREA. COLLECT AND PLACE IN CLOSABLE CONTAINER.

=====

===== **Handling and Storage**=====

Handling and Storage Precautions:KEEP OUT OF THE REACH OF CHILDREN.
Other Precautions:DO NOT INGEST.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:SELECT ONE OF THE FOLLOWING NIOSH APPROVED
RESPIRATORS BASED ON AIRBORNE CONCENTRATIONS OF CONTAMINANTS & IN
ACCORDANCE WITH OSHA REGULATIONS: HALF-MASK ORGANIC VAPOR
RESPIRATOR.

Ventilation:USE WITH APPROPRIATE LOCAL EXHAUST VENTILAT
ION. PROVIDE
APPROPRIATE LOCAL EXHAUST FOR HEAT CURING. USE RESPIRATORY
PROTECTION IF NEEDED.

Protective Gloves:WEAR APPROPRIATE GLOVES.

Eye Protection:WEAR UNVENTED GOGGLES.

Other Protective Equipment:USE ONE OR MORE OF THE FOLLOWING PERSONAL
PROTECTION ITEMS AS NECESSARY TO PREVENT SKIN CONTACT: APRON,
COVERALLS.

Supplemental Safety and Health

THIS MSDS IS FOR ONE PART OF A KIT (SCOTCHCAST BRAND ELECTRICAL RESIN
251). THE HMIS SERIAL NUMBERS FOR ALL PARTS OF THIS KIT

(INCLUDING THE ONE FOR THIS MSDS) ARE: CLFKZ & CLFLB.

===== **Physical/Chemical Properties**=====

HCC:V5

Spec Gravity:1.48

Viscosity:100 POISE

Solubility in Water:NEG

Appearance and Odor:BUFF VISCOUS LIQUID, PUNGENT ODOR

Percent Volatiles by Volume:0

===== **Stability and Reactivity Data**=====

Stability Indicator/Materials to Avoid:YES
NONE

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN AN INDUSTRIAL OR COMMERCIAL FACILITY. DISPOSE OF COMPLETELY ABSORBED WASTE PRODUCT IN A SANITARY LANDFILL. DISPOSE OF COMPLETELY CURED (OR POLYMERIZED) MATERIAL IN A SANITARY LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.