

AKZO COATINGS -- PAINT IMITATION SILVER 412-0105 L107 2AHK33442 -- 8010-01-344-5119

=====
Product Identification
=====

Product ID:PAINT IMITATION SILVER 412-0105 L107 2AHK33442

MSDS Date:09/01/1992

FSC:8010

NIIN:01-344-5119

Status Code:A

MSDS Number: CLJGD

=== Responsible Party ===

Company Name:AKZO COATINGS

Address:1845 MAXWELL STREET

City:TROY

State:MI

ZIP:48084

Country:US

Info Phone Num:313-63

7-0400

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:2E800

=== Contractor Identification ===

Company Name:AKZO COATINGS

Address:1845 MAXWELL STREET

Box:City:TROY

State:MI

ZIP:48084

Country:US

Phone:313-637-0400

CAGE:2E800

=====
Composition/Information on Ingredients
=====

Ingred Name:STODDARD SOLVENT

CAS:8052-41-3

RTECS #:WJ8925000

Minumum % Wt:40.

Maxumum % Wt:55.

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:525 MG/M3;100 PPM

Ingred Name:ALUMINIUM FLAKE

CAS:7429-90-5

RTECS #:BD0330000

Minumum % Wt:10.

Maxumum % Wt:25.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

=====
===== Hazards Identification =====

Health Hazards Acute and Chronic:ACUTE: 1. EXCESSIVE VAPOR CONCENTRATION IN AIR, ESPECIALLY IN CONFINED SPACES, MAY CAUSE ASPHYXIATION. 2. EXCESSIVE INHALATION OF VAPORS CAN CAUSE NASAL, THROAT, AND RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE AND POSSIBLE UNCONCIOUSNESS. 4. EYE CONTACT WITH LIQUID, VAPOR OR SPRAY MIST CAUSES IRRITATION, REDNESS, TEARING, BLURRED VISION, AND A SENSATION OF SEEING HALOS AROUND LIGHTS. 6. PROLONGED SKIN CONTACT MAY LEAD TO EXTRACTION OF NATURAL OILS WITH RESULTANT DRY SKIN, CRACKING. IRRITATION AND DERMATITIS. 9. SWALLOWING MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA VOMITING AND DIARRHEA.

Medical Cond Aggravated by Exposure:NONE EXPECTED.

=====
===== First Aid Measures =

First Aid:INHALATION: MOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY. SKIN CONTACT: WASH WITH SOAP AND WATER. DO NOT USE ORGANIC SOLVENTS. EYE CONTACT: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN. INGESTION: DRINK ONE OR TWO GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY.

=====
===== Fire Fighting Measures =====

Flash Point:=-40.6C, 105.F

Lower Limits:0.6

Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICALS ARE DESIRABLE. WATER SPRAY IS LESS EFFECTIVE.

Fire Fighting Procedures:WATER SHOULD BE USED TO COOL CONTAINERS EXPOSED TO FIRE. FIRE FIGHTING PERSONNEL SHOULD WEAR SELF-CONTAINING BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED, ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

POSED TO EXTREME HEAT.

APPLICATION TO HOT SURFACES RE QUIRES SPECIAL PRECAUTIONS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS, VENTILATE AREA, REMOVE WITH INERT ABSORBENT USING NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS OUT OF SUN AND AWAY FROM HEAT, SPARKS AND OPEN FLAMES. STORE PLASTIC CONTAINERS OF FLAMMABLE LIQUIDS INSIDE CLOSED, APPROVED CONTAINERS OR SAFETY CABINETS. CLOSE ALL CONTAINERS AFTER EACH USE. CONSULT NFPA AND LOCAL CODES FOR ADDITIONAL STORAGE REQUIREMENTS.

Other Precautions:DO NOT TAKE INTERNALLY. USE APPROVED BONDING AND GROUNDING PROCEDURE WHEN TRANSFERRING LIQUIDS. OBSERVE LABEL PRECAUTIONS. KEEP CLOSURES TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE. NEVER USE PRESS URE TO EMPTY CONTAINER ? DRUM IS NOT A PRESSURE VESSEL

. AVOID BREATHING SANDING DUST. DO NOT WELD OR FLAME CUT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:ADEQUATE VENTILATION IS REQUIRED. USE NIOSH/MSHS APPROVES RESPIRATOR DEVICE. SEE YOUR SAFETY EQUIPMENT SUPPLIER FOR EVALUATION AND RECOMMENDATION. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIRLINE RES PIRATOR OR HOOD.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO KEEP VAPOR CONCENTRATION BELOW THE GIVEN TLV AND PEL.

Protective

Gloves:REQUIRED FOR PROLONGED OR REPEATED CONTACT.

Eye Protection:USE SAFETY EYE GOGGLES DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

Other Protective Equipment:EYE AND BATH SHOWER SHOULD BE AVAILABLE. USE CHEMICAL RESISTANT APRON, BOOTS OR OTHER CLOTHING IF NEEDED TO AVOID REPEATED OR FREQUENT SKIN CONTACT. LIQUID MAY PENETRATE CLOTHING, SHOES AND LEATHER.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING THE WASHROOM, LAUNDER CLOTHING BEFORE REUSE.

Supp

lemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:=148.9C, 300.F
B.P. Text:300-490F
Spec Gravity:1.33
Percent Volatiles by Volume:56

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE REASONABLY FORESEEABLE
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,
OXIDES OF NITROGEN AND SMOKE.

===== Disposal Considerations =====

=

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE,
AND LOCAL POLLUTION REQUIREMENTS RAGS, FILTERS, PAINT SUITS, EMPTY
CANS, ETC., CONTAMINATED WITH PRODUCT MAY BE HAZARDOUS WASTE.
DETERMINE WHETHER CONTAMI NATED PRODUCTS ARE HAZARDOUS BEFORE
DISPOSAL AND DISPOSE OF AS APPROPRIATE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of Ame
rica in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.