

Product ID:AC-236 CLASS B BASE MSDS Date:06/26/2000 FSC:8030 NIIN:00-685-0915 Status Code:A MSDS Number: CLKFH === Responsible Party === Company Name: ADVANCED CHEMISTRY & TECHNOLOGY Address:7341 ANACONDA AVE **City:GARDEN GROVE** State:CA ZIP:92841-2921 Country:US Info Phone Num:714-373-2837 Emergency Phone Num: (800) 424-9300 Preparer's Name: HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300 CAGE:1DWR5 === Contractor Identification === Company Name: ADVANCED CHEMISTRY & TECHNOLOGY Address:7341 ANACONDA AVE Box:City:GARDEN GROVE State:CA ZIP:92841-2921 Country:US Phone:714-373-2837 CAGE:1DWR5

Ingred Name:LIMESTONE CAS:1317-65-3 RTECS #:EV9580000 = Wt:38.5 OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name:CALCIUM CARBONA

ΤE CAS:471-34-1 RTECS #:FF9335000 = Wt:3.

Ingred Name: TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 = Wt:2.5 OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: FORMALDEHYDE CAS:50-00-0 RTECS #:LP8925000 < Wt:.1 OSHA PEL:SEE 1910.1048 ACGIH STEL:C0.37 MG/M3;C0.3 PPM EPA Rpt Qty:100 LBS DOT Rpt Qty:100 LBS

Ingred Name:NON-HAZARDOUS AND OTHER INGREDIENTS BELOW REPORTABLE LEVELS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Health Hazards Acute and Chronic:LUNGS AND RESPIRATORY SYSTEM. Effects of Overexposure: EYE CONTACT: MAY CAUSE MECHANICAL IRRITATION SKIN CONTACT: INCIDENTAL CONTACT IS NOT EXPECTED INHALATION (BREATHING): EXPOSURE IS UNLIKELY INGESTION (SWALLOWING): EXPOSURE IS UNLIKELY, MAY CAUSE N AUSEA, VOMITING, PAIN, AND STOMACH UPSET (E.G., DIARRHEA)

Medical Cond Aggravated by Exposure: LUNGS AND RESPIRATORY SYSTEM

=======

First Aid: EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. SKIN CONTACT: IMMEDIATELY FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHIN G AND SHOES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. PROFESSIONALLY WASH CLOTHING AND SHOES BEFORE RE-USE. INHALATION (BREATHING): REMOVE TO FRESH AIR. IF SYMPTOMS DEVELOP, SEEK IMMEDIATE MEDIC AL ATTENTION. IF NOT BREATHING, GIVE ARTIFICIAL R

ESPIRATION. INGESTION (SWALLOWING): SEEK MEDICAL ATTENTION: IMMEDIATELY INDUCE VOMITING, AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUT H TO AN UNCONSCIOUS PERSON.

Flash Point Method:SCC

Flash Point:>93.3C, 200.F

Extinguishing Media:SMALL FIRES: DRY CHEMICAL, CARBON DIOXIDE, HALON, WATER SPRAY, OR FOAM. LARGE FIRES: WATER SPRAY, FOG, OR ALCOHOL FOAM.

Fire Fighting Procedures: FIRE FIGHTERS AND O

THERS WHO MAY BE EXPOSED TO

THE PRODUCTS OF COMBUSTION SHOULD BE EQUIPPED WITH NIOSH-APPROVED POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS (SCBA) AND FULL PROTECTIVE CLOTHIN G.

Unusual Fire/Explosion Hazard:DURING A FIRE, IRRITATING AND HIGHLY TOXIC GASES MAY BE GENERATED DURING COMBUSTION OR DECOMPOSITION.

Spill Release Procedures: ISOLATE HAZARD AREA. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM

ENTERING. SAFETY STOP DISCHARGE.

CONTAIN MATERIAL, AS NECESSARY, WITH A DIKE OR BARRIER. STOP MATERIAL FROM CONTAMINATING SOIL, OR FROM ENTERING SEWERS OF BODIES OF WATER. APPROPRIATE SAFETY MEASURES AND PROTECTIVE EQUIPMENT SHOULD BE USED. USE SUPPLIED AIR RESPIRATOR OF SELF-CONTAINED BREATHING APPARATUS IN ENCLOSED SPACES.

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA A

WAY FROM HEAT, IGNITION SOURCES, AND DIRECT SUNLIGHT. KEEP CONTAINERS TIGHTLY CLOSES. TRANSFER- NO SPECIAL PRECAUTIONS ARE NEEDED. FOLLOW GOOD MANUFACTURING A ND HANDLING PRACTICES.

Other Precautions: THIS CONTAINER CAN BE HAZARDOUS WHEN EMPTY. FOLLOW LABEL WARNINGS EVEN AFTER CONTAINER IS EMPTIED SINCE EMPTY CONTAINERS MAY RETAIN PRODUCT RESIDUES. DO NOT REUSE EMPTY CONTAINER WITHOUT PROFESSIONAL CLEANING FOR FOOD, CLOTHING, OR PRODUCTS FOR HUMAN OR ANIMAL CONSUMPTION OR WHERE SKIN CONTACT CAN O CCUR.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: AVOID BREATHING VAPOR OR MIST. WEAR NIOSH/MSHA-APPROVED EQUIPMENT. DETERMINE THE APPROPRIATE TYPE BY CONSULTING THE RESPIRATOR MANUFACTURER. HIGH AIRBORNE CONCENTRATION MAY NECESSITATE THE USE OF SELF CONTAINED BREATHING APPARATUS (SCBA) OR A SUPPLIED AIR RESPIRATOR. RESPIRATORY PROTECTION PROGRAMS MUST BE IN COMPLIANCE WITH 29 CFR 1910.134 Ventila

tion:LOCAL EXHAUST VENTILATION WHEN VAPORS, MISTS, OR DUSTS CAN BE RELEASED IN EXCESS OF ESTABLISHED AIRBORNE EXPOSURE LIMITS (TLV'S OR PEL'S)

Protective Gloves: WEAR PROTECTIVE CLOTHING AND APPROPRIATE IMPERVIOUS GLOVES.

Eye Protection:WEAR CHEMICAL SPLASH GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE EATING, DRINKING, SMOKING, AND USING RESTROOM FACILITIES. Supplemental Safety and Health

Spec Gravity:1.61 VOC Pounds/Gallon:48 VOC Grams/Liter:.4 Solubility in Water:INSOLUBLE Appearance and Odor:OFF-WHITE PASTE AND SULFIDE ODOR

Stability Indicator/Materials to Avoid:YES OXIDIZERS, ACIDS Stability Condition to Avoid:HIGH TEMPERATURES Hazardous Decomposition Products:SMOKE, SOOT, AND TOXIC/IRRITATING FUMES (I.E., CARBON DIOXIDE, CARBON MONOXIDE, ETC). FOR MALDEHYDE AND/OR OTHER ALDEHYDES. OXIDES OF NITROGEN, METALLIC OXIDES.

Toxicological Information:LIMESTONE REPEATED EXPOSURE TO DUST CAN LEAD TO PARTICULATE IN THE LUNGS (I.E., PNEUCONIOSIS). CAN CONTAIN TRACE AMOUNTS OF CRYSTALLINE SILICA AS AN IMPURITY. CALCIUM CARBONATE: REPEATED EXPOSURE TO DUSTS CAN LEAD TO PARTICULATE IN THE LUNGS (I.E., PNEUCONIOSIS). TITANIUM DIOXIDE: IN A 2 YEAR STUDY, AN I NCREASE IN BENIGN AND MALIGNANT LUNG TUMORS WERE OBSERVED AT 250-MG/M3 RESPIRABLE DUST LEVE L. THIS LEVEL IS 50 TIMES THE CURRENT OCCUPATIONAL EXPOSURE LEVEL AND IS NOT EXPECTED TO CORRELATE TO HUMAN EXPOSURES. FORMALDEHYDE: SEVERELY IRRITATING TO THE EYES, SKIN, AND RESPIRATORY TRACT.

Waste Disposal Methods:DISPOSE OF ACCORDING TO APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS OF THE METHODS OF DISPOSAL CURRENTLY

AVAILABLE, IT IS RECOMMENDED THAT AN ALTERNATIVE BE ACCORDING OR THE FOLLOWING ORDER OF PRE FERENCE. BASED UPON ENVIRONMENTAL ACCEPTABILITY. (1) RECYCLE OR REWORK, IF FEASIBLE; (2) INCINERATE AT AN AUTHORIZED FACILITY.

SARA Title III Information:SARA SECTION 302 EXTREMELY HAZARDOUS MAT FORMALDEHYDE SARA SECTION 313 TOXIC CHEMICALS FORMALDEHYDE Federal Regulatory Information:UNITED STATES CH EMICAL COMPONENTS THIS

PRODUCT ARE ON THE SECTION 8(B) CHEMICAL SUBSTANCE INVENTORY LIST (40 CFR 710)

State Regulatory Information:STATE RIGHT TO KNOW PENNSYLVANIA-NEW JERSEY R-T-K LIMESTONE 1317-65-3 38.5% CALCIUM CARBONATE 474-34-1 3% TITANIUM DIOXIDE 13463-67-7 2.5% FORMALDEHYDE 50-00-0