View NSN Online: https://aerobasegroup.com/nsn/8010-00-459-1756

CAAP CO INC -- CAAPCOAT B-274 BLACK POLYURETHANE RAIN EROSION COATING PER 8010-00-459-1756

============= Product Identification ==================

Product ID:CAAPCOAT B-274 BLACK POLYURETHANE RAIN EROSION COATING PER

MSDS Date:05/01/2000

FSC:8010

NIIN:00-459-1756

Status Code:A

MSDS Number: CLKKJ === Responsible Party ===

Company Name: CAAP CO INC Address: 152 PEPE'S FARM RD

City:MILFORD

State:CT ZIP:06460 Country:US

Info Phone Num:203-877-0375

Emergency Phone Num:(800)424-9300 Preparer's Name:HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300

CAGE:60922

=== Contractor Identification === Company Name:CAAP CO INC Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT ZIP:06460 Country:US

Phone:203-877-0375

CAGE:60922

======= Composition/Information on Ingredients ========

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:44.15

ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qt

y:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:MIBK CAS:108-10-1

RTECS #:SA9275000

= Wt:15.98

OSHA PEL:410 MG/M3;100 PPM ACGIH TLV:205 MG/M3;50 PPM ACGIH STEL:307 MG/M3;75 PPM

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

= Wt:.05

OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3

Ingred Name: METHYLENEBIS (4-CYCLOHEXYL ISOCYANATE)

CAS:5124-30-1

RTECS #:HQ9250000

Minumum % Wt:0.

Maxumum % Wt:.5

ACGIH TLV:0.054 MG/M3;.005 PPM

Ingred Name: ISOCYANTE TERMINATE

D POLYESTER PREPOLYMER

CAS:54954-83-5

= Wt:39.82

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: CONTACT MAY DAMAGE EYES.

IRRITATE SKIN, AND CAUSE RESPIRATORY IRRITATION UPON INHALATION.

CHRONIC: REPEATED OR PROLONGED EXPOSURE MAY CAUSE DEFATTING OF THE

SKIN, DERMATITIS AND POSSIBLE SENSIT IZATION. INHALATION OF VE

RY

HIGH VAPOR CONCENTRATIONS OR PROLONGED EXPOSURE MAY CAUSE NEURAL DYSFUNCTION, KIDNEY AND LIVER DAMAGE.

Effects of Overexposure: VAPOR EXPOSURE: BURNING EYES: HEADACHE, DIZZINESS, THROAT IRRITATION, LOSS OF APPETITE, NAUSEA. MAY CAUSE IRRITATION OF SKIN OR EYES.

Medical Cond Aggravated by Exposure: PREEXISTING ALLERGIES, EYE, SKIN, AND RESPIRATORY DISORDERS.

First Aid:EYES: FLUSH WITH WATER. GET IMMEDIATE MEDICAL ATTENTION.

SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN PROMPTLY WITH SOAP AND WATER. IF SIGNS AND SYMPTOMS OF EXPOSURE EXIST, GET IMMEDIATE MEDICAL ATT ENTION. INHALATION: REMOVE TO FRESH AIR, GIVE ARTIFICIAL RESPIRATION IF NECESSARY, GET IMMEDIATE ATTENTION. INGESTION: DO NOT INDUCE VOMITING, GET IMMEDIATE MEDICAL ATTENTION, IF VOMITING OCCURS SPO NTANEOUSLY, KEEP VICTIM?S HEAD BELOW HIS HIPS TO PREVENT BREATHING VOMITUS INTO LUNGS.

= Fire Fighting Measures ==========

Flash Point Method:TOC Flash Point:=20.C, 68.F Lower Limits:1.0

Upper Limits:1.0

Extinguishing Media:CO2, FOAM, DRY CHEMICAL.


Fire Fighting Procedures:UNUSUAL METHODS FOR FLAMMABLE LIQUIDS. THE PRODUCT IS NOT MISCIBLE WITH WATER, ALTHOUGH WATER MAY BE USED TO FIRE EXPOSED CONTAINERS. FIREFIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS, IN AD DITION TO PROTECTIVE CLOTHING, INCLUDING SOLVENT RESISTANT COATS, BOOT, GLOVES, AN

D HELMET.

Unusual Fire/Explosion Hazard: NONE, PRODUCT IS A FLAMMABLE LIQUID.

======== Accidental Release Measures ===========

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION AND DO NOT SMOKE IN THE AREA. WEAR PROTECTIVE EQUIPMENT INCLUDING SOLVENT RESISTANT GLOVES, APRON, BOOTS, AND A SELF CONTAINED APPARATUS IN THE PRESSURE DEMAND OR A POSI TIVE PRESSURE AIR SUPPLIED RESPIRATOR. CONTAIN THE SPILL WITH DIKES OF ABSORBENT MATERIAL AND SOAK UP THE S



PILL WITH THE ABSORBENT MATERIAL. CLEAN UP ABSORBENT

Stability Indicator/Materials to Avoid:YES
THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXI

DIZING AGENTS.

Stability Condition to Avoid: KEEP AWAY FROM ALL IGNITION SOURCES, HOT SURFACES, AND TEMPERATURES ABOVE 100F.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF NITROGEN, AS WELL AS NITROGEN, AS WELL AS TRACES OF HCN MAY BE RELEASED DURING COMBUSTION.

======= Disposal Considerations ===========

Waste Disposal Methods:INCINERATION IN AN APPROPRIATE DESIGNED AND LICENSED; THIS IS A RCRA HAZARDOUS IGNITABLE WASTE. REGULATIONS MAY

VARY FROM STATE TO STATE; DISPOSE OF ACCORDING TO STATE, LOCAL, AND FEDERAL REGULATIONS.

State Regulatory Information:MIBK, MEK, XYLENE: MA, PA RIGHT-TO-KNOW. METHYLENE
BIS (4-CYCLOHEXYLISOCYANTE): MA, NJ, PA
RIGHT-TO-KNOW.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Am erica in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.