View NSN Online: https://aerobasegroup.com/nsn/5930-01-366-0049

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- EPOXY RESIN COMPOUND PR1829 B-1/2 ACCELERATOR -- 8030-01-366-0049

Product ID:EPOXY RESIN COMPOUND PR1829 B-1/2 ACCELERATOR

MSDS Date:09/24/1998

FSC:8030

NIIN:01-366-0049 Status Code:A

MSDS Number: CLKMB === Responsible Party ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address

:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:(800)424-9300 Preparer's Name:HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

======= Composition/Information on Ingredients ========

Ing

red Name:EPOXY RESIN = Wt:40.

Ingred Name: EPOXY RESIN

CAS:28064-14-4

= Wt:25.

Ingred Name: CALICIUM CARBONATE @ LIMESTONE

CAS:1317-65-3

RTECS #:EV9580000

= Wt:25.

OSHA PEL:15 MG/M3 ACGIH TLV:10 MG/M3

Ingred Name: CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

< Wt:5.

OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3

Ingred Name: ORGANOSILANE ESTER

CAS:2530-83-8

RTECS #:VV4025000


< Wt:5.

Ingred Name: SILICA DERIVATIVES

CAS:67762-90-7

========= Hazards Identification ==============

Effects of Overexposure:EPOXY RESIN EYES: IRRITATING SKIN: IRRITANT.
MAY CAUSE SKIN SANITIZATION INHALATION: NONE INGESTION: LOW ORDER
OF ACUTE ORAL TOXICITY EPOXY RESIN EYES: MAY CAUSE SLIGHT
TRANSIENT (TEMPORARY) EYE IRRITATION SKIN: PROLONGED OR REPEATED
EXPOSURE MAY CAUSE SKIN IRRITATION. MAY RARELY CAUSE AN ALLERGIC
SKIN REACTION. INHALATION: AT ROOM TEMPERATURE, EXPOSURES TO
VAPORS ARE UNLIKELY TO PHYSICAL PROPERTIES; HIGHER TEMPERATURES
MAY GENERATE



Protective Equipment:NONE KNOWN Supplemental Safety and Health

======== Physical/Chemical Properties ===========

Boiling Pt:=260.C, 500.F B.P. Text:500-554F Vapor Density:>AIR Spec Gravity:1.37 VOC Pounds/Gallon:18

Evaporation Rate & Evaporation R

Appearance and Odor:BLACK PASTE

Percent Volatiles by Volume:0

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG AMINES Stability Condition to Avoid :NOT KNOWN

Hazardous Decomposition Products:OXIDES OF CARBON, ALSO OXIDES OF SILICON MAY BE EVOLVED.

======= Disposal Considerations ==========

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA REGULATIONS. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL TO DISPOSAL OF SPILLAGE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United Stat es of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.