

HENTZEN COATINGS INC -- 16440 GRAY ZENTHANE PLUS, MIL-PRF-85285C, TYPE I --  
8010-01-285-3046

===== Product Identification =====

Product ID:16440 GRAY ZENTHANE PLUS, MIL-PRF-85285C, TYPE I

MSDS Date:08/31/1998

FSC:8010

NIIN:01-285-3046

Status Code:A

MSDS Number: CLKNG

=== Responsible Party ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Info Phone Num:414-353-4200

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

===== Composition/Information on Ingredients =====

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

= Wt.:12

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG

/M3

Ingred Name:HOMOPOLMER OF HEXAMETHYLENE DIISOCYANATE

CAS:28182-81-2

Code:F

RTECS #:NQ9170000

Minumum % Wt:20.

Maxumum % Wt:30.

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Minumum % Wt:30.

Maxumum % Wt:40.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:METHYL PROPYL KETONE

CAS:107-87-9

RTECS #:SA7875000

Minumum % Wt:5.

Maxumum % Wt:10.

OSHA PEL:700 MG/M3;200 PPM

ACGIH TLV:705 MG/M3;200 PPM

ACGIH STEL:881 MG/M3;250 PPM

Ingred Name:HEXAMETHYLENE DIISOCYANATE

CAS:822-06-0

RTECS #:MO1740000

= Wt:.07

ACGIH TLV:0.034 MG/M3;.005 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:1.27

OSHA PEL:100 PPM

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:1,2,4-TRIMETHYLBENZENE

CAS:95-63-6

RTECS #:DC3325000

&lt; Wt:0.

OSHA PEL:25 PPM

Ingred Name:AROMATIC HYDROCARBONS

CAS:64742-95-6

Code:F

RTECS #:WF3400000

Minumum % Wt:10.

Maxumum % Wt:15.

Ingred Name:METHYL AMYL KE

TONE  
CAS:110-43-0  
RTECS #:MJ5075000  
Minumum % Wt:5.  
Maxumum % Wt:10.  
OSHA PEL:465 MG/M3;100 PPM  
ACGIH TLV:233 MG/M3;50 PPM

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:HARMFUL IF INHALED. MAY CAUSE THE  
FOLLOWING EFFECTS: NOSE, THROAT AND RESPIRATORY TRACT, IRRITATION.  
ALLERGIC RESPIRATORY REACTION. MAY CAUSE LUNG DAMAGE. EYE AND SKIN  
IRRITATION. ALLERGIC SKIN REACTI ON

Explanation of Carcinogenicity:THIS PRODUCT HAS NOT BEEN TESTED AS A  
WHOLE FOR CARCINOGENICITY. CONTAINS CARBON BLACK WHICH HAS BEEN  
LISTED BY IARC AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B) BASED UPON  
LABORATORY ANIMAL INHALATION S TUDIES.

Effects of Overexposure:EYE CONTACT: WITH LIQUID VAPORS CAUSING  
TEARING, REDDENING AND SWELLING ACCOMPANIED BY A STINGING. SKIN  
CONTACT: SYMPTOMS MAY BE REDDENING, RASH, SWELLING, SCALING OR  
BLISTERING. INHALATION: STEPS IF SEVERE OV  
EREXPOSURE IS CONTINUED:  
HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION OR UNCONSCIOUSNESS.  
INGESTION: CAN RESULT IN CORROSIVE ACTION IN THE MOUTH, STOMACH  
TISSUE AND DIGESTIVE TRACT

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY  
AILMENTS; SKIN ALLERGIES AND ECZEMA.

=====  
===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LOW PRESSURE LUKE WARM RUNNING WATER  
FOR AT LEAST 15 MINUTES. SKIN CONTACT: WASH AFFECTED  
AREAS  
THOROUGHLY WITH SOAP AND WATER. INMHALATION: MOVE TO AN AREA FREE  
FROM RISK OF FURTHER EXPOSURE. INGESTION: CALL A PHYSICIAN  
IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point Method:CALC  
Flash Point:=7.8C, 46.F  
Autoignition Temp:Autoignition Temp Text:NONE  
Lower Limits:.90  
Upper Limits:8.70  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM OR ALCOHOL FOAM.  
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING SELF

CONTAINED BREATHING APPARATUS SHOULD BE WORN.

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT MATERIAL IN OPEN CONTAINERS ADD FURTHER AMOUNTS OF DECONTAMINATION SOLUTION.

===== Handling and Storage =====

Handling and Storage Precautions:PRECAUTIONS MUST BE TAKEN SO THAT PERSONS HANDLING THIS PRODUCT DO NOT BREATHE THE VAPORS OR HAVE IT CONTACT THE EYES OR SKIN. STORAGE: KEEP CONTAINERS TIGHTLY CLOSED AND PROTECT FROM MOISTURE CONTAMINATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR-PURIFYING CHEMICAL CARTRIDGE RESPIRATORS.  
Ventilation:EXHAUST VENTILATION.  
Protective Gloves:PERMEATION RESISTANT GLOVES.  
Eye Protection:SPLASH GUARDS OR SIDE SHIELDS. A FULL FACE SHIELD MAY BE APPROPRIATE.  
Other Protective Equipment:SAFETY SHOWERS AND EYE WASH STATIONS SHOULD BE AVAILABLE.  
Supplemental Safety and Health

=====  
=== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:LO-213.00-HI-418 F  
Vapor Pres:27.800  
Vapor Density:4.800  
Spec Gravity:1.2960  
VOC Pounds/Gallon:440  
VOC Grams/Liter:3.68  
Evaporation Rate & Reference:2.3000 (N-BUTYL ACETATE=1  
Solubility in Water:REACTS WITH WATER  
Appearance and Odor:LIQUID OPAQUE LIQUID SOLVENT ODOR  
Percent Volatiles by Volume:51.857

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
EPOXY

CATALYSTS, ALCOHOLS, GLYCOL ETHERS, BASES, METAL COMPLEXES OR OTHER ACTIVE MATERIALS. CARBON DIOXIDE GAS COULD BUILD UP IN THE CONTAINER RESULTING IN RAPID DEPRESSURIZATION.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, CHLORINE, HYDROGEN CHLORIDE AND POSSIBLE CYANIDE, HEXAMETHYLENE DIISOCYANATE.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH APPLICABLE LAWS AND REGULATIONS.

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use.

e. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.