

LASTING PAINTS INC. -- LA ARCH A/SG P BSE FS 2-250 -- 8010-00-597-8195

=====
Product Identification
=====

Product ID:LA ARCH A/SG P BSE FS 2-250

MSDS Date:12/02/1985

FSC:8010

NIIN:00-597-8195

Status Code:A

MSDS Number: CLKNY

=== Responsible Party ===

Company Name:LASTING PAINTS INC.

Address:200 S FRANKLINTOWN RD

City:BALTIMORE

State:MD

ZIP:21223-2038

Country:US

Emergency Phone Num:410-947-6306

Pr

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:35178

=== Contractor Identification ===

Company Name:LASTING PAINTS INC.

Address:200 S FRANKLINTOWN RD

Box:City:BALTIMORE

State:MD

ZIP:21223-2038

Country:US

CAGE:35178

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC DISTILLATE (STODDARD)

CAS:8052-41-3

Code:F

RTECS #:WJ8925000

= Wt:25.5

OSHA PEL:2900 MG/M3;500 PPM

ACGIH TLV:525 MG/M3;100 PPM

=====
Hazards Identification
=====

=====
Effects of Overexposure:VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAN CAUSE EYE, SKIN, NOSE AND THROAT IRRITATION.

Medical Cond Aggravated by Exposure:EXCESSIVE INHALATION BY PERSONS WITH PRE-EXISTING RESPIRATORY CONDITIONS COULD HAVE THE PROBLEM ADDITIONALLY AGGRAVATED.

=====
First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. (EYES):

FLUSH WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. INGESTION: DRINK 1 OR 2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING.

=====
Fire Fighting Measures =====

Flash Point Method:CALC

Flash Point:=-43.3C, 110.F

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media:FOAM CO2 DRY CHEMICAL WATER FOG USE ANY CLASS B APPROVED FIRE EXTINGUISH ER.

Fire Fighting Procedures:WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP AND EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. HEAT APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

=====
Accidental Release Measures =====

Spill Release Procedures:USE SCOOP ON LARGE SPILLS AND ABSORBENT MATERIAL ON SMALL SPILLS.

=====
Handling and Storage =====

Handling and Storage

Precautions:KEEP CLOSURE TIGHT AND CONTAINER UPRIGHT TO PREVENT LEAKAGE.

Other Precautions:AVOID EYE AND SKIN CONTACT AND CONSTANT BREATHING OF VAPOR OR SPRAY MIST.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AIR LINE TYPE RESPIRATOR.

Ventilation:VENTILATION SHOULD ALSO BE PROVIDED.

Protective Gloves:USE NEOPRENE OR OTHER IMPERVIOUS TYPE GLOVES.

Eye Protection:USE GOGGLES OR SIDE SHIELD SPECTACLES.

Other Protective Equipment:HAVE EYE WASH STATION AND SAFETY SHOWERS AVAILABLE.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:323.00 TO390.00 DEG F

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Density:HEAVIER

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:NONE

Percent Volatiles by Volume:44.89%

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT AND OPEN FLAME.

Hazardous Decomposition Products:CARBON MONOXIDE AND OTHER ORGANIC MATERIALS MAY BE FORMED DURING COMBUSTION.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE DONE IN ACCORDANCE WITH FEDERAL STATE AND LOCAL REGULATIONS.

Disclaimer (provided

with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.