View NSN Online: https://aerobasegroup.com/nsn/6550-01-449-4657

SHANDON INC DBA SHANDON LIPSHAW -- 230034, EA-65 -- 6550-01-449-4657

============ Product Identification ==============

Product ID:230034, EA-65 MSDS Date:07/09/1998

FSC:6550

NIIN:01-449-4657 Status Code:A

MSDS Number: CLKVR === Responsible Party ===

Company Name: SHANDON INC DBA SHANDON LIPSHAW

Address:171 INDUSTRY DRIVE

City:PITTSBURGH

State:PA ZIP:15275 Country:US

Info Phone Num:412-788-1133 INFO 800-245-6212 Emergency Phone Num:813-979-0626 (CHEM-TEL INC)

CAGE:17602

=== Contractor Identification ===

Company Name: SHANDON INC DBA SHANDON LIPSHAW

Address:171 INDUSTRY DRIVE

Box:City:PITTSBURGH

State:PA ZIP:15275 Country:US

Phone:412-788-1133 INFO 800-245-6212

CAGE:17602

====== Composition/Information on Ingredients ========

Ingred Name:METHANOL

CAS:67-56-1

RTECS #:PC1400000 Minumum % Wt:50. Maxumum % Wt:60.

OSHA PEL:260 MG/M3;200 PPM ACGIH TLV:262 MG/M3;200 PPM ACGIH STEL:328 MG/M3;250 P PM EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name: ETHYLENE GLYCOL

CAS:107-21-1

RTECS #:KW2975000 Minumum % Wt:20. Maxumum % Wt:30.

ACGIH STEL:C127 MG/M3;C50 PPM

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: GLACIAL ACETIC ACID

CAS:64-19-7

RTECS #:AF1225000

< Wt:1.

OSHA PEL:25 MG/M3;10 PPM ACGIH TLV:25 MG/M3;10 PPM ACGIH STEL:37 MG/M3;15 PPM

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:EOSIN Y

CAS:548-26-5

RTECS #:DH6832500

< Wt:1.

Ingred Name:PHOSPHOTUNGSTIC ACID

CAS:13 43-93-7 < Wt:1.

Ingred Name:LIGHT GREEN SF YELLOWISH

CAS:5141-20-8

RTECS #:BQ4900000

< Wt:1.

========== Hazards Identification ===============

LD50 LC50 Mixture:NO DATA PROVIDED BY MANUFACTURER

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYE: SPLASHES & HIGH CONCENTRACTIONS

OF VAPORS CAN IRRITATE EYES. SKIN: MAY GIVE IRRITATION WITH

REDNESS. BOTH METHANOL & ETHYLENE GLYCOL CAN BE ABSORBED THROUGH

SKIN & PROLONG

ED OR REPEATED EXPOSURES CAUSE TOXIC EFFECTS (SEE INHALATION) & DEGREASE THE SKIN. INHALATION: INHALATION OF HIGH CONCENTRATIONS OF VAPORS MAY IRRITATE MUCOUS MEMBRANES IN THE AIRWAYS. INGESTION: TOXIC IF SWALLOWED. LONG TER M: PROLONGED OR FREQUENT EXPOSURE TO VAPORS OF VOC'S MAY RESULT IN DAMAGE TO LIVER, KIDNEYS, BLOOD OR CENTRAL NERVOUS SYSTEM & THE OPTICAL NERVE. PROLONGED OR FREQUENT CONTACT MAY CAUSE CHRONIC EYE IR RITATION. METHANOL CAN DAMAGE THE GENES.

Expl

anation of Carcinogenicity:NO DATA PROVIDED BY MANUFACTURER
Effects of Overexposure:EYE: BLURRED VISION. INHALATION: HEADACHE,
TIREDNESS, NAUSEA, VOMITING, AND DIZZINESS. INHALATION CAN CAUSE
PNEUMONIA. BE AWARE THAT SYMPTOMS (DYSPNOEA) CAN OCCUR SEVERAL
HOURS AFTER CONTACT. INGESTIO N: DIZZINESS, HEADACHE, NAUSEA,
VOMITING, VISUAL DISTURBANCE, BLINDNESS, CONVULSIONS, DAMAGE OF THE
KIDNEYS AND DEATH.

Medical Cond Aggravated by Exposure: NO DATA PROVIDED BY MANUFACTURER

=====		
============	First Aid Measures	

First Aid:EYE: IMMEDIATELY FLUSH WITH WATER OR PHYSIOLOGICAL SALT WATER FOR AT LEAST 15 MINUTES. REMEMBER TO REMOVE CONTACT LENSES, IF ANY. CONTINUE TO FLUSH ON THE WAY TO THE DOCTOR. SKIN: IMMEDIATELY REMOVE C ONTAMINATED CLOTHING AND WASH WITH WATER AND SOAP FOR 15 MINUTES. INHALATION: REMOVE TO FRESH AIR. KEEP AT REST. ADMINISTER OXYGEN OR ARTIFICIAL RESPIRATION AS NEEDED. INGESTION: RINSE MOUTH AND DRINK

PLENY WATER. PROVOKE VOMITING. BEND OVER, HEAD DOWN TO AVOID VOMIT IN THE LUNGS. SEEK MEDICAL ADVICE IN ALL CASES. BURNS: FLUSH WITH WATER UNTIL PAIN CEASES.

========= Fire Fighting Measures ==============

Flash Point:=24.C, 75.2F

APPROXIMATE

Extinguishing Media:SUITABLE: USE DRY CHEMICAL OR CARBON DIOXIDE FOR SMALL FIRES. USE "ALCOHOL" TYPE FOAM FOR LARGE FIRES. NOT SUITABLE: WATER.

Fire Fighting Procedures: WHEN EXTINGUISHING FIRES USE SELF CONTAINED

BREATHING APPARATUS. REMOVE CONTAINERS IF POSSIBLE OR USE WATERSPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. DO NOT BREATHE SMOKE GASES.

Unusual Fire/Explosion Hazard:THIS PRODUCT MAY FORM HAZARDOUS DECOMPOSITION PRODUCTS SUCH AS OXIDES OF CARBON. VAPORS ARE HEAVIER THAN AIR AND CAN TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE AND FLASHBACK TO VAPOR SOURCE.

======== Accidental Release Measures ============

Spill Release Procedures:PROVIDE FOR SUFFICIENT VE NTILATION/RESPIRATORY

PROTECTION. REMOVE SOURCES OF IGNITION. VENTILATE AREA OF LEAK OR SPILL. DO NOT EMPTY INTO DRAINS. IF THE PRODUCT CONTAMINATES LAKES, RIVERS OR SEWAGES, INFORM APPROPRIATE AUTHORITIES IN ACCORDANCE WITH LOCAL REGULATIONS. ABSORB SPILLED LIQUID WITH INERT MATERIAL AND PLACE SPILLAGE IN A PLASTIC CONTAINER FOR DISPOSAL. FLUSH SPILL AREA WITH WATER.

Neutralizing Agent: NO DATA PROVIDED BY MANUFACTURER

Handling and Storage Precautions:SAFE STORAGE: WELL CLOSED IN ORIGIONAL CONTAINER AWAY FROM STRONG OXIDIZERS. KEEP CLOSED WHEN NOT IN USE. STORE IN A FLAMMABLE LIQUID STORAGE AREA.

Other Precautions: NO DATA PROVIDED BY MANUFACTURER

====== Exposure Controls/Personal Protection ========

Respiratory Protection: IN CASE OF BADLY VENTILATED AREAS USE AN APPROVED SELF CONTAINED BREATHING APPARATUS. THE VAPOURS ARE NOT EFFECTIVELY ABSORBED BY CARBON FILTE

RS


Ventilation: AVOID BREATHING OF VAPORS. PROVIDE ADEQUATE VENTILATION Protective Gloves: USE GLOVES OF BUTYL RUBBER OR 4H

Eye Protection: WEAR TIGHT FITTING SAFETY GOGGLES

Other Protective Equipment: THERE SHALL BE ACCESS TO WATER AND EYE WASH FOUNTAIN.

Work Hygienic Practices:AFTER USE WASH WITH PLENTY OF WATER AND SOAP Supplemental Safety and Health

AVOID BREATHING OF VAPORS AND ALL CONTACT WITH SKIN, EYES AND CLOTHES. FLAMMABLE, DO NOT USE NEAR FIRE OR SPARKS, DO NOT SMOKE. FIRST AID:



32; LETTER: C; UN NO.: 1992; PROPER SHIPPING NAME: FLAMMABLE LIQUID, TOXIC, N.O.S. (METHANOL). SEA (IMDG): IMDG CLASS: 3; IMDG PAGE NO.: 3346-1; UN NO.: 1992; EMS: 3-07; PACK. GROUP: III.
======================================
SARA Title III Information:NO DATA PROVIDED BY MANUFACTURER Federal Regulatory Information:NO DATA PROVIDED BY MANUFACTURER State Regulatory Information:NO DATA PROVIDED BY MANUFACTURER

====== Other Informat ion =========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this informatio n to their particular situation.