

MINNESOTA MINING AND MFG CO -- EC-776 FUEL RESISTANT COATING -- 8040-00-597-9723
===== Product Identification =====

Product ID:EC-776 FUEL RESISTANT COATING
MSDS Date:02/14/1995
FSC:8040
NIIN:00-597-9723
Status Code:A
MSDS Number: CLKVS
=== Responsible Party ===
Company Name:MINNESOTA MINING AND MFG CO
Address:3M CENTER
City:SAINT PAUL
State:MN
ZIP:55144-1000
Country:US
Info Phone Num:800-364-3
557 / 651-737-6501(24 HR)
Emergency Phone Num:810-661-0260
Preparer's Name:RYAN MICKELSON
CAGE:76381
=== Contractor Identification ===
Company Name:MINNESOTA MINING AND MFG CO, DBA 3M
Address:3M CENTER BLDG 224-5S-04
Box:City:SAINT PAUL
State:MN
ZIP:55144-1000
Country:US
Phone:866-556 5712 / 612-733-1110
CAGE:76381

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE
CAS:108-10-1
RTECS #:SA9275000
Minumum % Wt:60.
Maxumum % Wt:70.
OSHA PEL:41

0 MG/M3;100 PPM
ACGIH TLV:205 MG/M3;50 PPM
ACGIH STEL:307 MG/M3;75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PHENOL-FORMALDEHYDE POLYMER
CAS:9003-35-4
Minumum % Wt:10.
Maxumum % Wt:20.

Ingred Name:ACRYLONITRILE-BUTADIENE POLYMER
CAS:9003-18-3
Minumum % Wt:10.
Maxumum % Wt:20.

Ingred Name:ETHYL ALCOHOL
CAS:64-17-5
RTECS #:KQ6300000
Minumum % Wt:1.
Maxumum % Wt:10.
OSHA PEL:1900 MG/M3;1000 PPM
ACGIH TLV:1880 MG/M3;1000 PPM

Ingred Name:METHYL ALCOHOL
CAS:67-56-1
RTECS #:PC140000
0
Minumum % Wt:.1
Maxumum % Wt:1.
OSHA PEL:260 MG/M3;200 PPM
ACGIH TLV:262 MG/M3;200 PPM
ACGIH STEL:328 MG/M3;250 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ACETATE
CAS:141-78-6
RTECS #:AH5425000
Minumum % Wt:.01
Maxumum % Wt:.1
OSHA PEL:1400 MG/M3;400 PPM
ACGIH TLV:1440 MG/M3;400 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:EYE CONTACT: MODERATE EYE IRRITATION:
SIGNS/SYMPTOM

S CAN INCLUDE REDNESS, SWELLING, PAIN, TEARING, AND HAZY VISION. SKIN CONTACT: MILD SKIN IRRITATION: SIGNS/SYMPTOMS CAN INCLUDE REDNESS, SWELLING, AND ITCHING. INHALATION: CENTRAL NERVOUS SYSTEM DEPRESSION: SIGNS/SYMPTOMS CAN INCLUDE HEADACHE, DIZZINESS, DROWSINESS, INCOORDINATION, SLOWED REACTION TIME, SLURRED SPEECH, GIDDINESS AND UNCONSCIOUSNESS .

=====
===== First Aid Measures =====

First Aid: EYE CONTACT: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER. GET IMMEDIATE MEDICAL ATTENTION. SKIN CONTACT: FLUSH SKIN WITH LARGE AMOUNTS OF WATER. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION. INHALATION: REMOVE PERSON TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GET MEDICAL ATTENTION. IF SWALLOWED: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. ONLY INDUCE VOMITING AT THE INSTRUCTION OF A PHYSICIAN. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

=====
===== Fire Fighting Measures =====

Flash Point: =10.C, 50.F
Lower Limits: 1.40
Upper Limits: 19.00
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM
Fire Fighting Procedures: WEAR FULL PROTECTIVE CLOTHING, INCLUDING HELMET, SELF-CONTAINED, POSITIVE PRESSURE OR PRESSURE DEMAND BREATHING APPARATUS, BUNKER COAT AND PANTS, BANDS AROUND ARMS, WAIST AND LEGS, FACE MASK, AND PROTECTIVE COVERING FOR EXPOSED AREAS OF THE HEAD.
Unusual Fire/Explosion Hazard: CLOSE D CONTAINERS EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE AND EXPLODE. VAPORS MAY TRAVEL LONG DISTANCES ALONG THE GROUND OR FLOOR TO AN IGNITION SOURCE AND FLASH BACK.

=====
===== Accidental Release Measures =====

Spill Release Procedures: REFER TO OTHER SECTIONS OF THIS MSDS THIS MSDS FOR INFORMATION REGARDING PHYSICAL AND HEALTH HAZARDS, RESPIRATORY PROTECTION, VENTILATION, AND PERSONAL PROTECTIVE EQUIPMENT. IN THE U.S.A., CALL (612) 733-1110 OR (

612) 733-6100 FOR 24 HOUR SPILL

ASSISTANCE. VENTILATE AREA. EXTINGUISH ALL IGNITION SOURCES. COVER WITH ABSORBENT MATERIAL. COLLECT USING NON-SPARKING TOOLS. PLACE IN A U. S. DOT-APPROVED

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINER CLOSED WHEN NOT IN USE.
KEEP OUT OF REACH OF CHILDREN.

Other Precautions:KEEP CONTAINER TIGHTLY CLOSED. FLAMMABLE LIQUID AND VAPOR. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, AND OTHER SOURCES

OF IGNITION. GROUND CONTAINERS SECURELY WHEN TRANSFERRING CONTENTS. WEAR LOW STATIC OR PROPERLY GROUNDED SHOES. AVOID STATIC DISCHARGE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:AVOID BREATHING OF VAPORS, MISTS OR SPRAY. SELECT ONE OF THE FOLLOWING NIOSH APPROVED RESPIRATORS BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS AND IN ACCORDANCE WITH OSHA REGULATIONS: HALF MASK ORGANIC VAPOR RESPIRATOR, HALF

MASK ORGANIC VAPOR RESPIRATOR WITH DUST/MIST PREFILTER.

Ventilation:USE WITH FUNCTIONING SPRAY BOOTH OR LOCAL EXHAUST. USE IN A WELL VENTILATED AREA.

Protective Gloves:BUTYL RUBBER, POLYETHYLENE/ETHYLENE VINYL ALCOHOL, POLYTETRAFLUROETHYLENE

Eye Protection:AVOID EYE CONTACT WITH VAPOR, SPRAY OR MIST. WEAR VENTED GOGGLES. SIDE SHIELDS

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boiling Pt:=73.3C, 164.F

Vapor Pres:42.1000MMHG

Vapor Density:3.00 AIR

Spec Gravity:0.880 WATER=1

Viscosity:CA. 950.0 CENTISTOKES

Evaporation Rate & Reference:>5.00 ETHER=1

Solubility in Water:ISOLUBLE

Appearance and Odor:THIN LIQUID, TRANSPARENT AMBER, CHARACTERISTIC KETONE ODOR

Percent Volatiles by Volume:74

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE, OXIDES OF NITROGE

N, HYDROGEN CYANIDE, ALDEHYDES, KETONES,
HYDROCARBONS.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE IN A PERMITTED HAZARDOUS WASTE
INCINDERATE IN THE PRESENCE OF A COMBUSTIBLE MATERIAL. DISPOSE OF
WASTE PRODUCT IN A FACILITY PERMITTED TO ACCEPT CHEMICAL WASTE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United
States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.