View NSN Online: https://aerobasegroup.com/nsn/8010-01-302-3604

NILES CHEMICAL PAINT -- N-6240A, DARK GRAY 1.8, T-III F#153 -- 8010-01-302-3604

Product ID:N-6240A, DARK GRAY 1.8, T-III F#153 MSDS Date:09/13/2000 FSC:8010 NIIN:01-302-3604 Status Code:A MSDS Number: CLLDK === Responsible Party === Company Name: NILES CHEMICAL PAINT Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Info Phone Num:616-683-3 377/219-236-5856 Emergency Phone Num:219-236-5856 Preparer's Name: BOBBY STOKES CAGE:02388 === Contractor Identification === Company Name: NILES CHEMICAL PAINT Address:225 FORT STREET Box:307 City:NILES State:MI ZIP:49120 Country:US Phone:616-683-3377/219-236-5856 CAGE:02388

Ingred Name:TALC CAS:14807-96-6 RTECS #:WW2710000 = Wt:35. OSHA PEL:SEE TABLE Z-3 ACGIH TLV:2 MG/M3

Ingred Name:BUTYL ALCOHOL CAS:71-36-3 RTECS #:EO140000 0 = Wt:31. OSHA PEL:300 MG/M3;100 PPM ACGIH STEL:C152 MG/M3;C50 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:POLYAMIDE/EPOXY ADDUCT = Wt:20.

Ingred Name:AMIDOAMINE RESIN = Wt:1.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic:EYES:SEVERE

IRRITATION, LACRIMATION. REDNESS, BLURRED VISION. SKIN: HARMFUL IF ABSORBED THROUGH SKIN. CAN BE ABSORBED IN TOXIC AMOUNTS. ESPEC IALLY

FROM PROLON ED OR REPEATED E XPOSURES. BREATHING : NA SAL AND RESPIRATORY IRRITATION. CNS DEPRESSION (DIZZINESS, DROWNINESS, WEAKNESS, FATIGUE. CONFUSION) NAUSEA HEADACHE. VERTIGO. POSSIBLE UNCONSCIOUSNESS. EVEN ASPHYXIATION. SWOLLOWING: GASTROINTESTI NAL IRRITATION. ABDOMINAL PAIN. NAUSEA, VOMITING, DIARRHEA CHRONIC EFFECTS OF OVEREXPOSURE RESPIRATORY TRACT, CORNEAL INFLAMMATION, PHOTOPHOBIA.

Effects of Overexposure:EYES:SEVERE IRRITATION, LACRIMATION, RED NESS,

BLURRED VISION.SKIN: REDNESS AND IRRIATATION, DEFATTING TO SKIN LEADING TO DERMATTIS. BREATHING: NASAL AND RESPIRAOTY IRRITATION, CNS DEPRESSION.SWALLOWIN G: GASTROINTESTINAL IRRITATION, ABDOMINAL PAIN,NAUSEA, VOMITING, DIARRHEA.

Medical Cond Aggravated by Exposure:NONE KNOWN

First Aid:INHALTION: MOVE VICTIM TO FRESH AIR AT ONCE. GET MEDICAL ATTENTION. SWALLOWING: DRINK 1 OR 2 GLASSES OF WATER. CONSU LT A

PHYSICIAN IMMEDIATEY SKIN CONTACT: FLUSH SKIN WITH PLENTY OF WATER. EYE CONTACT : FLUSH EYES WITH LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES. SWALLOWING: DRINK 1 OR 2 GLASSES OF WATER. DO NOT INDUCE VOMITING.

Flash Point Method:TCC Flash Point:=41.7C, 107.F Lower Limits:1.7 Upper Limits:11.0 Extinguishing Media:DRY CHEMICAL, FOAM, CO2 Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS WIT ΗA

FULL FACEPIECE OPERATED IN POSITIVE PRESSURE MODE AND FULL PROTECTIVE CLOTHING. WATER MAY BE USED TO COOL CONTAINERS TO PREVENT PRESSURE BUILD UP AND POS SIBLE AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE. ISCOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT, AND OPEN FLAME, CLOSED CONTAINERS MAY EXPLODE WHEN EXP OSED TO

EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. MINIMIZE THE BREATHING OF VAPORS AND AVOID SKIN CONTACT. ABSORB WITH AN INERT MATERIAL SUCH AS CLAY, SOIL, OR A COMMERCIALLY AVAILABLE ABSORBENT. SHOVEL RECLAIMED LIQUID AND ABSORBENT INTO RECOVERY OR SALAGE DRUMS FOR DISPOSAL.

Neutralizing Agent: CANCER CAUSING AGENT.

Handling and Storage Precautions: AVOID STORAGE IN HIGH TEMPERATURE AREAS OR NEAR FIRE OR OPEN FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE. AVOID ROUGH HANDLING.

Other Precautions:CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTY. DO NOT WELD OR FLAME OUT ON EMPTY DRUMS.SHOCK FROM DROPPING MAY SPLIT CONTAINERS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:W

EAR AN APPROPRIATE PROPERLY FITTED HALF MASK OR

FULL FACEPIECE RESPIRATOR DURING AND AFTERAPPLICATION UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVEL ARE BELOW APPLICABLE LIMITS

Ventilation:SUFFICIENT VENTILATION IN VOLUME AND PETTERN SHOULD BE PROVIDED TO KEEP THE AIR CONCENTRATION BELOW CURRENT APPLICABLE OSHA PERMISSIBLE EXPOSURE LIMIT.

Protective Gloves:WEAR CHEMICAL RESISTANT GLOVES AND CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.

Eye Protection:WEAR CHEMICAL GOGG

LES, SAFETY GLASSES, OR FACE SHIELDS Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING, OR USING RESTROOM Supplemental Safety and Health

Boiling Pt:=116.7C, 242.F Vapor Density:HEAVIER Spec Gravity:1.310 VOC Grams/Liter:3.41 Viscosity:99-108 KU Evaporation Rate & amp; Reference:SLOWER THAN AIR Solubility in Water:SLIGHT Appearance and Odor:LIQUID, ODER OF SOLVENTS Percent Volatiles by Volume:50.66 Corrosion Rate:MI NIMAL.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:HIGH TEMPERATURES Hazardous Decomposition Products:CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.

Federal Regulatory Information:EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355)THIS PRODUCT DOES NOT CONTAIN INGREDIENTS LISTED IN APPENDIX A AND B AS AN EXTREMELY HAZARDOUS SUBSTANCE.M.S.D.S. REQUIREMENTS (40 CFR 370).OUR HAZARD EVALUA TION HAS FOUND THIS PRODUCT TO BE HAZARDOUS.[X]IMMEDIATE(ACUTE)HEALTH HAZARD. [X] DELAYED (CHRONIC) HEALTH HAZARD. [X] FIRE HAZARD.
State Regulatory Information:

Disclaimer (p

rovided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.