View NSN Online: https://aerobasegroup.com/nsn/6750-01-010-7343

EASTMAN KODAK COMPANY -- 191 9042, PT C, KODAK FLEXICOLOR DEVELOPER (SEE SUPPL) -- 6750-01-010-7343

Product ID:191 9042, PT C, KODAK FLEXICOLOR DEVELOPER (SEE SUPPL) MSDS Date:01/08/2001 FSC:6750 NIIN:01-010-7343 Status Code:A Kit Part:Y **MSDS Number: CLLFB** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State: NY ZIP:14650 Country:US Info Phone Num:716-477-3194 MSDS :800- 242-2424 Emergency Phone Num:716-722-5151 Preparer's Name:NOT PROVIDED CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 Contract Num:SP0500-96-D-9413-N525 CAGE:19139

Ingred Name:WATER CAS:7732-18-5 RTEC S #:ZC0110000 Minumum % Wt:55. Maxumum % Wt:60. Other REC Limits:NOT PROVIDED Code:F Code:F

Ingred Name:4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE SULFATE CAS:25646-77-9 RTECS #:KJ6477000 Minumum % Wt:35. Maxumum % Wt:35. Other REC Limits:0.1 MG/M3 (MFR) OSHA PEL:NOT PROVIDED ACGIH TLV:NOT PROVIDED

Ingred Name:SODIUM BISULFITE CAS:7631-90-5 RTECS #:VZ2000000 Minumum % Wt:1. Maxumum % Wt:5. Other REC Limits:NOT PROVIDED OSHA PEL:NOT PROVIDED ACGIH TLV:5 MG/M3 EPA Rpt Qty:5000 LB S DOT Rpt Qty:5000 LBS

LD50 LC50 Mixture:NOT PROVIDED

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:GENERAL: CONTAINS

4-(N-ETHYL-N-2HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE SULFATE. MAY CAUSE KIDNEY DAMAGE BASED ON ANIMAL DATA. INHALATION: LIBERATES SULFUR DIOXIDE GAS WHICH CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT. SOME ASTHMATICS OR HYPERSENSITIVE INDIVIDUALS MAY EX PERIENCE

DIFFICULT BREATHING. EYES: CAUSES IRRITATION. VAPOR IRRITATING. SKIN: CAUSES IRRITATION. MAY CAUSE ALLERGIC SKIN REACTI ON. INGESTION: MAY BE FATAL IF SWALLOWED. MAY CAUSE IRRITATION OF THE GASTROINTESTINAL TRACT. MAY CAUSE KIDNEY DAMAGE BASED ON ANIMAL DATA.

Explanation of Carcinogenicity:INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC): NONE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH): SODIUM BISULFITE, A4; NOT CLASSIFIABLE AS A HUMAN CARCINOGEN, SULFUR DIOXIDE, A4; NOT CLASSIFIABLE AS A HUMAN CARCINOGEN. - NATIONAL TOXICOLOGY PROGRAM (NTP): NONE -OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA): NONE
Effects of Overexposure:INHALATION: LIBERATES SULFUR DIOXIDE GAS WHICH CAN CAUSE IRRITATION TO THE RESPIRATORY TRACT. EYES: CAUSES IRRITATION. VAPOR IRRITATING. SKIN: CAUSES IRRITATION. INGESTION: MAY CAUSE IRRITATION OF THE GASTROINTESTINAL TRACT.
Medical Cond Aggravated by Exposure:SOME ASTHMAT
ICS, HYPERSENSITIVE OR SULFITE-SENSITIVE INDIVIDUALS MAY EXPERIENCE DIFFICULT BREATHING, WHEEZING, CHEST TIGHTNESS, STOMACH UPSET, HIVES, FAINTNESS, WEAKNESS AND DIARRHEA.

First Aid:INHALATION: IF SYMPTOMATIC, MOVE TO FRESH AIR. GET MEDICAL ATTENTION IF SYMPTOMS PERSIST. EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MIN. GET MEDICAL ATTENTION. IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST

15 MINUTES WHILE REMOVING

CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION IF SYMPTOMS OCCUR. INGESTION: NDUCE VOMITING AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHIN G BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM. USE WATER SPRAY TO KEEP FIRE EXPOSED CONT AINERS COOL.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING. FIRE OR EXCESSIVE HEAT MAY PRODUCE HAZARDOUS DECOMPOSITION PRODUCTS.

Unusual Fire/Explosion Hazard: ELEVATED TEMPETRAUES CAN CAUSE DECOMPOSITION.

Spill Release Procedures: FLUSH TO SEWER IF ALLOWABLE WITH LARGE AMOUNT OF WATER. OTHERWISE, ABSORB SPILL WITH VERMICULITE OR OTHER INERT MATERIAL, THEN PLACE IN A

CONTAINER FOR CHEMICAL WASTE. CLEAN SURFACE TO REMOVE RESIDUAL CONTAMINATION. Neutralizing Agent:NOT PROVIDED

Handling and Storage Precautions: STORE IN A COOL PLACE. KEEP AWAY FROM INCOMPATIBLE SUBSTANCES. KEEP CONTAINER CLOSED. Other Precautions: AVOID BREATHING MIST OR VAPOR. AVOID CONTACT WITH EYES AND PROLONGED OR REPEATED CONTACT WITH SKIN. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. == Respiratory Protection: IF ENGINEERING CONTROLS DO NOT MAINTAIN AIRBORNE CONCENTRATIONS BELOW RECOMMENDED EXPOSURE LIMITS, AN APPROVED RESPIRATOR MUST BE WORN. RESPIRATOR TYPE: ACID GAS. Ventilation: GOOD GENERAL VENTILATION (TYPICALLY 10 AIR CHANGES Protective Gloves:WEAR IMPERVIOUS GLOVES. Eye Protection: WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES). Other Protective Equipment: EYE BATH, SAFETY SHOWER, WASHING FACILIT IES. WEAR PROTECTIVE CLOTHING APPROPRIATE Work Hygienic Practices:NOT PROVIDED Supplemental Safety and Health CONTD FROM PRODUCT ID: REPLENISHER. THIS IS A KIT. THE OTHER MSDS SERIAL NUMBERS ARE: CLLDN, CLLDW. ABBREVIATION: N/A = NOT APPLICABLE, N/AV = NOT AVAILABLE, N/K = UNKNOWN, N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED. HCC:C2 NRC/State Lic Num:NOT RELEVANT R oiling Pt:>100.C, 212.F Melt/Freeze Pt:M.P/F.P Text:NOT PROVIDED Decomp Temp:>172.2C, 342.F Vapor Pres:18MM @ 20C Vapor Density:0.6 Spec Gravity:1.15 pH:2.1 Viscosity:NOT PROVIDED Evaporation Rate & amp; Reference: NOT PROVIDED Solubility in Water:COMPLETE Appearance and Odor: RED-BROWN LIQUID; STRONG SULFUR DIOXIDE ODOR. Percent Volatiles by Volume:55-60 WT Corrosion Rate:NOT PROVIDED

Stability Indicator/Materials to Avoid:YES

S

TRONG BASES, STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:STABLE; HOWEVER, MATERIAL CAN DECOMPOSE ABOVE 170C. AVOID TEMPERATURES ABOVE 70C.
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF SULFUR, OXIDES OF NITROGEN.

Toxicological Information:CONTAINS

4-(N-ETHYL-N-2-HYDROXYETHYL)-2-METHYLPHENYLENEDIAMINE SULFATE. MAY CAUSE KIDNEY DAMAGE BASED ON ANIMAL DATA. ORAL LD-50 (MALE

RAT): 25-50 MG/KG (TARGET ORGAN EFFECTS: KIDNEY) ORAL LD-50 (FEMALE RAT): 30 MG/KG (TARGET ORGAN EFFECTS: KIDNEY) ORAL LD-50 (MOUSE): 141 MG/KG (TARGET ORGAN EFFECTS: KIDNEY) DERMAL LD-50: > 2000 MG/KG SKIN IRRITATION: MODERATE

Ecological:THE FOLLOWING PROPERTIES ARE ESTIMATED FROM THE COMPONENTS OF THE PREPARATIONS. POTENTIAL TOXICITY: FISH LC50 MG/L: 70%): YES (7 DAYS). POTENTIAL

BIOACCUMULATION: LOG POW 100.

Waste Disposal Methods:DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO NATIONAL, STATE OR LOCAL LAWS. FLUSH TO SEWER WITH LARGE AMOUNT OF WATER.

Transport Information:FOR TRANSPORTATION INFORMATION REGARDING THIS PRODUCT CALL THE KODAK WORLDWIDE TRANSPORTATION HAZMAT HOT LINE: (716) 722-2400 BETWEEN 8 A.M. AND 5 P.M. (EASTERN STANDARD TIME), MONDAY THROUGH FRIDAY.

SARA Title III Information:CHEMICAL(S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OR TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372: NONE Federal Regulatory Information:NOT PROVIDED

State Regulatory Information:MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE -

MATERIAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE ADVERSE REPRODUCTIVE EFFECTS: NONE

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utiliz ing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.