

=====
Product Identification
=====

Product ID:INSULATING VARNISH,ELECTRICAL

MSDS Date:12/29/1997

FSC:5970

NIIN:00-990-4924

Status Code:A

MSDS Number: CLLHT

=== Responsible Party ===

Company Name:HUMISEAL DIVISION, COLUMBIA CHASE CORP.

Address:26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:445

City:WOODSIDE

State:NY

ZIP:11377-0445

Country:US

Info Phone Num:718-932-0800

Emerg

ency Phone Num:800-424-9300

Preparer's Name:BOBBY STOKES

Chemtre Ind/Phone:(800)424-9300

CAGE:0SR97

=== Contractor Identification ===

Company Name:HUMISEAL DIVISION, COLUMBIA CHASE CORP.

Address:26-60 BROOKLYN QUEENS EXPRESSWAY WEST

Box:445

City:WOODSIDE

State:NY

ZIP:11377-0445

Country:US

Phone:718-932-0800

CAGE:0SR97

=====
Composition/Information on Ingredients
=====

Ingred Name:SECTION 3A (SARA RQ)

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

Minimum % Wt:47.

Maximu

m % Wt:53.
OSHA PEL:SEE TABLE Z-2
ACGIH TLV:188 MG/M3;50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE
CAS:78-93-3
RTECS #:EL6475000
Minumum % Wt:13.
Maxumum % Wt:18.
OSHA PEL:590 MG/M3;200 PPM
ACGIH TLV:590 MG/M3;200 PPM
ACGIH STEL:885 MG/M3;300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACRYLIC POLYMER
Minumum % Wt:32.
Maxumum % Wt:38.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YE
S Ingestion:YES

Effects of Overexposure:EYES: SHORT TERM CONTACT MAY RESULT IN SLIGHT EYE IRRITATION AND CONJUNCTIVITIS. PROLONGED CONTACT WITH LIQUID CAN RESULT IN CORNEAL BURNS. HIGH VAPOR CONCENTRATIONS>APPROX. 1000PPM ARE IRRITATING TO THE EYES. SKIN: PROLONGED AND REPEATED LIQUID CONTACT CAN CAUSE DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION AND DERMATITIS. DERMAL LD (50) (RABBITS) :>2000MG/KG.SKIN ABSORPTION MAY ADD SIGNIFICANTLY T

○ EXPOSURE. INHALATION: DIZZINESS, WEAKNESS, HEADACHE, NAUSEA. INGESTION: MODERATELY TOXIC; SERIOUS HAZARD POSED BY VOMITING.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION: SKIN: FLUSH WITH WATER WHILE REMOVING CONTAMINATED CLOTHING AND SHOES, FOLLOW BY WASHING WITH SOAP AND WATER. DO NOT REUSE CLOTHING OR SHOES UNTIL PROPERLY CLEANED. IF IRR

ITATION PERSISTA, GET MEDICAL ATTENTION.

INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO LUNGS. GET MEDICAL ATTENTION IMMEDIATELY

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point

t:-1.1C, 30.F

Lower Limits:1.6

Upper Limits:11.2

Extinguishing Media:FOAM, CARBON DIOXIDE AND DRY CHEMICAL

Fire Fighting Procedures:FIGHT AS A FLAMMABLE LIQUID FIRE; WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:VAPOR IS FLAMMABLE AND HEAVIER THAN AIR AND MAY TRAVEL TO SOURCE OF IGNITION AND FLASHBACK

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB WITH INERT MATERIAL (SAND, VERMICULITE, ETC.) LARGE SPILLS

MAY BE SCOOPED UP WITH NON-SPARKING TOOLS..

REMOVE SOURCES OF IGNITION. PROVIDE VENTILATION AND/OR RESPIRATORY PROTECTION.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. STORE AT AMBIENT TEMPERATURE. GROUND TO PROTECT FROM STATIC CHARGE. KEEP CONTAINER CLOSED. USE ADEQUATE VENTILATION.

Other Precautions:PREVENT CONTACT TO WORKERS AS REQUIRED. IF MORE THAN 2 ML/KG HAS BEEN

INGESTED, AND VOMITING HAS NOT OCCURRED, EMESIS

SHOULD BE INDUCED WITH SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE US

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RESPIRATOR-ORGANIC VAPOR TYPE IF TLV IS EXCEEDED (NIOSH APPROVED).

Ventilation:YES; MECHANICAL: EXPLOSION PROOF.

Protective Gloves:I

IMPERVIOUS TO CHEMICAL AND PETROLEUM (BUNA-N, SOLVEX, ETC.)

Eye Protection:CHEMICAL TYPE GOGGLES MUST BE WORN.

Other Protective Equipment:PREVENT CONTACT TO WORKERS AS REQUIRED.

Supplemental Safety and Health

KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAMES. STORE AT AMBIENT TEMPERATURE. GROUND TO PROTECT FROM STATIC CHARGE. KEEP CONTAINER CLOSED. USE ADEQUATE VENTILATION.

===== Physical/Chemical Properties =====

Boiling Pt:=82.2C, 180.F

Vapor Pres:(MM HG)

: 45.4.

Vapor Density:4(AIR=1)

Spec Gravity:(H2O=1) : .88.

Evaporation Rate & Reference:(BUAC=1) : 3.62

Solubility in Water:NEGLIGIBLE-LESS THAN 0.1

Appearance and Odor:WATER CLEAR, LOW VISCOSITY LIQUID, AROMATIC ODOR.

Percent Volatiles by Volume:62-68

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

Conditions to Avoid Polymerization:

WILL NOT OCCUR

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL OF HUMISEAL PRODUCTS REQUIRES STRICT COMPLIANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS PERTAINING TO DISPOSING HAZARDOUS WASTE MATERIALS. CONTACT THE APPROPRIATE ENVIRONMENTAL AGENCIES.

===== Disclaimer (provided with this information by the compiling agencies):

This information is fo

rmulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.