

HENTZEN COATINGS INC -- BROWN HEAT RESISTANT PAINT, MIL-P-14105D -- 8010-01-235-2695

=====
Product Identification
=====

Product ID:BROWN HEAT RESISTANT PAINT, MIL-P-14105D

MSDS Date:02/08/1999

FSC:8010

NIIN:01-235-2695

Status Code:A

MSDS Number: CLLJD

=== Responsible Party ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Info

Phone Num:414-353-4200

Emergency Phone Num:999-999-9999

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:09225

=== Contractor Identification ===

Company Name:HENTZEN COATINGS INC

Address:6937 WEST MILL ROAD

Box:18749

City:MILWAUKEE

State:WI

ZIP:53218

Country:US

Phone:414-353-4200

CAGE:09225

=====
Composition/Information on Ingredients
=====

Ingred Name:TALC

CAS:14807-96-6

RTECS #:WW2710000

Minimum % Wt:5.

Maximum % Wt:10.

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:2

MG/M3

Ingred Name:MICA
CAS:12001-26-2
RTECS #:VV8760000
Minumum % Wt:1.
Maxumum % Wt:5.
ACGIH TLV:3 MG/M3

Ingred Name:XYLENE
CAS:1330-20-7
RTECS #:ZE2100000
= Wt:18.75
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:651 MG/M3;150 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CHROME
CAS:7440-47-3
RTECS #:GB4200000
= Wt:1.55
OSHA PEL:1 MG/M3
ACGIH TLV:0.5 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ZINC
CAS:7440-66-6
RTECS #:ZG8600000
= Wt:3.02
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000
LBS

Ingred Name:FRITS, CHEMICALS
CAS:65997-18-4
= Wt:21.64

Ingred Name:ETHYLBENZENE
CAS:100-41-4
RTECS #:DA0700000
= Wt:2.07
OSHA PEL:435 MG/M3;100 PPM
ACGIH TLV:434 MG/M3;100 PPM
ACGIH STEL:543 MG/M3;125 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:BUTYL ALCOHOL
CAS:71-36-3
RTECS #:EO1400000
= Wt:3.45
OSHA PEL:300 MG/M3;100 PPM
ACGIH STEL:C152 MG/M3;C50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:AROMATIC HYDROCARBONS

1.85

Ingred Name:SILICEOUS EXTENDER PIGMENT

CAS:66402-68-4

Code:F

Minumum % Wt:1.

Maxumum % Wt:5.

Ingred Name:CRYSTALITE SS

CAS:14808-60-7

RTECS #:VV7330000

< Wt:.5

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.1 MG/M3

===== Hazards Identification =====

LD50 LC50 Mixture:NONE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:EYE CONTACT: CAN CAUSE IRRITATION.

SKIN C

ONTACT: CAN CAUSE IRRITATION. MAY CAUSE DEFATTING OF THE SKIN. INHALATION: CAN CAUSE IRRITATION OF THE RESPIRATORY TRACT.

HEADACHE, DIZZINESS, STAGGERING GAIT , CONFUSION OR

UNCONSCIOUSNESS. INGESTION: IF SWALLOWED, CONSULT A PHYSICIAN

IMMEDIATELY. CHRONIC EFFECTS: PROLONGED EXPOSURE ASSOCIATED WITH

PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE, LIVER AND KIDNE Y

DAMAGE, DERMATITIS.

Explanation of Carcinogenicity:CRYSTALLINE SILICA AS REASONABLY

ANTICIPATED TO BE A CARCI

NOGEN". MAY CAUSE LUNG INJURY IF

RESPIRATORY PRECAUTIONS ARE NOT USED. THE NICKEL COMPOUND IN THIS

PRODUCT HAS NOT BEEN SPECIFICALLY IDENTIFIE D AS CAUSING CANCER IN

HUMANS OR ANIMALS.

Effects of Overexposure:NONE

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY

AILMENTS; CHEMICAL SENSITIZATION.

===== First Aid Measures =====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF RUNNING WATER FOR AT LEAST 15 MINUTES WHILE L

IFTING EYELIDS. TAKE TO A PHYSICIAN FOR
MEDICAL TREATMENT. SKIN CONTACT: WASH AFFECTED AREAS WITH SOAP AND
WATER. CONSULT A PHYSICIAN. INHALATION: REMOVE FROM EXPOSURE.
RESTORE BREATHING. INGESTION: IF SWALLOWED, CALL A PHYSICIAN OR
POISON CONTROL CENTER IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:81.00 F
Autoignition Temp:Autoignition Temp Text:NONE
Lower Limits:1.00
Upper Limits:11.20
Extinguishing Media:CARBON DIOXIDE, DRY C
HEMICAL OR FOAM.
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT INCLUDING
SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. EQUIPMENT CLEAN UP CREW WITH
APPROPRIATE PROTECTIVE EQUIPMENT.AVOID BREATHING VAPORS. AVOID SKIN
CONTACT. CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING
TOOLS.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:USE ONLY WITH ADEQUATE VENTILATION.
WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR. AVOID CONTACT WITH
EYES AND CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID PROLONGED
OR REPEATED CONTACT WITH SKI N.STORAGE: DO NOT STORE ABOVE 120 F OR
BELOW 32 F

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAY APPLIED AND WHEN USED IN LIMITED
VENT
ILATION AREAS< WEAR A NIOSH?MSHA APPROVED ORGANIC
VAPOR?PARTICULATE RESPIRATOR DESIGNED TO REMOVE A COMBINATION OF
PARTICULATE< GAS AND VAPOR.USE NIOSH APPROVED RESPIRATOR.
Ventilation:NONE
Protective Gloves:CHEMICAL RESISTANT GLOVES ARE REQUIRED.
Eye Protection:USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS.
Other Protective Equipment:SAFETY SHOWERS AND EYE WASH STATIONS SHOULD
BE AVAILABLE.
Work Hygienic Practices:NONE
Supplemental Safety and Health
NONE

=====

Physical/Chemical Properties =====

Boiling Pt:B.P. Text:242.00 F 418.00 F
Melt/Freeze Pt:M.P/F.P Text:NONE
Decomp Temp:Decomp Text:NONE
Vapor Pres:9.000
Vapor Density:4.800
Spec Gravity:1.4640
Evaporation Rate & Reference: .7000 (N-BUTYL ACETATE=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:OPAQUE LIQUID SOLVENT ODOR.
Percent Volatiles by Volume:48.613

===== Stability and Reactivity Data =====

STRONG OXIDIZERS.
Stability Condition to Avoid:
NONE
Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND
OTHER TOXIC VAPORS DEPENDING UPON THE TEMPERATURE REACHED.
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:NONE

===== Other Information =====

=====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.