

FARWEST PAINT MANUFACTURING CO -- GLOSS LACQUER COLOR #16473 -- 8010-00-935-7076  
===== Product Identification =====

Product ID:GLOSS LACQUER COLOR #16473  
MSDS Date:02/17/1999  
FSC:8010  
NIIN:00-935-7076  
Status Code:A  
MSDS Number: CLLNC  
=== Responsible Party ===  
Company Name:FARWEST PAINT MANUFACTURING CO  
Address:4522 SOUTH 133RD ST  
City:TUKWILA  
State:WA  
ZIP:98168  
Country:US  
Info Phone Num:206-244-8  
844  
Emergency Phone Num:800-424-9300  
Preparer's Name:ERNEST CARTER  
Chemtrec Ind/Phone:(800)424-9300  
CAGE:6F266

=== Contractor Identification ===  
Company Name:FARWEST PAINT MANUFACTURING CO  
Address:4522 SOUTH 133RD ST  
Box:City:TUKWILA  
State:WA  
ZIP:98168  
Country:US  
Phone:206-244-8844  
CAGE:6F266

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE  
CAS:108-88-3  
RTECS #:XS5250000  
= Wt:21.3  
OSHA PEL:SEE TABLE Z-2  
ACGIH TLV:188 MG/M3;50 PPM  
EPA Rpt Qty:1000 LBS  
DOT

Rpt Qty:1000 LBS

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

= Wt:11.3

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE

CAS:78-93-3

RTECS #:EL6475000

= Wt:9.5

OSHA PEL:590 MG/M3;200 PPM

ACGIH TLV:590 MG/M3;200 PPM

ACGIH STEL:885 MG/M3;300 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE

CAS:108-10-1

RTECS #:SA9275000

= Wt:5.4

OSHA PEL:410 MG/M3;100 PPM

ACGIH TLV:205 MG/M3;

50 PPM

ACGIH STEL:307 MG/M3;75 PPM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL

CAS:67-63-0

RTECS #:NT8050000

= Wt:7.2

OSHA PEL:980 MG/M3;400 PPM

ACGIH TLV:983 MG/M3;400 PPM

ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:ISOPROPYL ACETATE

CAS:108-21-4

RTECS #:AI4930000

= Wt:2.4

OSHA PEL:950 MG/M3;250 PPM

ACGIH TLV:1040 MG/M3;250 PPM

ACGIH STEL:1290 MG/M3;310 PPM

Ingred Name:ISOBUTYL ACETATE

CAS:110-19-0

RTECS #:AI4025000

= Wt:11.

OSHA PEL:700 MG/M3;150 PPM

ACGIH TLV:713

MG/M3;150 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: THIS MATERIAL MAY CAUSE

IRRITATION, SENSITIZATION, OR DEFATTING OF SKIN UPON REPEATED

CONTACT. INHALATION: EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MIST CAN

RESULT IN HEADACHE, DIZZINESS, NAUS

EA AN D LOSS OF CONSCIOUSNESS.

EYES: THIS MATERIAL MAY BE AN EYE IRRITANT.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:NONE

Medical Cond Aggravated by Exposure:NONE

===== First Aid Measures =====

First Aid:SKIN: PROMPTLY WASH WITH SOAP AND WATER. REMOVE AND WASH ANY

CONTAMINATED CLOTHING BEFORE REUSE. EYES: FLUSH WITH LARGE

QUANTITIES OF WATER FOR 15 MINUTES AND SEEK MEDICAL ATTENTION.

SWALLOWING: IF IN GESTED DO NOT INDUCE V

OMITING; KEEP PERSON WARM

AND QUIETAND GET MEDICAL ATTENTION. INHALATION: REMOVE VICTIM TO

FRESH AIR IMMEDIATELY. IF RESPIRATORY SYMPTOMS DEVELOP, SEEK

MEDICAL ATTENTION AT ONCE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:20 F.

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:1.1

Upper Limits:NONE

Extinguishing Media:FOAM, CO2, DRY CHEMICAL,OR WATER FOG, CLASS B

EXTINGUISHING AGENT. WATER MAY BE UNSUITABLE A

S AN EXTINGUISHING

MEDIUM, BUT HELPFUL IN KEEPING ADJACENT CONTAINERS COOL.

Fire Fighting Procedures:FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR

PRODUCTS OF COMBUSTION SHOULD WEAR SELF CONTAINED BREATHING

APPARATUS. EVACUATE AREA OF UNPROTECTED PERSONNEL. WEAR PROTECTIVE

CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN

AIR AND MAY BE IGNITED BY SPARKS, PILOT LIGHTS, ETC. CLOSED

CONTAINERS MAY RUPTURE WHEN EXPOSED TO EXTREME HEAT.

=====

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA. ABSORB SPILL WITH AN ABSORBENT MATERIAL SUCH AS SAWDUST, VERMICULITE OR SAND AND PLACE MATERIAL INTO A CLOSED CONTAINER. IF LARGE SPILL, DIKE AREA TOPR EVENT THIS MATERIAL FROM ENTERING WATER SYSTEM OR SEWERS. WEAR PROTECTIVE EQUIPMENT DURING CLEANUP.

===== Handling and Storage =====

Handling and Storage Precau

tions:AVOID PROLONGED OR REPEATED INHALATION

OF HEATED VAPORS OR SPRAY MIST. KEEP AWAY FROM HEAT OR OPEN FLAME.

THIS MATERIAL MAY CAUSE SENSITIZATION. DO NOT GET IN EYES. ON SKIN

OR CLOTHING, DO NOT ALLOW C ONTAMINATED CLOTHING TO CONTACT SKIN.

DO NOT WELD ON FULL OR EMPTY CONTAINERS. KEEP CONTAINERS CLOSE

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER TYPE RESPIRATOR MUST BE WORN TO PREVENT THE I

NHALATION OF VAPORS OR SPRAY MIST WHEN THE TLV OR PEL IS EXCEEDED.

Ventilation:GENERAL VENTILATION IS REQUIRED DURING NORMAL USE.

Protective Gloves:CHEMICAL RESISTANT NITRILE, NEOPRENE OR RUBBER GLOVES REQUIRED.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR SMOKING. PRECAUTIONS TO BE TAKEN IN

Supplemental Safety and Health

THE INFORMATION IN THIS

DATA SHEET IS BELIEVED TO BE ACCURATE AND TRUE

AT THE TIME OF PREPARATION OF THIS DOCUMENT. THIS IS NOT A WARRANTY OF PRODUCT OR PRODUCT SPECIFICATION. THE END-USER OF THIS PRO DUCT IS ADVISED TO VERIFY IN ADVANCE THAT THE INFORMATION IN THIS SHEET IS CURRENT, APPLICABLE, AND SUITABLE.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:160-340 F.

Melt/Freeze Pt:M.P/F.P Text:NONE

Decomp Temp:Decomp Text:NONE

Vapor Pres:70 MM HG@20C

Vapor

Density:HEAVIER  
VOC Pounds/Gallon:650  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:NIL  
Appearance and Odor:WHITE LIQUID, OR COLOR OF TINT.  
Percent Volatiles by Volume:80%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDANTS, ACIDS, BASES AND EPOXY HARDENERS  
UNDER UNCONTROLLED CONDITIONS.  
Stability Condition to Avoid:HEAT, SPARK, OPEN FLAME. IF PRODUCT  
CONTAINS ALUMINU  
M, MOISTURE IN CLOSED CONTAINERS WILL GENERATE  
HYDROGEN GAS.  
Hazardous Decomposition Products:INCOMPLETE COMBUSTION CAN YIELD CARBON  
MONOXIDE AND TOXIC VAPORS.

===== Ecological Information =====

Ecological:DO NOT LET THIS MATERIAL ENTER WATER SYSTEMS OR SEWERS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL AGENCIES.

===== Regulatory  
Information =====

SARA Title III Information:THIS MATERIAL HAS BEEN CATEGORIZED AS HAVING  
THE FOLLOWING HAZARDS AS DEFINED BY SARA TITLE III REGULATIONS (40  
CFR 370): ACUTE, FIRE. PURSUANT TO TITLE III OF THE SUPERFUND  
AMENDMENTS AND REAUTHORIZA TION ACT OF 1986 (SARA) AND 40 CFR PART  
372, THIS PRODUCT CONTAINS OR MAY CONTAIN A TOXIC CHEMICAL IN A  
QUANTITY SUBJECT TO THE REPORTING REQUIREMENTS UNDER SECTION 313.

Disclaimer (provided with this information b  
y the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.