View NSN Online: https://aerobasegroup.com/nsn/8010-01-285-3035

Product ID:MIL-PRF-85285C(MIL-C-85285B) MSDS Date:10/14/1997 FSC:8010 NIIN:01-285-3035 Status Code:A MSDS Number: CLLTJ === Responsible Party === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Info Phone Num:949-474-0400 Emergency Phone Num: (800)424-9 300 Preparer's Name: HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300 CAGE:33461 === Contractor Identification === Company Name: DEFT, INC. Address:17451 VON KARMAN AVE City:IRVINE State:CA ZIP:92614 Country:US Phone:949-474-0400 CAGE:33461

Ingred Name:N-BUTYL ACETATE CAS:123-86-4 RTECS #:AF7350000 < Wt:5. OSHA PEL:710 MG/M3;150 PPM ACGIH TLV:713 MG/M3;150 PPM ACGIH STEL:950 MG/M3;200 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL 3-ETHOXYPROPIONATE CAS:763-69-9 RTECS #:UF3325000 = Wt:5.

Ingred Name:C8&10 AROMATIC HYDROCARBON CAS:64742-95-6 RTECS #:WF3400000 &It; Wt:1.

Ingred Name:PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE CAS:108-65-6 RTECS #:AI8925000 &It; Wt:1.

Ingred Name:METHYL N-PROPYL KETONE CAS:107-87-9 RTECS #:SA7875000 = Wt:5. OSHA PEL:700 MG/M3;200 PPM ACGIH TLV:705 MG/M3;200 PPM ACGIH STEL:881 MG/M3;250 PPM

Ingred Name:ANTI MAR AGENT & lt; Wt:.1

Ingred Name:XYLENE CAS:1330-20-7 RTECS #:ZE2100000 &It; Wt:.1 ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3;150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:BENZENE, ETHYL-CAS:100-41-4 RTECS #:DA0700000 < Wt:.1 OSHA PEL:435 MG/M3;100 PPM ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:543 MG/M3;125 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:DIBUTYLTIN DILAURATE CAS:77-58-7 RTECS #:WH7000000 &It; Wt:.1

Ingred Name:CYRIC & TERTIARY AMINE & t; Wt:1.

Ingred Name:TOLUENE CAS:108-88-3 RTECS #:XS5250000 t:1. OSHA PEL:SEE TABLE Z-2 ACGIH TLV:188 MG/M3;50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:FLOW AGENT CAS:26376-86-3 < Wt:1.

Ingred Name:N-METHYLPYRROLIDONE CAS:872-50-4 RTECS #:UY5790000 &It; Wt:1.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: VAPORS ARE IRRITATING TO EYES, NOSE, AND THROAT. INHAL
ATION MAY CAUSE HEADACHE, DIFFICULT
BREATHING AND LOSS OF CONSCIOUSNESS. CHRONIC: PROLONGED CONTACT
WILL CAUSE DRYING AND CRACKING OF THE SKIN, DUE TO DEFATTING ACTION. SKIN SENSITIZATION, ASTHMA OR OTHER ALLERGIC RESPONSES MAY DEVELOP.
Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY TRACT

Effects of Overexposure:INHALATION: IRRITATION OF THE RESPIRATORY TRACT & ACUTE NERVOUS SYSTEM DEPRESSION. SKIN AND EYE CONTACT: CONTACT WITH THE SKIN CAN CAUSE IRRITATION. SYMPTOMS MAY BE SWELLING, REDNESS, AND RASH. EYES: LIQUID,

AEROSOLS OR VAPORS ARE IRRITATING AND MAY CAUSE TEARING, REDNESS, AND SWELLING ACCOMPANIED BY A STINGING SENSATION. SKIN ABSORPTION: PROLONGED AND REPEATED CONTACT CAN CAUSE MODERATE IRRITATIO N, DRYING, AND DEFATTING OF THE SKIN WHICH CAN CAUSE THE SKIN TO CRACK. INGESTION: CAN RESULT IN IRRITATION AND POSSIBLE CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT.

Medical Cond Aggravated by Exposure:ASTHMA AND OTHER RESPIRATORY DISORDERS. SKIN ALLERGIES, ECZEMA, AND DERMITITIS.

First Aid:INHALATION: MOVE TO AN AREA FREE FROM RISK OF FURTHER EXPOSURE. RESTORE BREATHING. ASTHMATIC TYPE SYMPTOMS MAY DEVELOP AND MAY BE IMMEDIATE OR DELAYED BY SEVERAL HOURS. OBAIN MEDICAL CONDITION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. WASH CONTAMINATED CLOTHES BEFORE REUSE. EYES: FLUSH WITH CLEAN LUKEWARM WATER (LOW PRESSURE ) FOR AT

LEAST 15 MINUTES, OCCASIONALLY LIFTING EYELIDS. OBTAIN MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:=7.2C. 45.F Lower Limits:.60% Upper Limits:13.10% Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, WATER SPRAY Fire Fighting Procedures: FULL FIRE FIGHTING EQUIPMENT WITH SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING SHOULD BE WORN BY FIRE FIGHTERS. WATER MAY USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP, AUTO IGNITION OR EXPLOSION. Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS. DURING EMERGENCY COND

ITIONS OVEREXPOSURES TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

Spill Release Procedures: EVACUATE ALL NON-ESSENTIAL PERSONNEL, REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES). VENTILATE AREA. CONTAIN AND REMOVE INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling and Storage Precautions:STORE IN BUILDINGS DESIGNED TO COMPLY

WITH OSHA 1910.106. AVOID STORING NEAR HIGH TEMPERATURES, FIRE, OPEN FLAMES, AND SPARK SOURCES. STORE IN TIGHTLY CLOSED CONTAINERS. STORE IN WELL VENTILATED AREAS.

Other Precautions:KEEP CONTAINERS TIGHT AND UPRIGHT TO PREVENT LEAKAGE. PREVENT PROLONGED BREATHING OF VAPORS OR SPRAY MISTS. PROLONGED OVEREXPOSURE MAY CAUSE AN ALLERGIC REACTION. AVOID CONTACT WITH SKIN AND EYES. DO NOT TAKE INTERNALLY. DO NOT HANDLE UNTIL THE MANUFACTURERS SAFETY PRECAUTIONS H AVE BEEN READ AND UN DERSTOOD.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: A RESPIRATOR THAT IS RECOMMENDED OR APPROVED FOR USED IN AN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING OR FRESH AIR SUPPLIED) IS NECESSARY. OBSERVE OHSA REGULATIONS FOR RESPIRATOR USE.

Ventilation:EXHAUST VENTILATION SUFFICIENT TO KEEP THE AIRBORNE CONCENTRATIONS OF SOLVENT VAPORS OR MISTS BELOW THEIR RESPECTIVE TLV'S MUST BE UTILIZED.

Protective Gloves:PR

OTECTIVE GLOVES ARE RECOMMENDED

Eye Protection: SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES OR FACE SHIELD.

Other Protective Equipment:THE USE OF LONG SLEEVES AND LONG LEG CLOTHING IS RECOMMENDED. REMOVE AND WASH CONTAMINATED CLOTHING BEFORE.

Supplemental Safety and Health

Boiling Pt:=100.6C, 213.F B.P. Text:213-401F Vapor Density:> AIR Spec Gravity:1.55702 VOC Pounds/Gallon:275 Viscosity:THIN TO HEAVY MATERIAL

Evaporation Rate & amp; Reference:.93 X N-BUTYL ACETATE Solubility in Water:INSOLUBLE Appearance and Odor:WHITE LIQUID WITH SOLVENT ODOR Percent Volatiles by Volume:31.4%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OR OPEN FLAMES Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN

====== Disp

Waste Disposal Methods:WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS. EMPTY CONTAINERS MUST BE HANDLE WITH CARE, DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED CONTAINERS.

SARA Title III Information:SARA 313 THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO THE REPORTING REQUIREM ENTS OF

SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND OF 40 CFR 372. 1330- 20-7 XYLENE 0.05% 100-41-4 ETHYL BENZENE 0.02% 108-88-3 TOLUENE 0.12%

State Regulatory Information: PROP 65-TERATOGENIC WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM. 108-88-3 TOLUENE

Disclaimer (provided with this information by the compiling agencies):

This information is formulated f

or use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.