

ASHLAND CHEMICAL CO -- AA 3-007 -- 8010-01-441-5940

=====
===== Product Identification =====

Product ID:AA 3-007
MSDS Date:01/26/1998
FSC:8010
NIIN:01-441-5940
Status Code:A
MSDS Number: CLMHR
=== Responsible Party ===
Company Name:ASHLAND CHEMICAL CO
Box:2219
City:COLUMBUS
State:OH
ZIP:43216-2219
Country:US
Info Phone Num:614-790-3333/800-274-5263
Emergency Phone Num:1-800-274-5263
Preparer's Name:ERN
EST CARTER
Chemtrec Ind/Phone:(800)424-9300
CAGE:34897

==== Contractor Identification ====

Company Name:ASHLAND CHEMICAL CO
Box:2219
City:COLUMBUS
State:OH
ZIP:43216-2219
Country:US
Phone:614-790-3333/800-274-5263
CAGE:34897

=====
===== Composition/Information on Ingredients =====

Ingred Name:ALIPHATIC PETROLEUM DISTILLATES
CAS:64742-89-8
Code:F
Minumum % Wt:54.
Maxumum % Wt:58.

Ingred Name:ISOBUTYL ISOBUTYRATE
CAS:97-85-8
RTECS #:NQ5250000
Minumum % Wt:18.
Maxumum % Wt:22.

Ingred

Name:ISOPROPANOL
CAS:67-63-0
RTECS #:NT8050000
Minumum % Wt:18.
Maxumum % Wt:22.
OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:ETHYL ACETATE
CAS:141-78-6
RTECS #:AH5425000
Minumum % Wt:2.3
Maxumum % Wt:6.
OSHA PEL:1400 MG/M3;400 PPM
ACGIH TLV:1440 MG/M3;400 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards A

cute and Chronic:EYE: SYMPTOMS INCLUDE STINGING,

TEARING, REDNESS, AND SWELLING OF EYES. SKIN: SYMPTOMS MAY INCLUDE REDNESS, BURNING, DRYING AND CRACKING OF SKIN, AND SKIN BURNS.

SWALLOWING: LARGE AMOUNTS MAY BE HAR MFUL. THIS MATERIAL CAN GET INTO THE LUNGS DURING SWALLOWING OR VOMITING. INHALATION:

BREATHING LARGE AMOUNTS MAY BE HARMFUL. SYMPTOMS USUALLY OCCUR AT AIR CONCENTRATIONS HIGHER THAN THE RECOMMENDED EXPOSURE LIMITS.

Effects of Overexposure:SIGNS AND SYMPT

OMS OF EXPOSURE TO THIS MATERIAL

THROUGH BREATHING, SWALLOWING, AND/OR PASSAGE OF THIS MATERIAL THROUGH THE SKIN MAY INCLUDE: STOMACH OR INTESTINAL UPSET, NAUSEA, VOMITING, DIARRHEA, IR RITATION, (NOSE, THROAT, AIRWAYS), CENTRAL NERVOUS SYSTEM DEPRESSION (DIZZINESS, DROWSINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE, UNCONSCIOUSNESS), LOW BLOOD PRESSURE, MILD TEMPORARY CHANGES IN THE LI VER, EFFECTS ON HEART RATE, RESPIRATORY DEPRESSION, (SLOWING OF BREATHING), LOSS OF

COORDINATION, CONFUSION, LUNG EDEMA (FLUID BUILDUP IN THE LUNG TISSUE) KIDNEY DAMAGE AND COMA.

Medical Cond Aggravated by Exposure: MATERIAL IS ASPIRATION HAZARD.

DANGER FROM ASPIRATION MUST BE WEIGHED AGAINST ORAL TOXICITY WHEN DECIDING WHETHER TO INDUCE VOMITING.

===== First Aid Measures =====

First Aid: EYES: MOVE PERSON AWAY TO FRESH AIR. FLUSH GENTLY WITH WATER AT LEAST 15 MINUTES WHILE HOLDING EYELIDS APART. SKIN: REMOVE

CONTAMINATED CLOTHING. WASH EXPOSED AREA WITH SOAP AND WATER.

LAUNDER CLOTHING. SWALLOWING: IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH. PLACE PERSON ON LEFT SIDE WITH THE HEAD DOWN. INHALATION: MOVE PERSON INTO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. KEEP PERSON WARM AND QUIET.

===== Fire Fighting Measures =====

Flash Point Method: TCC

Flash Point: =10.C, 50.F

Lower Limits: 1.0%

Upper Limits: 12.0%

Extinguishing

Media: REGULAR FOAM, CARBON DIOXIDE, DRY CHEMICAL.

Fire Fighting Procedures: WEAR A SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WITH APPROPRIATE TURN-OUT GEAR AND CHEMICAL RESISTANT PERSONAL PROTECTIVE EQUIPMENT.

Unusual Fire/Explosion Hazard: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC

MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT LOCATIONS.

NEVER USE WELDING TORCH NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT CAN IGNITE EXPLOSIVELY

===== Accidental Release Measures =====

Spill Release Procedures: ABSORB LIQUID ON VERMICULITE, FLOOR ABSORBENT.

LARGE SPILL: ELIMINATE IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL

CLEAN-UP HAS

BEEN COMPLETED. STOP SPILL AT SOURCE. PREVENT FROM ENTERING DRAINS,
SEWERS, STREAMS, OR OTHER WATER BODIES. PREVENT FROM SPREADING.
ABSORB UNRECOVERABLE PR

=====
===== Handling and Storage =====

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE
HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT
RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS
GIVEN IN THE DATA SHEET MUST BE OBSERVED
. ALL 5 GALLON PAILS AND
LARGER METAL CONTAINERS, INCLUDING TANK CARS AND TANK TRUCKS SHOULD
BE GR

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF WORKPLACE EXPOSURE LIMITS OF PRODUCT OR ANY
COMPONENT IS EXCEEDED (SEE EXPOSURE GUIDELINES) A NIOSH/MSHA
APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL
EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV'S.

Protective Glove

s:WEAR RESISTANT GLOVES.

Eye Protection:CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA
REGULATIONS ARE ADVISED)

Other Protective Equipment:IMPREVIOUS CLOTHING AND BOOTS.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:=75.6C, 168.F

Vapor Pres:76.000 MMHG @ 58.00 F

Vapor Density:.1, AIR=1

Spec Gravity:.782@77.00 F

VOC Pounds/Gallon:782

VOC Grams/Liter:6.51

Evaporation Rate & Reference:SLOWER THAN ETHYL

=====
===== S

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

ACETALDEHYDE, ACIDS, CHLORINE, ETHYLENE OXIDE ISOCYANATES, STRONG ALKALIES, STRONG OXIDIZING AGENTS.

Stability Condition to Avoid: DO NOT USE WITH ALUMINUM EQUIPMENT AT TEMPERATURES ABOVE 120 F

Hazardous Decomposition Products: CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS.

===== Toxicological Information =====

Toxicological Information: SILICON: LD50 (ORAL, RAT) 3160 MG/KG.

MANGANESE: LD50 (ORAL, RAT) 9,000 MG/KG. IRON: INTRAPERITONEAL RABBIT LDL0: 20 MG/KG - NO TOXIC EFFECT NOTED.

===== Ecological Information =====

Ecological: NOT AVAILABLE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

===== MSDS Transport Information =====

Transport Info

Information: CONTAINER/MODE: 55 GAL DRUM/TRUCK PACKAGE NOS

COMPONENT: NOT APPLICABLE RQ (REPORTABLE QUANTITY) -49 CFR 172.101

PRODUCT QUANTITY: (50000 LBS) COMPONENT: BENZENE

===== Regulatory Information =====

Federal Regulatory Information: CERCLA RQ: ETHYL ACETATE: 5000 LB RQ;

State Regulatory Information: CALIFORNIA CARCINOGENS: BENZENE,

ACETALDEHYDE; NJ RIGHT TO KNOW: NAPHTHA, SOLVENT, 64742-89-8, ISOBUTYL ISOBUTYRATE, 97-85-8, ISOPROPYL ALCO

HOL, 67-63-0, ETHYL

ACETATE, 141-78-6; PA RIGHT TO KNOW: ALIPHATIC PETROLEUM

DISTILLATES: 64742-89-8, 2-PROPANOL: 67-63-0, ACETIC ACID ETHYL

ESTER: 141-78-6

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information t

o be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.