View NSN Online: https://aerobasegroup.com/nsn/8040-00-779-4704

DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV. -- HYSOL RE2038 EPOXY RESIN COMPOUND -- 8040-00-779-4704

============= Product Identification ========================

Product ID:HYSOL RE2038 EPOXY RESIN COMPOUND

MSDS Date:07/14/1998

FSC:8040

NIIN:00-779-4704 Status Code:A

MSDS Number: CLMJG === Responsible Party ===

Company Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV.

Address:211 FRANKLIN ST.

City:OLEAN State:NY

ZΙ

P:14760-1297 Country:US

Info Phone Num:716-372-6300/6309 Emergency Phone Num:1-800-424-9300 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:04347

=== Contractor Identification ===

Company Name: DEXTER CORP THE DEXTER ELECTRONIC MATERIAL DIV

Address:211 FRANKLIN ST.

Box:City:OLEAN

State:NY

ZIP:14760-1297 Country:US

Phone:716-372-6300/6309

CAGE:04347

====== Composition/Information on Ingredients ========

Ingred Name: BISPHENOL A-EPICHLOROHYDRIN EPOXY RESIN

CAS:250 68-38-6

RTECS #:CE6880000 Minumum % Wt:60. Maxumum % Wt:100.

Ingred Name: OXIRANE, (BUTOXYMETHYL)-

CAS:2426-08-6

RTECS #:TX4200000 Minumum % Wt:10. Maxumum % Wt:30.

OSHA PEL:270 MG/M3;50 PPM ACGIH TLV:133 MG/M3;25 PPM

========== Hazards Identification ================

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:EYE CONTACT: CONTACT MAY CAUSE EYE

IRRITATION. SKIN CONTACT: PROLONGED OR REPEATED SKIN CONTACT MAY

**CAUSE IRRIT** 

ATION. CONTACT WITH PRODUCT AT ELEVATED TEMPERATURES
(>1501/2 C) CAN RESULT IN THERMAL BURNS. INHALATION: MAY CAUSE
ALLERGIC RESPIRATORY REACTION SUCH AS ASTHMA. INGESTION: MODERATELY
TOXIC, MAY CAUSE VOMITIN

Medical Cond Aggravated by Exposure:PREEXISTING SKIN OR LUNG ALLERGIES MAY INCREASE THE CHANCE OF DEVELOPING INCREASED ALLERGIC SYMPTOMS FROM EXPOSURE TO THIS PRODUCT.

First Aid:EYE CONTACT: WASH/FL USH EYES WITH WATER FOR MINIMUM TEN(10) MINUTES. SKIN CONTACT: WASH OFF IN FLOWING WATER OR SHOWER. INHALATION: MOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. Flash Point Method:CC Flash Point:=73.3C, 164.F Autoignition Temp: Autoignition Temp Text: NONE Lower Limits: NONE **Upper Limits:NONE** Extinguishing Media: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM. Fire Fighting Procedures: RECOMMENDED USE OF SELF-CONTAINE **D BREATHING** APPARATUS. Spill Release Procedures: CONTAIN SPILL IN NATURAL FORM OR WITH SAND OR DIRT (INERT MATERIAL). ELIMINATE ALL IGNITION SOURCES. PREVENT RUNOFF TO STORM SEWERS, DITCHES AND WATERWAYS. SHOVEL OR SCRAPE (NON METALLIC) ABSORBED WAS TE MATERIALS INTO DISPOSAL CONTAINER. SEAL LID TIGHTLY WITH TAPE OR LOCKING RING AND LABEL PROPERLY. CLEAN UP SPILL IMMEDIATELY, OBSERVING PRECAUTIONS INCLUD ING ADEQUATE VENTILATION AND/OR PERSONAL PR ============= Handling and Storage ========================== Handling and Storage Precautions: PLASTIC CONTAINERS MAY BE SLIPPERY WHEN HANDLING. STORAGE: KEEP CONTAINERS CLOSED AND TIGHTLY SEALED. ====== Exposure Controls/Personal Protection ========

Respiratory Protection: A RESPIRATOR IS REQUIRED IF INGREDIENT EXPOSURE LIMITS ARE NOT EXCEEDED. AN OSHA APPROVED (29 CFR 1910.134 USA

DEPT. OF LABOR). AIR PURIFYING

RESPIRATOR WITH APPROPRIATE CARTRIDGE SHOULD BE USED IF EX POSURE LIMITS ARE EXCEEDED. Ventilation: USE LOCAL EXHAUST VENTILATION. Protective Gloves:GLOVES PVC, RUBBER (NITRILE, BUTYL). Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS GOGGLES FULL FACE SHIELDS. Other Protective Equipment: A SAFETY SHOWER AND EYE WASH STATION SHOULD BE WITHIN REASONABLE DISTANCE OF THE WORK AREA. Supplemental Safety and Health ========= Physical/Chemical Properties =========== Vapor P res:(MM HG) Vapor Density:3.8 Spec Gravity:1.2 Evaporation Rate & Dr.; Reference:1.0 Solubility in Water: INSOLUBLE Appearance and Odor:LIQUID, LOW VISCOSITY, AMBER COLOR, AROMATIC ODOR ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HIGH TEMPERATURE, OPEN FLAMES. Hazardous Decomposition Products: CARBON DIOXIDE. CARBON MONOXIDE. POSSIBLE ORGANICS. Conditions to Avoid Polymeriz ation:EXOTHERMIC.

======== Toxicological Information ===========

Toxicological Information:PHOSPHORIC ACID: INHALATION LC50-N.D.; ORAL LD50 (RATS)-1530 MG/KG; DERMAL LD50 (RABBIT)-2750 MG/KG. NITRIC ACID: INHALATION LC50-115 PPM; ORAL LD50 (RATS)-50-500 MG/KG; DERMAL LD50 (RABBIT)-N.D. MUTA GENICITY: NOT KNOWN TO BE MUTAGENIC. TERATOGENICITY: NOT KNOWN TO NE TERATOGENIC. REPRODUCTIVE TOXICITY: NOT KNOWN TO HAVE REPRODUCTIVE TOXICITY.

================

Waste Disposal Methods: DISPOSAL OF WASTE PROPERLY AND IN ACCORDANCE WITH LEGAL REQUIREMENTS. Transport Information: HAZARD CLASS: 8. LABEL: NONE. DOT PROPER SHIPPING NAME: COMPOUND, CLEANING, LIQUID (PHOSPHORIC ACID, NITRIC ACID), 8, NA1760, III, LTD. QTY. ========== Regulatory Information =========================== SARA Title III Information: SARA (TITLE I II)-SECTION 302, 311, 312, & 313: SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355): THIS PRODUCT CONTAINS NITRIC ACID WHICH IS ON THE LIST OF EXTREMELY HAZARDOUS SUBSTANCES. SECTIO N 311 AND 312 MSDS SUBMISSION & INVENTORY REPORTING (40 CFR 370): THIS PRODUCT CONTAINS PHOSPHORIC ACID & NITRIC ACID THAT REQUIRE REPORTING UNDER 311 & 312, IF STORED IN LARGE ENOUGH QUANTITIES. SECT ION 313 TOXIC CHEMICAL RELEASES REPORTING: THIS PRODUCT CONTAINS PHOSPHORIC ACID & **NITRIC** 

ACID WHICH MAY REQUIRE REPORTING UNDER 313.

Federal Regulatory Information:TOXIC SUBSTANCE CONTROL ACT (TSCA): THIS PRODUCT COMPLIES WITH RULES AND REGULATIONS OF TSCA. CERCLA/SUPERFUND, 40 CFR 117, 302: THIS PRODUCT CONTAINS PHOSPHORIC ACID AND NITRIC ACID, BOTH REPORTABLE QUANTITIES (RQ) SUBSTANCES, & IF 100,000 POUNDS OF PRODUCT ARE RELEASED, THE NATIONAL RESPONSE CENTER, WASHINGTON D.C. MUST BE NOTIFIED (1-800-424-8802).

State Regulatory Information: CALIFORNIA

PROPOSITION 65: THIS PRODUCT

DOES NOT CONTAIN ANY MATERIAL, THAT CURRENTLY LISTED BY THE STATE OF CALIFORNIA UNDER PROPOSITION 65. NEW JERSEY AND PENNSYLVANIA RIGHT TO KNOWN INFORMATION: WA TER (7732-18-5), PHOSPHORIC ACID (7664-38-2), NITRIC ACID (7697-37-2), ALUMINUM OXIDE (1344-28-1), CLAY (1318-93-0).

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United Stat

es of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.