## COVENTRY COATINGS -- EPOXY PRIMER CATALST -- 8010-00-082-2450

Product ID: EPOXY PRIMER CATALST MSDS Date:06/24/1998 FSC:8010 NIIN:00-082-2450 Status Code:A MSDS Number: CLNNQ === Responsible Party === Company Name: COVENTRY COATINGS Address:55 RAILROAD AVENUE Box:339 City:GARNERVILLE State:NY ZIP:10923 Country:US Info Phone Num:(914)786-3465 **Emergency Phone Num:91** 4-786-3465 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone: (800) 424-9300 CAGE:1PXV4 === Contractor Identification === Company Name: COVENTRY COATINGS Address:55 RAILROAD AVENUE Box:339 City:GARNERVILLE State:NY ZIP:10923 Country:US Phone: (914) 786-3465 CAGE:1PXV4

Ingred Name:BUTYL CELLOSOLVE CAS:111-76-2 RTECS #:KJ8575000 = Wt:10. OSHA PEL:240 MG/M3;50 PPM ACGIH TLV:121 MG/M3;25 PPM

Ingred Name:ISOPROPYL ALCOHOL CAS:67-63-0 R TECS #:NT8050000 = Wt:29. OSHA PEL:980 MG/M3;400 PPM ACGIH TLV:983 MG/M3;400 PPM ACGIH STEL:1230 MG/M3;500 PPM Ingred Name:XYLENE CAS:1330-20-7 RTECS #:ZE2100000 = Wt:47. ACGIH TLV:434 MG/M3;100 PPM ACGIH STEL:651 MG/M3:150 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Effects of Overexposure: DIZZINESS, NAUSEA, VOMITING, LOSS OF COORDINATION, AND FATIGUE. Medical C ond Aggravated by Exposure:ASTHMA, HEART CONDITION. First Aid:SKIN CONTACT:FLUSH WITH WATER.IF REDNESS PERSISTS SEEK MEDICAL ATTENTION. INHALATION: IF RESPIRATORY SYMPTOMS DEVELOP, REMOVE VICTIM FROM SOURCE OF EXPOSURE TO FRESH AIR. IF SYMPTOMS PERSIST SEEK MEDIC AL ATTENTION. INGESTION: SEEK EMERGENCY MEDICAL ATTENTION. Flash Point Method:T CC Flash Point:=27.2C, 81.F **Upper Limits:7%** Extinguishing Media:CO2/FOAM. Fire Fighting Procedures: THE USE OF SCBA IS RECOMMENDED FOR FIRE FIGHTERS. WATER SPRAY MAY BE USEFUL IN IN COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOIDSPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES. FIGH T AS VOLATILE LIQUID FIRE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. USE WATER TO COOL FIRE EXPOSED C Unusual Fire/Explosion Hazard: THIS MATERIAL MAY BE IGNITED

BY HEAT,

SPARKS, FLAME OR STATIC ELECTRICITY.KEEP CONTAINERS CLOSED WHEN NOT IN USE. ISOLATE FROM HEAT, SPARKS, PILOT LIGHTS SMOKING MATERIALS AND OTHER SOURCES OF IGNITIO N.

Spill Release Procedures: STAY UPWIND. REMOVE SOURCE OF IGNITION. KEEP OUT OF DRAINS SEWERS, WATERWAYS USE ABSORBENT PADS.

Handling and Storage Precautions:KEEP IN COOL P ROPERLY VENTILATED EXPLOSION PROOF AREA. Other Precautions:KEEP AWAY FROM HEAT SPARKS, AND OPEN FLAMES. USE

APPROVED GROUNDING EQUIPMENT TO AVOID STATIC SPARKS. THIS PRODUCT CONTAINS XYLOL AND IS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA 313 AND 40 CFR 37 2.

Respiratory Protection:APPROVED ORGANIC SUPPLIED AIR RESPIRATOR. Ventilation:MECHANICAL EXPLOSIONPROOF. Protective Gloves:YES. Eye Protection:YES. Othe r Protective Equipment:IMPERVIOUS CLOTHING. Work Hygienic Practices:WASH BEFORE EATING. Supplemental Safety and Health

Boiling Pt:B.P. Text:282.00-286.00 F Vapor Density:HEAVIER VOC Grams/Liter:7.15 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:NIL Appearance and Odor:AMBER FLUIF

Stability Indicator/Materials to Avoid:YES Stability

Condition to Avoid:HEAT, SPARKS OPEN FLAMES, STATIC ELECTRICITY. Hazardous Decomposition Products:CO2. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods: DISPOSE PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Uni

ted States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.