

AKRON PAINT AND VARNISH INC -- WALKWAY TYPE I LIGHT GULL GRAY, G-8605 --  
8010-00-141-7842

=====  
Product Identification  
=====

Product ID:WALKWAY TYPE I LIGHT GULL GRAY, G-8605

MSDS Date:02/04/1999

FSC:8010

NIIN:00-141-7842

Status Code:A

MSDS Number: CLNNR

=== Responsible Party ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Info Phone Num:216-773-8911

Emergency Phone Num:330-773-8911

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:70228

=== Contractor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM&P NAPHTHA

CAS:64742-89-8

Code:F

Minumum % Wt:20.

Maxumum % Wt:50.

OSHA PEL:300 PPM

ACGIH TLV:300

PPM

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

Minumum % Wt:1.

Maxumum % Wt:5.

OSHA PEL:100 PPM

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====  
===== Hazards Identification =====

Effects of Overexposure:EYES: CAN CAUSE REDNESS, IRRITATION, SWELLING AND BLURRED VISION. SKIN: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS. BREATHING: CAN CAUSE RESPIRATORY

IRRITATION , DIZZINESS, WEAKNESS, FATIGUE NAUSEA, HEADACHE, UNCONSCIOUSNESS.AND EVEN ASPHYXIATION.SWALLOWING: CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA; ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.LIFT EYELIDS OCCASIONALLY, GET PROMPT MEDICAL ATTENTION.SKIN: WASH TH

OROUGHLY WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING PROMPTLY;WASH CLOT HING BEFORE REUSE. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.SWALLOWING:SINCE THIS PRODUCT MAY CONTAIN MATERIALS WHICH CAN CAUSE LUNG DAMAGE IF ASPIRATED INTO THE LUNGS,THE DECISION WHETHER TO IN DUCE VOMITING MUST BE MADE BY A PHYSICIAN AFTER CAREFUL CONSIDERATION OF ALL MATERIALS INGESTED. INHALATION: MOVE AFFECTED PERSON TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN.

IF BRE ATHING HAS STOPPED, GIVE ARTIFICIAL RES

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:=10.C, 50.F

Lower Limits:0.90%

Upper Limits:12.30%

Extinguishing Media:CARBON DIOXIDE DRY CHEMICAL FOAM WATER FOG. USE WATER FOR COOLING MATERIAL STORED IN VICINITY OF FIRE.

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE. WEAR PROTE

CTIVE CLOTHING.

Unusual Fire/Explosion Hazard:VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND TO AN IGNITION SOURCE SOME DISTANCE FROM MATERIAL HANDLING OINT. IGNITION SOURCES INCLUDE PILOT LIGHTS, SMOKING, HEATERS, ELECTRIC MOTORS, SPARKS FROM ELECTRICAL SWITCHES AND STATIC DISCHARGES.NEVER USE CUTTING TORCH ON EMPTY CONTAINERS!

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: ABSORB LIQUID WITH RAGS, FLOOR ABSORBENT, VERMICULITE OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD. LARGE SPILL: ELIMINATE ALL IGNITION SOURCES DIKE AREA OF SPILL TO PREVENT SPREADING . VENTILATE AREA IF INDOORS PUMP LIQUID INTO SALVAGE TANK REMAINING LIQUID MAY BE TAKEN UP WITH SAND, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS PREVENT RUN OFF TO SEWERS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT DROP CONTAINERS. AVOID HEAT, SPARKS, AND OPEN FLAME. STORE LARGE QUANTITIES ONLY IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. NEVER USE PRESSURE TO EMPTY. AVOID BREATHING SANDING DUST.DO NOT HANDLE UNTIL THE MANUFACTURERS SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

Other Precautions:THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE ORIGINATING WITH THE COMPANY OR NOT.RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE

INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN AREAS WITH UNRESTRICTED VENTILATION APPROVED CHEMICAL/MECHANICAL FILTERS DESIGNED TO REMOVE A COMBINATION OF PARTICULATES AND VAPOR. IN CONFINED AREAS, APPROVED AIR LINE TYPE RESPIRATORS OR HOODS.

Ventilation:PROVIDE SUFFICIENT VENTILATION IN VOLUME AND PATTERN TO KEEP AIR CONTAMINANT CO

NC BELOW CURRENT OSHA PEL OR ACGIH TLV  
LIMITS, VOLATILES BELOW VOLATILE LIMIT.  
Protective Gloves:WEAR RESISTANT GLOVES SUCH AS NITRILE RUBBER.  
Eye Protection:CHEMICAL SPLASH GOGGLES. ARE SAFETY GLASSES.  
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:240-289 DEG F  
Vapor Density:HEAVIER  
Spec Gravity:1.27011  
Evaporation Rate & Reference:6.5 X N-BUTYL ACETATE  
Appearance and Odor:LT GULL GRAY  
Percent Volatiles by Volume:54.1%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
AVOID CONTACT WITH STRONG OXIDIZERS. ( LIKE NITRIC ACID)  
Stability Condition to Avoid:KEEP AWAY FROM HEAT AND OPEN FLAME.  
Hazardous Decomposition Products:MAY FORM CARBON MONOXIDE AND DIOXIDE,  
VARIOUS HYDROCARBONS, ETC.  
Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND  
LOCAL REGULATIONS.

===== Regulatory Information =====

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
e

xpressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.