

CUSTOM AEROSOL PACKAGING -- AEROSOL,PAINT -- 8010-00-137-9150

=====  
Product Identification  
=====

Product ID:AEROSOL,PAINT

MSDS Date:08/31/1988

FSC:8010

NIIN:00-137-9150

Status Code:A

MSDS Number: CLNWH

=== Responsible Party ===

Company Name:CUSTOM AEROSOL PACKAGING

Address:128 E WATER ST

City:PIQUA

State:OH

ZIP:45356

Country:US

Info Phone Num:513-773-1824

Emergency Phone Num:800-424-9300

Preparer

's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:0G0J3

=== Contractor Identification ===

Company Name:CUSTOM AEROSOL PACKAGING

Address:128 E WATER ST

Box:City:PIQUA

State:OH

ZIP:45356

Country:US

Phone:513-773-1824

CAGE:0G0J3

=====  
Composition/Information on Ingredients  
=====

Ingred Name:VM&P NAPTHA

CAS:8030-30-6

Code:F

RTECS #:DE3030000

= Wt:10.

OSHA PEL:400 MG/M3;100 PPM

ACGIH TLV:1590 MG/M3;400 PPM

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

&lt; Wt:5.1

A

CGIH TLV:434 MG/M3;100 PPM  
ACGIH STEL:651 MG/M3;150 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:SECONDARY BUTYL ALCOHOL OR 2-BUTYL  
&lt; Wt:5.

Ingred Name:AROMATIC HYDROCARBON  
CAS:64742-95-6  
Code:F  
RTECS #:WF3400000  
&lt; Wt:5.

Ingred Name:LOW ODOR MINERAL SPIRITS  
CAS:8032-32-4  
Code:F  
RTECS #:OI6180000  
&lt; Wt:5.  
ACGIH TLV:1370 MG/M3;300 PPM

Ingred Name:ACETONE  
CAS:67-64-1  
RTECS #:AL3150000  
= Wt:15.  
OSHA PEL:2400 MG/M3;1000 PPM  
ACGIH TLV:1780 MG/M3;750 PPM  
ACGIH STEL:2380 MG/M3;1  
000 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISO-BUTYL KETONE  
CAS:108-10-1  
RTECS #:SA9275000  
&lt; Wt:5.  
OSHA PEL:410 MG/M3;100 PPM  
ACGIH TLV:205 MG/M3;50 PPM  
ACGIH STEL:307 MG/M3;75 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL  
CAS:71-36-3  
RTECS #:EO1400000  
&lt; Wt:5.  
OSHA PEL:300 MG/M3;100 PPM  
ACGIH STEL:C152 MG/M3;C50 PPM  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:1,1,1-TRICHLOROETHANE  
CAS:71-55-6  
RTECS #:KJ2975000  
= Wt:25.  
OSHA

PEL:1900 MG/M3;350 PPM  
ACGIH TLV:1910 MG/M3;350 PPM  
ACGIH STEL:2460 MG/M3;450 PPM  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:PROPANE  
CAS:74-98-6  
RTECS #:TX2275000  
= Wt:15.  
OSHA PEL:1800 MG/M3;1000 PPM

Ingred Name:ISOBUTANE  
CAS:75-28-5  
RTECS #:TI4300000  
= Wt:5.

===== Hazards Identification =====

Effects of Overexposure:INGESTION: HARMFUL OR FATAL IF SWALLOWED. EYE CONTACT: PRIMARY IRRITANT. SKIN CONTACT: PRIMARY IRRITANT.  
INHALATION: HIGH CONCENTRATIONS OF VAPORS ARE ANESTHETIC, WILL IRRITATE THE RESPIRATORY TRACT AND CAUSE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY DROWSINESS, LIGHTHEADEDNESS, HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS OR COMA.  
Medical Cond Aggravated by Exposure:REPORTS HAVE SHOWN THAT REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS MAY CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

===== First Aid Measures =====

First Aid:INGESTION: DO NOT INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY. EYE CONTACT: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. CALL PHYSICIAN IMMEDIATELY. SKIN CONTACT: WASH AFFECTED AREA WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING. INHALATION: REMOVE TO FRESH AIR. IF NECESSARY APPLY ARTIFICIAL RESPIRATION AND/OR OXYGEN. CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:PM

CC

Lower Limits:2.3

Extinguishing Media:NFPA CLASS B EXTINGUISHERS. (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE BUT MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED. FOG NOLLES ARE PREFERABLE. FIRE FIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLAT E

FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAMES. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY ON HOT SURFACES. TOXIC GASES M AY FORM WHEN PRODUCT IS CONTACTED BY FLAME OR HOT SURFACES. AEROSOL CONTAINERS HOLD EXTREMELY FLAMMABLE GAS AND FLAMMAB

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION AND PROVIDE MAXIMUM VENTILATION. EQUIP. PERSONNEL WITH PROPER RESPI RATORY, SKIN AND EYE PROTECTION. TAKE UP SPILLED MATERIAL WITH SAWDUST, VERMICULITE OR OTHER ABSORBENT MATERIAL AND PLACE IN CONTAINERS FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120 F. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. DO NOT PUNCTURE. KEEP OUT OF REACH OF CHILDREN.

Other Precautions:USE ONLY AROUND EXPLOSION PROOF EQUIPMENT. AVOID PROLONGED BREATHING OF VAPORS. AVOI D CONTACT WITH SKIN. DO NOT TAKE INTERNALLY. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTE NTS OF THE AEROSOL CAN BE HARMFU

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WERA NIOSH/MSHA APPROVED (TC-23-C) PAINT SPRAY OR (TC-19-C) AIR SUPPLIED RESPIRATOR.

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE CONCENTRATION OF INGREDIENTS LISTED IN SECTION II.

P

rotective Gloves:WEAR PROTECTIVE CLOTHING INCLUDING APRON AND GLOVES.

Eye Protection:WEAR CHEMICAL TYPE GOGGLES OR FACE SHIELD.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt: