View NSN Online: https://aerobasegroup.com/nsn/8040-00-582-4596

\_\_\_\_\_\_

-- FIRELAND FLOOR TILE ADHESIVE

MSDS Safety Information

RALRUBE INC.

\_\_\_\_\_ FSC: 8040 NIIN: 00-582-4596 MSDS Date: 02/01/1998 MSDS Num: CLNWV Product ID: FIRELAND FLOOR TILE ADHESIVE MFN: 01 **Responsible Party** Cage: 6X798 Name: RALRUBE INC. Address: 36977 FOX GLEN City: FARMINGTON HILLS MI 4833 1 Info Phone Number: 248-661-0260 Emergency Phone Number: 800-424-9300 Preparer's Name: ERNEST CARTER Chemtrec IND/Phone: (800)424-9300 Review Ind: Y Published: Y \_\_\_\_\_ Contractor Summary \_\_\_\_\_\_ Cage: 6X798 Name: RALRUBE INC. Address: 36977 FOX GLEN City: FARMINGTON HILLS MI 48331 Phone: 248-661-0260, FAX 248-661-3941 \_\_\_\_\_ Item Description Informa tion \_\_\_\_\_\_ Item Manager: GSA Item Name: ADHESIVE Specification Number: MIL-A-21016 Unit of Issue: GL UI Container Qty: 4 Type of Container: METAL \_\_\_\_\_ Health Hazards Data \_\_\_\_\_ Route Of Entry Inds - Inhalation: YES Ingestion: YES First Aid: IN CASE OF EYE CONTACT, FLUSH EYES WITH WATER FOR FIFTEEN(15) MINUTES. \_\_\_\_\_

\_\_\_\_\_

Handling and Disposal

\_\_\_\_\_ Spill Release Procedures: SCOOP MATERIAL INTO DOT APPROVED CONTAINER. REMOVE TO SAFE PLACE WHERE MATERIAL CAN DRY. Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL DISPOSAL **REGULATIONS.** Handling And Storage Precautions: AVOID EXTREME HEAT OR COLD. Other Precautions: KEEP OUT OF REACH OF CHILDREN.USE ONLY AS DIRECTED ON LABEL. CLOSE CONTAINER AFTER EACH USE. DO NOT RE-USE CONTAIN ER. AVOID SKIN AND EYE CONTACT. \_\_\_\_\_\_ Fire and Explosion Hazard Information Flash Point Method: CALC Flash Point: =93.3C, 200.F \_\_\_\_\_ Control Measures \_\_\_\_\_ Ventilation: USE WITH ADEQUATE VENTILATION. OPEN DOORS AND WINDOWS, AND UTILIZE OTHER MEANS TO ASSURE FRESH AIR ENTRY AND EXHAUST. SLIGHT ODOR OF ASPHALT MAY EXIST. Eye Protection: GLASSES TO AVOID SPLASHES. Work Hygienic Practices: WASH SKIN WITH SOAP AND WATER OR HAND CLEANER. \_\_\_\_\_ Physical/Chemical Properties \_\_\_\_\_ B.P. Text: 212-250 F Vapor Density: HEAVIER VOC Pounds/Gallon: 8.6 Evaporation Rate & amp; Reference: SLOWER THAN ETHER Solubility in Water: 35-45% Percent Volatiles by Volume: 35-45% \_\_\_\_\_ Reactivity Data \_\_\_\_\_ Stability Indicator: YES Hazardous Polymerization Indicator: NO Conditions To Avoid Polymerization: WILL NOT OCCUR. \_\_\_\_\_ HAZCOM Label \_\_\_\_\_ Product ID: FIRELAND FLOOR TILE ADHESIVE Cage: 6X798 Company Name: RALRUBE INC. Street: 36977 FOX GLEN **City: FARMINGTON HILLS MI** Zipcode: 48331 Health Em

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by o

\_\_\_\_\_

r to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department

of Defense or other government situation.