

VIMASCO CORP -- LAGGING ADHESIVE & COATING 713 WHITE & RED -- 8040-01-101-3866

=====  
Product Identification  
=====

Product ID:LAGGING ADHESIVE & COATING 713 WHITE & RED

MSDS Date:04/16/1998

FSC:8040

NIIN:01-101-3866

Status Code:A

MSDS Number: CLNWZ

=== Responsible Party ===

Company Name:VIMASCO CORP

Box:516

City:NITRO

State:WV

ZIP:25143

Country:US

Info Phone Num:304-755-3328

Emergency Phone Num:304-

755-3328

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:14947

=== Contractor Identification ===

Company Name:VIMASCO CORP

Box:516

City:NITRO

State:WV

ZIP:25143

Country:US

Phone:304-755-3328

CAGE:14947

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYLENE GLYCOL

CAS:107-21-1

RTECS #:KW2975000

= Wt:1.5

ACGIH STEL:C127 MG/M3;C50 PPM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:VINYL ACETATE-DIBUTYL MALEATE POLYMER

CAS:25035-90-9

= Wt:14.

Ingred Name:HEXYLENE GLYCOL  
CAS:107-41-5  
RTECS #:SA0810000  
= Wt:.5  
ACGIH STEL:C121 MG/M3;C25 PPM

Ingred Name:CHLORINATED PARAFFIN  
CAS:63449-39-8  
RTECS #:RV0450000  
= Wt:6.

===== Hazards Identification =====

Health Hazards Acute and Chronic:ETHYLENE GLYCOL: CAN CAUSE SKIN AND EYE IRRITATION. EXCESSIVE INHALATION CAN CAUSE NASAL AND RESPIRATORY IRRITATION.INGESTION CAUSES DRUNKENNESS, RAPIDLY PASSING INTO COMA, WITH SERIOUS KIDNEY INJURY AND/OR DEATH.

Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING LUNG DISORDERS MAY BE MORE SUSCEPTIBLE.

===== First Aid Measures =====

First Aid:SKIN: WASH WITH SOAP AND WATER. EYES: FLUSH WITH CLEAN WATER AT LEAST 15 MINUTES, IF IRRITATION PERSISTS, CONSULT PHYSICIAN. INHALATION: REMOVE TO FRESH AIR.IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.INGESTION: GIVE TWO GLASSES OF WATER, INDUCE VOMITING, CONSULT PHYSICIAN OR POISON CONTROL CENTER, NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

===== Fire Fighting Measures =====

Flash Point Method:TCC  
Flash Point:~100.C, 212.F  
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.  
Fire Fighting Procedures:PRODUCT WILL NOT BURN UNTIL WATER HAS BOILED OR EVAPORATED.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE A

REA. CONTAIN THE LIQUID WITH INERT

MATERIALS SUCH AS SAND. ABSORB LIQUIDS USING AN INERT MATERIAL AND SHOVEL INTO CONTAINERS. PREVENT PRODUCT FROM ENTERING STREAMS OR DRINKING WATER SUPPLIES. BEFORE DRYING, PRODUCT MAY BE WASHED AWAY WITH WATER, AFTER DRYING REMOVE WITH A PAINT SCRAPER OR STRONG SOLVENT. SPILLED PRODUCT MAY BE SLIPPERY, WEAR NON-SKID FOOTWEAR.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: USE WITH ADEQUATE VENTILATION. STORE

INDOORS AT TEMPERATURES OF 45 F TO 90 F.

Other Precautions: FOR INDUSTRY/PROFESSIONAL USE ONLY.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IN RESTRICTED VENTILATION AREAS, USE APPROVED CHEMICAL VAPOR RESPIRATOR. IN APPLICATIONS WHERE MISTS OR SPRAY MAY BE GENERATED, AVOID INHALATION OF AIRBORNE PARTICULATES BY USING AN APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE WITH PREFILTER FOR MIST OR DUST.

Vent

ilation: GENERAL (MECHANICAL) ROOM VENTILATION IS EXPECTED TO BE SATISFACTORY.

Protective Gloves: IMPERVIOUS GLOVES.

Eye Protection: GOGGLES, FACESHIELD, OR OTHER EYE WEAR TO PROTECT FROM SPLASH.

Work Hygienic Practices: THOROUGHLY CLEANSE HANDS AFTER HANDLING.

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

Boiling Pt: =100.C, 212.F

Melt/Freeze Pt: =-3.7C, 25.F

Decomp Temp: =115.6C, 240.F

Vapor Density: LIGHTER

Spec Gravity: 1.29

VOC Pounds/

Gallon: 575

pH: 8.0 TO 9.0

VOC Grams/Liter: .48

Viscosity: 75,000

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: APPRECIABLE

Appearance and Odor: VISCOUS, WHITE OR RED PASTE WITH MILD LATEX ODOR.

Percent Volatiles by Volume: 60%

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

MATERIALS INCOMPATIBLE WITH WATER.

Hazardous Decomposition Products: WILL YIELD CO, CO<sub>2</sub>, HCl,

ANTIMONY-OXYCHLORIDE, AND FRAGMENTED SHORT-

CHAIN HYDROCARBONS.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims

all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.