

FISKE BROTHERS REFINING CO -- LUBRIPLATE -- 4510-00-808-4850

===== Product Identification =====

Product ID:LUBRIPLATE

MSDS Date:01/01/2000

FSC:4510

NIIN:00-808-4850

Status Code:A

MSDS Number: CLPCZ

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:8038

City:TOLEDO

State:OH

ZIP:43605-3843

Country:US

Info Phone Num:419-691-2491

Emergency Phone Num:1-800-255-3924

Preparer's Name:JAMES R. KONTAK

Chemtrec Ind/Phone:(800)424-9300

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Effects of Overexpo

sure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRITATION. HUMAN HEATH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOSURE TO LIQUIDS, VAPORS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PRODUCT HAS A LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY .

=====  
===== First Aid Measures =====  
==

First Aid:EYE: FLUSH WITH CLEAR WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT A PHYSICIAN.  
SKIN: REMOVE ANY CONTAMINATED CLOTHING & WASH WITH SOAP & WARM WATER. IF INJECTED BY HIGH PRESSURE UNDER SKIN, REGARDLESS OF THE APPEARANCE OR ITS SIZE, CONTACT A PHYSICIAN IMMEDIATELY. DELAY MAY CAUSE LOSS OF AFFECTED PART OF THE BODY. INHALATION: VAPOR PRESSURE IS VERY LOW & INHA LATION AT ROOM TEMPERATURE IS NOT A PROBLEM. IF OVERCOME  
BY VAPOR FROM HOT PRODUCT, IMMEDIATELY REMOVE FROM EXPOSURE & CALL A PHYSICIAN. INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT I NDUCE VOMITING.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:=182.2C, 360.F  
Lower Limits:0.9%  
Upper Limits:7.0%  
Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).  
Fire Fighting Procedures:COOL EXPOSED CONTAINERS WITH WATER. USE AIR-SUPPLIED BREATHING EQ  
UIPMENT FOR ENCLOSED OR CONFINED SPACES.  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER WITH SUITABLE PETROLEUM SOLVENT OR ADD ABSORBENT. KEEP PETROLEUM PRODUCTS OUT OF SEWERS AND WATER COURSES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED  
O

