

GE SILICONES -- RTV615B CROSSLINKING AGENTS -- 8030-00-485-9200

===== Product Identification =====

Product ID:RTV615B CROSSLINKING AGENTS

MSDS Date:06/10/1998

FSC:8030

NIIN:00-485-9200

Status Code:A

Kit Part:Y

MSDS Number: CLPGF

=== Responsible Party ===

Company Name:GE SILICONES

Address:260 HUDSON RIVER ROAD

City:WATERFORD

State:NY

ZIP:12188

Country:US

Info Phone Num:518-237-3330

Emergency Phone

Num:518-237-3330

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:01139

=== Contractor Identification ===

Company Name:GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT

Address:260 HUDSON RIVER RD

Box:City:WATERFORD

State:NY

ZIP:12188

Country:US

Phone:518-237-3330/800-332-3390

CAGE:01139

===== Composition/Information on Ingredients =====

Ingred Name:BENZENE

CAS:71-43-2

RTECS #:CY1400000

OSHA PEL:SEE 1910.1028

ACGIH TLV:32 MG/M3;10 PPM

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

< Wt:.5

OSHA PEL:SEE TABLE Z-2

ACGIH TLV:188 MG/M3;50 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:VINYLPOLYDIMETHYLSILOXANE

CAS:68083-19-2

Code:F

RTECS #:VW3300000

Minumum % Wt:30.

Maxumum % Wt:60.

Ingred Name:TRADE SECRET COMPONENT

Minumum % Wt:30.

Maxumum % Wt:60.

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acu

te and Chronic:EYE CONTACT: MAY CAUSE MILD EYE
IRRITATION.

Explanation of Carcinogenicity:THIS PRODUCT OR ONE OF ITS INGREDIENTS
PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED
CARCINOGEN BY NTP, IARC, OR OSHA.

Effects of Overexposure:CLEAR LIQUID MILD ODOR PRODUCT GENERATES
FLAMMABLE GAS ON CONTACT WITH ACIDS, BASES OR OXIDIZING
MATERIALS.AVOID CONTACT WITH ACIDIC, BASIC, OR OXIDIZING
AGENTS.REFER TO OTHER MSDS SECTIONS FOR DETAIL ED INFORMATION.

=====
===== First Aid Measures =====

First Aid:INGESTION: RINSE MOUTH WITH WATER SEVERAL TIMES. SKIN: WASH
WITH SOAP AND WATER. EYES: FLUSH EYES WITH PLENTY OF WATER FOR AT
LEAST 15 MINUTES AND GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TOC

Flash Point:~121.1C, 250.F

Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA.

=====
===== Accidental Release Measures =====

Spill

Release Procedures:WASH WALKING SURFACES WITH DETERGENT AND WATER TO REDUCE SLIPPING HAZARD. WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT SECTION.WIPE, SCRAPE, OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER INTENDED FOR FLAMMABLE MATERIALS FOR DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT REUSE THIS CONTAINER. RELIEVE ANY INTERNAL PRESSURE WHEN RECEIVED AND AT LEAST WEEKLY THEREAFTER BY SLOWLY LOOSENING BUNG. RETIGHTEN BUNG IMMEDIATELY. AVOID CONTACT WITH EYES.KEEP CONTAINER CLOSED WHEN NOT IN USE TO PREVENT CONTACT WITH ACIDIC, BASIC OR OXIDIZING MATERIALS.

=====
===== Exposure Controls/Personal Protection =====

Protective Gloves:CLOTH GLOVES.
Eye Protection:SAFETY GLASSES.
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:>260.C, 500.F
Vapor Density:~1.0
Spec Gravity:0.99
VOC Pounds/Gallon:137
Solubility in Water:INSOLUBLE
Appearance and Odor:LIQUID SLIGHT CLEAR
Percent Volatiles by Volume: