

DEFT, INC. -- TYPE II, ALIPHATIC ISOCYANATE -- 8010-01-293-1369

=====
Product Identification
=====

Product ID:TYPE II, ALIPHATIC ISOCYANATE

MSDS Date:07/01/1999

FSC:8010

NIIN:01-293-1369

Status Code:A

MSDS Number: CLPTS

=== Responsible Party ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Info Phone Num:949-474-0400

Emergency Phone Num:800-424-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:33461

=== Contractor Identification ===

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL 3-ETHOXYPROPIONATE

CAS:763-69-9

RTECS #:UF3325000

= Wt:10.

Ingred Name:POLY(HEXAMETHYLENE DIISOCYANATE)

CAS:28182-81-2

RTECS #:NQ9170000

= Wt:60.

Ingred Name:C8&10 AROMAT

IC HYDROCARBON
CAS:64742-95-6
Code:F
RTECS #:WF3400000
< Wt:5.

Ingred Name:N-BUTYL ACETATE
CAS:123-86-4
RTECS #:AF7350000
< Wt:5.
OSHA PEL:710 MG/M3;150 PPM
ACGIH TLV:713 MG/M3;150 PPM
ACGIH STEL:950 MG/M3;200 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL N-PROPYL KETONE
CAS:107-87-9
RTECS #:SA7875000
= Wt:25.
OSHA PEL:700 MG/M3;200 PPM
ACGIH TLV:705 MG/M3;200 PPM
ACGIH STEL:881 MG/M3;250 PPM

===== Hazards Identification =====

Report

s of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:VAPORS ARE IRRITATING TO EYES, NOSE, AND THROAT. INHALTION MAY CAUSE HEADACHES, DIFFICULT BREATHING AND LOSS OF CONSCIOUSNESS. AS A RESULT OF PREVIOUS REPEATED OVEREXPOSURE OR A SINGLE LARGE DOSE, CE RTAIN INDIVIDUALS WILL DEVELOP ISOCYANATE SENSITIZATION WHICH WILL CAUSE THEM TO REACT TO A LATER EXPOSURE OF ISOCYANATE LEVELS WELL BELOW THE TLV VALUE OF ISOCYANATES.

Effects of Overexposure:l

NHALATION: IRRITATION OF THE RESPIRATORY TRACT

HEADACHE, DIZZINESS, STAGGERING GAIT. SKIN: CAN CAUSE SWELLING, REDNESS, AND RASH. EYES: VAPORS MAY CAUSE TEARING, REDNESS, AND SWELLING ACCOMPANIED BY A STINGING SENSATION. INGESTION: CAN RESULT IN CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT.

Medical Cond Aggravated by Exposure:ASTHMA AND ANY RESPIRATORY DISORDERS. SKIN ALLERGIES, AND DERMATITS.

===== First Aid Measures =====

=====

First Aid:INHALATION: MOVE TO AN AREA FREE FROM RISK OF FURTHER EXPOSURE. RESTORE BREATHING.ASTHMATIC TYPE SYMPTOMS MAY DEVELOP AND MAY BE IMMEDIATE OR DELAYED BY SEVERAL HOURS. OBTAIN MEDICAL ATTENTION. SKIN:REMOVE CONTAMIONATED CLOTHING. WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER.EYES: FLUSH WITH CLEAN LUKE WARM WATER (LOW PRESSURE) FOR AT LEAST 15 MINUTES , OCCASIONALLY LIFTING EYELIDS.OBTAIN MEDICAL ATTENTION.INGESTION: DO NOT INDUCE VOMITI
NG. DO NOT GIVE ANYTHING TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:=7.8C, 46.F
Lower Limits:1.00%
Upper Limits:8.00%
Extinguishing Media:FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, WATER SPRAY.
Fire Fighting Procedures:FULL FIRE FIGHTING EQUIPMENT WITH SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING SHOULD BE WORN BY FIRE FIGHTERS. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILT UP AUTO IGNITION OR PLOSION. DURING A FIRE HDI VAPORS AND OTHER IRRITATING VAPORS MAY BE GENERATED BY COMBUSTION OR
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, SPARKS, ELECTRICAL EQUIPMENT AND OPEN FLAME, CLOSED CONTAINERS MAY EXPLODE TO EXTREME HEAT. APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS . DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:EVACUATE ALL NON-ESSENTIAL PERSONNEL. REMOVE ALL SOURCES OF IGNITION (FLAME, SPARK SOURCES, HOT SURFACES).VENTILATE AREA CONTAIN AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS. STORE IN BUILDINGS DESIGNED TO CO

MPLY WITH OSHA 1910.106. AVOID

STORING NEAR HIGH TEMPERATURES, FIRE, OPEN FLAMES AND SPARK SOURCES.

Other Precautions:KEEP CONTAINERS TIGHT AND UPRIGHT TO PREVENT LEAKAGE. EMPTY CONTAINERS MUST BE HANDLED WITH CARE DUE TO PRODUCT RESIDUE AND FLAMMABLE VAPOR. DO NOT INCINERATE CLOSED CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A RESPIRATOR IS RECOMMENDED OR APPROVED FOR USE IN AN ORGANIC VAPOR ENVIRONMENT (AIR PURIFYING OR FRESH AIR SUPPLIED) IS NECESSARY. OBSERVE OSHA REGULATIONS FOR RESPIRATOR USE.

Ventilation:EXHAUST VENTILATION SUFFICIENT TO KEEP AIRBORNE CONCENTRATIONS OF SOLVENT, HDI AND POLYISOCYANATES BELOW THEIR RESPECTIVE TLVS.

Protective Gloves:PROTECTIVE GLOVES (COTTON, NEOPRENE, RUBBER, POLYETHYLENE)

Eye Protection:SPLASH GUARDS OR SIDE SHIELDS OR CHEMICAL GOGGLES OR FACE SHIELDS.

Other Protective Equipment:THE USE OF LONG SLEEVE AND LONG LEG CLOTHING IS RECOMMENDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:213-330 DEG F

Vapor Density:HEAVIER

Spec Gravity:1.0072

VOC Pounds/Gallon:425

VOC Grams/Liter:8.39

Viscosity:THIN LIQUID TO HEAVY

Evaporation Rate & Reference:1.25 X N-BUTYL ACETATE

Solubility in Water:INSOLUBLE

Appearance and Odor:AMBER LIQUID WITH SOLVENT ODOR

Percent Volatiles by Volume:50.2%

===== Stability and Reactivity Data =====

Stab

ility Indicator/Materials to Avoid: YES

WATER, AMINES, STRONG BASES, ALCOHOLS, METAL COMPOUNDS AND SURFACE ACTIVE MATERIALS.

Stability Condition to Avoid: CONTACT WITH MOISTURE, MATERIAL WHICH REACT WITH ISOCYANATES AND HIGH TEMPERATURES.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

Conditions to Avoid Polymerization: WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods: WASTE MUST BE DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.