View NSN Online: https://aerobasegroup.com/nsn/8010-01-438-3671

COURTAULDS AEROSPACE -- POLYURETHANE POLYMER COMPOUND PART B -- 8010-01-438-3671

Product ID:POLYURETHANE POLYMER COMPOUND PART B

MSDS Date:10/20/1998

FSC:8010

NIIN:01-438-3671 Status Code:A

MSDS Number: CLQTT === Responsible Party ===

Company Name: COURTAULDS AEROSPACE

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US Info Phone

Num:818-240-2060

Emergency Phone Num:800-228-5635 Preparer's Name:ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300

CAGE:0NYS9

=== Contractor Identification ===

Company Name: COURTAULDS AEROSPACE

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:0NYS9

====== Composition/Information on Ingredients ========

Ingred Name: METHYL ISOBUTYL KETONE

CAS:108-10-1

RTECS #:SA9275000

< Wt:5.

OSHA PEL:410 MG/M3;100 PPM

ACGIH TLV:205 MG/M3

;50 PPM ACGIH STEL:307 MG/M3;75 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: CARBONYL IRON

CAS:7439-89-6

RTECS #:NO4565500

Ingred Name: POLYURETHANE PREPOLYMER

CAS:9042-82-4

Code:F = Wt:15.

========== Hazards Identification ==============

Effects of Overexposure:EYES: MAY CAUSE BURNING, TEARING, REDDENING, POSSIBLE TRANSIENT CORNEAL INJURY. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN. POSSIBLE DERMATITIS. INHALATION: MAY CAUSE CO

UGHING, CHE ST PAIN AND DIFFICULTY IN BREATHING.

INGESTION: MAY CAUSE NAUSEA, VOMITING, ABDOMINAL DISCOMFORT AND DIARRHEA.

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN: WASH THOROUGHLY WITH SOAP AND WATER. COVER EXPOSED AREAS WITH POLYETHYLENE GLYCOL WASH AGAIN WITH SOPA AND WATER. INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS. GIVE AR

TIFICIAL RESPIRATION OR OXYGEN. CONSULT A PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING. GIVE MILK OR WATER TO DRINK IF CONCIOUS. CONSULT A PHYSICIAN.


========= Fire Fighting Measures ===============

Flash Point Method:SCC Flash Point:=43.3C, 110.F

Lower Limits: 1.3%

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS. USE WATER TO COOL HEAT EXPOSED CONTAINERS..

Unusual Fire/Explosio



TROGEN, POSSIBLE TRACES OF HCN. Conditions to Avoid Polymerization:WILL NOT OCCUR.
======== Disposal Considerations ===========
Waste Disposal Methods: EPA NO. D-001 HAZARDOUS WASTE. DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.
============ Other Information ==============

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense

. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.