View NSN Online: https://aerobasegroup.com/nsn/8030-00-761-4040

Product ID:SILICONE CATALYST SOLUTION MIXTURE MSDS Date:01/28/1999 FSC:8030 NIIN:00-761-4040 Status Code:A MSDS Number: CLQVV === Responsible Party === Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT Address:HUDSON RIVER RD City:WATERF ORD State:NY ZIP:12188 Country:US Info Phone Num:518-237-3330/800-332-3390 Emergency Phone Num:518-237-3330 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:01139 === Contractor Identification === Company Name: GENERAL ELECTRIC CO, SILICONE PRODUCTS BUSINESS DEPT Address:260 HUDSON RIVER RD Box:City:WATERFORD State:NY ZIP:12188 Country:US Phone:518-237-3330/800-332-3390 CAGE:01139

Ingred Name:DIBUTYLTIN DILA URATE CAS:77-58-7 RTECS #:WH7000000 Minumum % Wt:80. Maxumum % Wt:99.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGESTION: HARMFUL IF SWALLOWED. SKIN CONTACT: CAUSES MODERATE SKIN IRRITATION. HARMFUL IF ABSORBED THROUGH THE SKIN. INHALATION: VAPORS GIVEN OFF BY HEATED PRODUCT MAY BE HARMFUL. EYE CONTACT: CAUSES SE

## VERE EYE IRRITATION.

SUBCHRONIC (TARGET ORGAN) EFFECTS: CENTRAL NERVOUS SYSTEM DAMAGE. EYE CONTACT: CAUSES SEVERE EYE IRRITATION.

Explanation of Carcinogenicity: THIS PRODUCT OR ONE OF ITS INGREDIENTS PRESENT 0.1% OR MORE IS NOT LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY NTP, IARC, OR OSHA.

Medical Cond Aggravated by Exposure: CENTRAL NERVOUS SYSTEM DISORDERS.

First Aid:INGESTION: DO NOT INDUCE VOMITING.

**SLOWLY DILUTE WITH 1-2** 

GLASSES OF WATER OR MILK AND SEEKL MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. SKIN: REMOVE CONTAMINATED CLOTHIN G AND LAUNDER BEFORE REUSE. WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: MOVE PERSON TO FRESH AIR. EYES: IN CASE OF CONTACT, OR SUSPECTED CONTACT, IMMEDIATELY FL USH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION.

\_\_\_\_\_

Flash Point Method:COC Flash Point:=235.C, 455.F Extinguishing Media:ALL STANDARD FIREFIGHTING MEDIA. Fire Fighting Procedures:WEAR RESPIRATORY PROTECTION IF IN A CONFINED AREA. Unusual Fire/Explosion Hazard:SENSITIVITY TO STATIC DISCHARGE IS NOT EXPECTED. WEAR RESPIRATORY PROTECTION IN CONFINED AREAS.

Spill Release Procedures:WIPE, SCRAPE OR SOAK UP IN AN INERT MATERIAL AND PUT IN A CONTAINER FOR DISPOSAL. WEAR PROPER PROTECTIVE EQUIPMENT AS SPECIFIED IN THE PROTECTIVE EQUIPMENT SECTION. WARN OTHER WORKERS OF SPILL.

Handling and Storage Precautions: KEEP CONTAINER CLOSED WHEN NOT IN USE . AVOID CONTACT WITH SKIN AND EYES. WASH HANDS BEFORE EATING AND SMOKING.

======= Exposure Controls/Personal Protection ==========

Ventilation: USE ONLY IN WELL VENTILATED AREA.

Protective Gloves:RUBBER GLOVES. Eye Protection:SAFETY GLASSES. MONOGOGGLES. Other Protective Equipment:RUBBER APRON. Work Hygienic Practices:SHOWERS. EYEWASH STATIONS. Supplemental Safety and Health

Boiling Pt:=204.4C, 400.F Melt/Freeze Pt:=18.3C, 65.F Vapor Pres:NEGL. Vapor Density:21.8 Spec Gravity:1.035 VOC Pounds/Gallon:27 Evaporation Rate & amp; Reference:2,000 (RBT) -ACUTE INHALATION LC50 (MG/L): NONE FOUND. OTHER N ONE.

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS..INCINERATION RECOMMENDED IN APPROVED INCINERATOR ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoeve r,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.