View NSN Online: https://aerobasegroup.com/nsn/8010-01-235-0827

CAAP CO INC -- CAAPCOAT POLYURETHANE ACCELERATOR -- 8010-01-235-0827

Product ID:CAAPCOAT POLYURETHANE ACCELERATOR MSDS Date:11/01/1997 FSC:8010 NIIN:01-235-0827 Status Code:A MSDS Number: CLQWT === Responsible Party === **Company Name: CAAP CO INC** Address:152 PEPE'S FARM RD City:MILFORD State:CT ZIP:06460 Country:US Info Phone Num:203-877-0375 Emergency Phone Num:(800)424-9300 Preparer's Name: HENRY SIMMONS Chemtrec Ind/Phone:(800)424-9300 CAGE:60922 === Contractor Identification === **Company Name: CAAP CO INC** Address:152 PEPE'S FARM RD Box:City:MILFORD State:CT ZIP:06460 Country:US Phone:203-877-0375 CAGE:60922

Ingred Name:METHYL ISOBUTYL KETONE CAS:108-10-1 RTECS #:SA9275000 = Wt:39. OSHA PEL:410 MG/M3;100 PPM ACGIH TLV:205 MG/M3;50 PPM ACGIH STEL:307 MG/M3;75 PPM EPA Rpt Qty:5000 LBS D OT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE CAS:78-93-3 RTECS #:EL6475000 = Wt:60. OSHA PEL:590 MG/M3;200 PPM ACGIH TLV:590 MG/M3;200 PPM ACGIH STEL:885 MG/M3;300 PPM EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:DIBUTYLTIN DILAURATE CAS:77-58-7 RTECS #:WH7000000 &It; Wt:1.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chr onic:ACUTE: CONTACT MAY DAMAGE EYES, IRRITATE SKIN, AND CAUSE RESPIRATORY IRRITATION UPON INHALATION. CHRONIC: VAPORS AND MIST IRRITATE THE NOSE AND THROAT. INHALATION OF HIGHER CONCENTRATION OR PROLONGED EXPOSURE MAY CAUSE KIDNEY AND LIVER DAMAGE.

Medical Cond Aggravated by Exposure:PREEXISTING ALLERGIES, EYE, SKIN, AND RESPIRATORY DISORDERS.

First Aid:EYES: FLUSH WITH LOTS OF RUNNING WATER FOR 15 MINUTE S,

LIFTING UPPER AND LOWER EYELIDS OCCASSIONALLY, GET IMMEDIATE MEDICAL ATTENTION. SKIN: WASH WELL WITH LOTS OF SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. WASH BEFORE REUSE. IF IRRITATION PERSISTS, OR IF SIGNS AND SYMPTOMS OF EXPOSURE EXIST. GET IMMEDIATE MEDICAL ATTENTION. INHALATION: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BR EATHING. GIVE IMMEDIATE MEDICAL ATTENTION. INGESTION: GET IMMEDIATE MEDICAL ATTENTION. DO NOT INDUCE VOMITING. IF VOMI TING OCCURS SPONTANEOUSLY, KEEP VICTIM'S HEAD BLOW HIS HIPS TO PREVENT THE VOMITUS INTO HIS LUNGS.

Flash Point Method:TCC

Flash Point:=-5.C, 23.F

Lower Limits:1.0

Upper Limits:11.5

Extinguishing Media:USE WATER FOG, DRY CHEMICAL, FOAM, OR CO2, DO NOT USE A DIRECT WATER STREAM.

Fire Fighting Procedures: FIREFIGHTERS SHOULD WEAR SELF CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. USE WATER SPRAY TO

COOL NEARBY CONTAINERS AND STRUCTURES EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:PRODUCT IS A FLAMMABLE LIQUID. AVOID ACCUMULATION OF WATER AS THIS PRODUCT MAY FLOAT ON WATER AND MAY REIGNITE ON THE SURFACE OF WATER. EXTINGUISH ALL NEARBY SOURCES OF IGNITIONS BECAUSE THE VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO AN IGNITION SOURCE AND FLASHBACK.

Spill Release Procedures:REMOVE ALL

SOURCES OF IGNITION AND DO NOT

SMOKE IN THE AREA. WEAR PROTECTIVE EQUIPMENT INCLUDING RUBBER BOOTS, RUBBER BOOTS, RUBBER APRON, AND A SELF CONTAINING BREATHING APPARATUS IN THE PRESSURE DEM AND MODE OR A SUPPLLIED AIR RESPIRATOR. ALWAYS WEAR EYE PROTCTION. CONTAIN THE SPILL WITH ABSORBENT MATERIAL. CLEAN UP THE ABSORBENT AND CONTAIN SECURELY. SWEET AND WET MOP THE AFFECTED AREA.

Respiratory Protection:

IF USE CONDITIONS GENERATE VAPORS OR MISTS WEAR A NIOSH APPROVED RESPIRATOR APPROPRIATE FOR THOSE EMMISION LEVELS OF POINT OF USE. APPROPRIATE RESPIRATORS INCLUDE A FULL FACEPIECE OR A PURIFING CARTRI DGE EQUIPPED FOR ORGANIC VAPOR AND MISTS, A SELF CONTAINED BREATHING APPARATUS IN THE PRESSURE DEMAND MODE, OR A SUPPLIED AIR RESPIRATOR.

Ventilation: THIS PRODUCT IS NOT USED ALONE; IT IS USED IN CONJUCTION WITH CAAPCOAT POLYURETHANE COATINGS. A SPRAY BOOTH IS REQUIRED FOR

SPRAY APPLICATIONS. Protective Gloves: SOLVENT RESISTANT GLOVES AND APRON SHOULD ALSO BE WORN. Eye Protection: SOLVENT RESISTANT SAFETY GOGGIES UNLESS A FULL FACEPIECE IS WORN. Other Protective Equipment: AN EYEWASH AND SAFETY SHOWER SHOULD BE NEARBY AND READY FOR USE. WASH WELL WITH SOAP AND WATER HANDLING THIS PRODUCT. Supplemental Safety and Health Boiling Pt:=79.4C, 175.F B.P. Text:175-241 F (79-116 C) Vap or Pres:48 Vapor Density:209 Spec Gravity:0.8 Evaporation Rate & amp; Reference: 3.0 Solubility in Water:SLIGHT Appearance and Odor: CLEAR LIQUID WITH KETONE ODOR Stability Indicator/Materials to Avoid:YES THIS PRODUCT IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, CHLORINATED COMPOUNDS, COPPER ALLOYS, ACIDS, AND ALKALIS. Stability Condition to Avoid: KEEP AWAY FROM ALL IGNITION SOURCES, HOT SURFACES AND TEMPERATURES ABOVE 100F (38C). DO NOT SMOKE IN THE IMMEDIATE AREA WHERE THE PRODUCT IS BEING USED. Hazardous Decomposition Products: CARBON MONOXIDE, CARBON MONOXIDE, AND BLACK SMOKE CONTAINING UNIDENTIFIED ORAGNIC COMPOUNDS MAY BE

RELEASED DURING COMBUSTION.

Waste Disposal Methods: INCINERATION IN AN APPROPRIATE DESIGNED AND LINCENSED INCINERATOR IS PREFERRED; THIS IS A RCRA HAZARDOUS IGNITABLE WASTE. REGULATION MAY VARY FROM

STATE TO STATE; DISPOSE OF ACCORDING TO STATE, LOCAL AND FEDERAL REGULATIONS

State Regulatory Information:MIBK; CA, MA, PA RIGHT TO KNOW MEK: CA, MA, PA RIGHT TO KNOW

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of Americ a in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.