

FREECOM INC -- PART-A CERAM-KOTE 54 (BASE) -- 8010-01-423-0402

=====
Product Identification
=====

Product ID:PART-A CERAM-KOTE 54 (BASE)

MSDS Date:07/01/1999

FSC:8010

NIIN:01-423-0402

Status Code:A

MSDS Number: CLQXX

=== Responsible Party ===

Company Name:FREECOM INC

Address:MCMAHON/WRINKLEAIR PK BLDG 1103

Box:2119

City:BIG SPRING

State:TX

ZIP:79721-5000

Country:US

Info Phone Num:915-263-8021/915

-263-4234

Emergency Phone Num:915-263-8497/800-346-4299

Preparer's Name:HENRY SIMMONS

CAGE:0U675

=== Contractor Identification ===

Company Name:FREECOM INC

Address:MCMAHON/WRINKLEAIR PK BLDG 1103

Box:2119

City:BIG SPRING

State:TX

ZIP:79721-5000

Country:US

Phone:915-263-8021/915-263-4234

CAGE:0U675

=====
Composition/Information on Ingredients
=====

Ingred Name:4-METHYL-2-PENTANONE

CAS:108-10-1

RTECS #:SA9275000

Minimum % Wt:2.

Maxumum % Wt:5.

OSHA PEL:410 MG/M3;100 PPM

ACGIH T

LV:205 MG/M3;50 PPM
ACGIH STEL:307 MG/M3;75 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPANOL
CAS:67-63-0
RTECS #:NT8050000
Minumum % Wt:1.
Maxumum % Wt:4.
OSHA PEL:980 MG/M3;400 PPM
ACGIH TLV:983 MG/M3;400 PPM
ACGIH STEL:1230 MG/M3;500 PPM

Ingred Name:METHYL ETHYL KETONE
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:590 MG/M3;200 PPM
ACGIH TLV:590 MG/M3;200 PPM
ACGIH STEL:885 MG/M3;300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:CERAMIC FILLER
CAS:67762-90-7
Minumu
m % Wt:43.
Maxumum % Wt:78.

Ingred Name:EPOXY RESIN
CAS:41638-13-5
Minumum % Wt:2.
Maxumum % Wt:6.

Ingred Name:EPOXY RESIN
CAS:28064-14-4
Minumum % Wt:1.
Maxumum % Wt:8.

Ingred Name:EPOXY RESIN
CAS:25068-38-6
RTECS #:CE6880000
Minumum % Wt:6.
Maxumum % Wt:20.

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:ACUTE- THIS PRODUCT IF INHALED MAY
CAUSE NOSE, THROAT, AND MUCOUS MEMBRA

NE IRRITATION AND POSSIBLE

CENTRAL NERVOUS SYSTEM EFFECTS INCLUDING HEADACHES, NAUSEA, VOMITING, DIZZINESS, DROWSINESS, LOSS OF COORDINATION, IMPAIRED JUDGMENT, AND GENERAL WEAKNESS. IT MAY CAUSE MODERATE IRRITATION TO THE SKIN WITH DRYNESS, CRACKING, AND POSSIBLE DERMATITIS WITH PROLONGED OR REPEATED CONTACT. CHRONIC-PROLONG ED OR REPEATED SKIN CONTACT MAY RESULT IN IRRITATION, DERMATITIS MARKED BY ROUGH, DRY CRACKING SKIN.

Explanation of Carcinogenicity:PERSONS WITH A HISTORY OF CHRONIC

RESPIRATORY DISEASE, SKIN DIEASE, OR CENTRAL NERVOUS SYSTEM DISORDERS MAY BE AT INCREASE RISK FOR WORSENING THEIR CONDITIONS FROM EXPOSURES TO THIS PRODUCT.

Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:INHALATION-REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN AND OBTAIN MEDICAL AID. EYES-FLUSH WITH RUNNING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

SKIN: - WASH WITH FLOWING WATER. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE RE-WEARING. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. INGESTION- DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION

===== Fire Fighting Measures =====

Flash Point:=17.8C, 64.F

Lower Limits:1.2

Upper Limits:8.0

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:TREAT AS A FLAMMABLE LIQUID TYPE FIRE. IN A SUSTAINED WEAR-CONTAINED B REATHING APPARATUS AND FULL PROTECTIVE BUNKER TURNOUT GEAR.

Unusual Fire/Explosion Hazard:PRODUCT IS A NFPA CLASS 1B FLAMMABLE LIQUID. PREVENT SMOKING, OPEN FLAME, STATIC, AND OTHER ELECTRICAL SPARKING. EXCESSIVE HEAT MAY CAUSE LIDS OF CONTAINERS TO POP UP FROM EXCESSIVE VAPOR PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:PREVENT MATERIAL FROM ENTERING SEWERS OR WATERWAYS. REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT S

URFACES,
AND ELECTRICAL STATIC OR FRICTIONAL SPARKS). VENTILATE AREA. ABSORB
WITH INERT MATERIAL (VERMI CULITE OR SAND) AND PLACE IN A CLOSED
CONTAINER FOR DISPOSAL AS SOLID WASTE. WASH AREA WITH TRISODIUM
PHOSPHATE AND WATER.

=====
===== Handling and Storage =====

Other Precautions:

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF IRRITATION OCCURS, OR IF THE TLV OR PEL IS
EXCEEDED, USE A NIOSH/MSH
A APPROVED AIR PURIFYING RESPIRATOR WITH
ORGANIC VAPOR CARTRIDGES OR CANISTERS, OR SUPPLIED AIR RESPIRATORS.
USE RESPIRATORY PROT ECTION IN ACCORDANCE WITH YOUR COMPANY?S
RESPIRATORY PROGRAM, LOCAL REGULATIONS OR OSHA REGULATION UNDER 29
CFR 1910.134.

Ventilation:GENERAL DILUTION VENTILATION AND/OR EXHAUST VENTILATION
SHOULD BE PROVIDED AS NECESSARY TO MAINTAIN EXPOSURES BELOW
REGULATORY LIMITS.

Protective Gloves:NEOPRENE OR NATURAL RUBBER GLOVES.

Eye Protection:CHEMICAL
PROTECTIVE GOGGLES.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

Boiling Pt:=116.1C, 241.F

Vapor Density:3.2

Spec Gravity:1.8612

VOC Pounds/Gallon:211

pH:SLIGHTLY ACIDIC

VOC Grams/Liter:1.76

Viscosity:800 TO 1200 CENTAPOISE

Solubility in Water:INSOLUBLE

Appearance and Odor:NEURTRAL BASE IS TRANSLUCENT AROMATIC ODOR

Percent Volatiles by Volume:10 TO 12%

=====
===== Stability and Reactivity Data =====

Stability Indicato

r/Materials to Avoid:YES

AVOID ORGANIC PEROXIDES AND OXIDERS.

Stability Condition to Avoid:AVOID HIGH HEAT

Hazardous Decomposition Products:VARIOUS HYDROCARBONS FRAGMENTS; CARBON MONOXIDE, CARBON DIOXIDE, LOW MOLECULAR WEIGHT HYDROCARBONS.

Conditions to Avoid Polymerization:MAY OCCUR. AVOID EXCESSIVE HEAT, CONTAMINATION AND PROLONGED STORAGE ABOVE 70F .

=====
===== Disposal Considerations =====

Waste Disposal Methods:

=====
===== Regulatory Informa
tion =====

Federal Regulatory Information:TSCA STATUS: EACH INVENTORY IS ON THE INVENTORY SARA TITLE III SEC 304: MIBK SEC 313: MIBK CLEAN AIR ACT: MIBK LISTED AS A HAP

=====
===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.