View NSN Online: https://aerobasegroup.com/nsn/8030-00-670-8553

Product ID:CS 2725 (PART B) MSDS Date:01/21/2000 FSC:8030 NIIN:00-670-8553 Status Code:A MSDS Number: CLQYS === Responsible Party === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Info Phone Num:818-982-1650 Em ergency Phone Num:1-800-424-9300 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:14439 === Contractor Identification === Company Name: FLAMEMASTER CORP THE CHEM SEAL DIV Address:11120 SHERMAN WAY Box:City:SUN VALLEY State:CA ZIP:91352-4949 Country:US Phone:818-982-1650 CAGE:14439

Ingred Name:TETRAETHYLENEPENTAMINE CAS:112-57-2 RTECS #:KH8585000 = Wt:5.

======== Hazards Identification =======

\_\_\_\_\_

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: VAPOR/MIST CAN IRRITATE THE NOSE AND THROAT. SEVERELY IRRITATING TO EYES AND SKIN. MATERIAL CAN CAUSE SKIN SENSITIZATION AND DERMATITIS. Effects of Overexposure: HEADACHE, DIZZINESS, TEARING OF EYES AND NOSE IRRTATION. ITCHING OF SKIN WITH SIGN OF REDNESS. Medical Cond Aggravated by Exposure: ASTHMA, LIVER. \_\_\_\_\_ First Aid: EYE AND SKIN CONTACT: FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. Flash Point Method:TCC Flash Point:=93.3C, 200.F Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER SPRAY. Fire Fighting Procedures: IN CONFINED AREAS WEAR SELF CONTAINED **BREATHING APPARATUS.** Unusual Fire/Explosion Hazard:OXIDES OF NITROGEN , MAY BE PRODUCTS OF COMBUSTION. Spill Release Procedures: SCOOP UP AND RETURN TO CONTAINER. WASH AREA WITH SOAP AND WATER. Neutralizing Agent:ACID. Handling and Storage Precautions: STORE IN COOL DRY AREAS AWAY FROM DIRECT SUNLIGHT. KEEP IN CLOSED CONTAINERS. Other Precautions: AVOID CONTACT WITH SKIN, EYES AND CLOTHING. WASH

CONTAMINATED CLOTH

## ING BEFORE REUSE.

Respiratory Protection:NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR CANISTER.
Ventilation:LOCAL EXHAUST YES.
Protective Gloves:RUBBER.
Eye Protection:SAFETY GLASSES.
Other Protective Equipment:APRON AND SAFETY SHOES.
Work Hygienic Practices:DO NOT SMOKE, DRINK OR EAT IN WORK AREAS.
Supplemental Safety and Health

Boiling Pt:=287.8C, 550 .F Vapor Pres: