

CROWN NORTH AMERICAN PROFESSIONAL PRODUCTS -- TOOLMAKER'S INK REMOVER #7001 --
6850-01-052-0891

=====
===== Product Identification =====

Product ID:TOOLMAKER'S INK REMOVER #7001

MSDS Date:02/26/1997

FSC:6850

NIIN:01-052-0891

Status Code:A

MSDS Number: CLRJT

=== Responsible Party ===

Company Name:CROWN NORTH AMERICAN PROFESSIONAL PRODUCTS

Address:1500 MCCONNELL RD

City:WOODSTOCK

State:IL

ZIP:60098-7310

Country:US

Info Phone Num:800-766-7655

Emergency Phone Num:1-800-766-7655

Resp. Party Other MSDS Num.:P/N: LP50-7001

Preparer's Name:CHRISTINA S. SALAZAR

CAGE:02HV1

=== Contractor Identification ===

Company Name:CROWN NORTH AMERICAN PROFESSIONAL PRODUCTS

Address:1500 MCCONNELL RD

Box:City:WOODSTOCK

State:IL

ZIP:60098-7310

Country:US

Phone:800-766-7655

CAGE:02HV1

=====
===== Composition/Information on Ingredients =====

Ingred Name:HEPTANE

CAS:142-82-5

RTECS #:MI7700000

Minumum % Wt:

11.

Maxumum % Wt:30.
OSHA PEL:500 PPM
ACGIH TLV:400 PPM
ACGIH STEL:500 PPM

Ingred Name:METHYL ETHYL KETONE

CAS:78-93-3
RTECS #:EL6475000
Minumum % Wt:1.
Maxumum % Wt:20.
OSHA PEL:200 PPM
ACGIH TLV:200 PPM
ACGIH STEL:300 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACETONE

CAS:67-64-1
RTECS #:AL3150000
Minumum % Wt:31.
Maxumum % Wt:50.
OSHA PEL:1000 PPM
ACGIH TLV:750 PPM
ACGIH STEL:1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE

CAS:108-88-3
RTECS #:XS525000
0
Minumum % Wt:1.
Maxumum % Wt:10.
OSHA PEL:200 PPM
ACGIH TLV:50 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOPROPYL ALCOHOL

CAS:67-63-0
RTECS #:NT8050000
Minumum % Wt:1.
Maxumum % Wt:10.
OSHA PEL:400 PPM
ACGIH TLV:400 PPM
ACGIH STEL:500 PPM

Ingred Name:ISOBUTANE

CAS:75-28-5
RTECS #:TI4300000
Minumum % Wt:11.
Maxumum % Wt:30.
ACGIH TLV:800 PPM

Ingred Name:PROPANE

CAS:74-98-6
RTECS #:TX2275000
Minumum % Wt:1.

ntification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:YES

Health Hazards Acute and Chronic:INHALATION: IRRITATION TO THE RESPIRATORY SYSTEM, DIZZINESS, LIGHT HEADEDNESS, NAUSEA OR HEADACHES. INGESTION: NOT LIKELY - LOW TOXICITY EYE CONTACT: LIQUID SPLASHED INTO THE EYES CAN RESULT IN DISCOM FORT, PAIN AND IRRITATION. SKIN CONTACT: PROLONGED OR REPEATED CONTACT WITH SKIN CAN CAUSE DEFATTING

, IRRITATION AND DERMATITIS. SKIN ABSORPTION: NOT LIKELY IN TOXIC AMOUNTS.

Explanation of Carcinogenicity:NONE KNOWN. TARGET ORGAN AFFECTED: PROLONGED EXPOSURE ABOVE THE OSHA PERMISSIBLE EXPOSURE LIMITS MAY RESULT IN LUNGS, KIDNEYS AND LIVER DAMAGE.

Effects of Overexposure:INHALATION: IRRITATION TO THE RESPIRATORY SYSTEM, DIZZINESS, LIGHT HEADEDNESS, NAUSEA OR HEADACHES. INGESTION: NOT LIKELY - LOW TOXICITY EYE CONTACT: LIQUID SPLASHED INTO THE EYES CAN RESULT IN DISCOM F

ORT, PAIN AND IRRITATION. SKIN CONTACT: PROLONGED OR REPEATED CONTACT WITH SKIN CAN CAUSE DEFATTING, IRRITATION AND DERMATITIS. SKIN ABSORPTION: NOT LIKELY IN TOXIC AMOUNTS.

Medical Cond Aggravated by Exposure:MAY CAUSE MYOCARDIAL IRRITABILITY. AVOID EPINEPHRINE OR SIMILAR DRUGS IF AT ALL POSSIBLE.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES OR UNTIL IRRITATION SUBSIDES. SKIN: REMOVE ALL CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. INHALATION: REMOVE FROM EXPOSURE IMMEDIATELY. IF BREATHING IS STOPPED OR IRREGULAR, BEGIN ARTIFICIAL RESPIRATION AND ADMINISTER OXYGEN. INGESTION: DO NOT INDUCE VOMITING. DRINK PLENTY OF WATER.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point: