View NSN Online: https://aerobasegroup.com/nsn/9150-01-237-7467

CENTURY LUBRICANTS CO -- KF 46/AW (LUBRICATING OIL, FOOD PROCESSING EQUIPMENT) -- 9150-01-237-7467

Product ID:KF 46/AW (LUBRICATING OIL, FOOD PROCESSING EQUIPMENT) MSDS Date:07/19/1999 FSC:9150 NIIN:01-237-7467 Status Code:A MSDS Number: CLSJV === Responsible Party === Company Name: CENTURY LUBRICANTS CO Address:2140 S 88TH STREET City:KANSAS CITY State:MO ZIP:66 111-8701 Country:US Info Phone Num:913-422-4022/ 800-800-6457 Emergency Phone Num: (800) 424-9300 Resp. Party Other MSDS Num.:DOC 601 411402 Preparer's Name:M.D. HART Chemtrec Ind/Phone:(800)424-9300 CAGE:12905 === Contractor Identification === Company Name: CENTURY LUBRICANTS CO Address:2140 S 88TH STREET Box:City:KANSAS CITY State:MO ZIP:66111-8701 Country:US Phone:913-422-4022/ 800-800-6457 CAGE:12905 Company Name:SDB CONSULTANTS LTD Address:401 WHITNEY AVE SUITE 120 Box:City:GRETNA State:LA ZIP

:70056 Country:US Phone:504-366-9105 Contract Num:SP0450-02-M-L342 CAGE:0PGK2

Ingred Name:WHITE OIL ACGIH TLV:5 MG/M3

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: NONE EXPECTED. SKIN: PROLONGED OR REPEATED CONTACT MAY CAUSE MILD IRRITATION. INHALATION: NONE EXPECTED. INGESTION: NONE EXPECTED. CHRONIC:
NONE EXPECTED.
Explanation of Carcinogenicity:NOT LISTED BY IARC, NTP, OSHA.
Effects of Overexposure:SKIN IRRITATION.

First Aid:EYES: FLUSH WITH WATER. SEE PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF HIGH PRESSURE, GET IMMEDIATE MEDICAL ATTENTION. INHALATION: REMOVE FROM CONTAMINATED AREA.

Flash Point Method:COC Flash Point:=150.C, 302.F MINIMUM. EST. Lower Limits:UNK Upper Limits:UNK Extinguishing Media:DRY CHEMICAL, CO2, WATERSPRAY, AND FOAM. Fire Fighting Procedures:AVOID BREATHING VAPORS. USE BREATHING APPARATUS IN CONFINED AREAS. COOL EXPOSED CONTAINERS WITH WATERSPRAY. Unusual Fire/Explosion Hazard:HAZARDOUS THERMAL DECOMPOSITION PRODUCT:

CARBON OXIDES, AND UNIDENTIFIED COMPOUNDS.

Spill Release Procedures: ADD ABSORBENT TO SPILL AREA. KEEP SILICONE

## PRODUCTS OUT OF SEWERS AND WATERWAYS. ADVISE AUTHORITIES IF THEY DO ENTER.

Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE NEAR HEAT, FLAMES, SPARKS. DO NOT WELD OR HEAT EMPTY CONTAINERS.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection:NONE NORMALLY NEEDED. Ventilation:GENERAL ADEQUATE. USE LOCAL MECHANICAL TO INSURE TLV'S NOT

SURPASSED WHERE APPLICABLE. Protective Gloves: CHEMICALLY RESISTANT DESIRABLE FOR SKIN PROTECTION.. Eye Protection: GOGGLES OR FACESHIELD DESIRABLE. Other Protective Equipment: NONE NORMALLY NEEDED. Supplemental Safety and Health

HCC:V6 Vapor Density:>1(AIR=1) Spec Gravity:1.0 G/CM3 @20C Evaporation Rate & amp; Reference: