NSN 1005-01-296-2134

Firing Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1005-01-296-2134

| Casehardening Indicator: |
|--|
| Not casehardened |
| Overall Length: |
| 3.065 inches |
| Metallic Hardness Rating: |
| 38.0 rockwell c and 42.0 rockwell c |
| Striking End Diameter: |
| 0.104 inches |
| Striking End Radius: |
| 0.500 inches |
| Firing Pin Type: |
| Multiple shoulder |
| Striking End Type: |
| Spherical |
| Special Features: |
| New part number represents both firing pin (p/n 11793 and spring (p/n 14629) |
| |
| Material: |
| Material: Steel |
| |
| Steel |
| Steel Material: |
| Steel Material: Steel |
| Steel Material: Steel Surface Treatment: |
| Steel Material: Steel Surface Treatment: Oxide |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: Black oxide |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: Black oxide Shelf Life: |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: Black oxide Shelf Life: N/a |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: Black oxide Shelf Life: N/a |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: Black oxide Shelf Life: N/a Unit Of Measure: |
| Steel Material: Steel Surface Treatment: Oxide Surface Treatment: Black oxide Shelf Life: N/a Unit Of Measure: Demilitarization: |