

View Online at <https://aerobasegroup.com/nsn/1020-00-476-2041>

General Description:

Steel sae 1020, alternate qq-s-633 class 1020, o-a lg 2.562in., o-a w 2.062 in., o-a h 3.306 in., 4 ea holes 7-16-14nc-30.750 in. Dp, center to center distance between holes along lg 1.750 in., center to center distance between holes along w 0.687in., this drilled and tapped end designed to connect with a flanged connection to recess diameter 1.187 in. P 0.002 in. M 0.000 in. To a recess depth of 0.187 in. P 0.000 in. M 0.005 in., 2nd end has 4 ea holes 0.468 in. Diameter through and counterbore 0.656 in. Diameter to a depth of 0.187 in., this drilled and tapped end designed to connect with a flanged connection to recess 1.137 in. Diameter p 0.015 in. M 0.000 in. To a recess depth of 0.100 in. P 0.030 m 0.000 in., 3rd end 0.062 in. P 0.002 in. M 0.000 in. Raised face height, 1.187in. Diameter p 0.000 in. M 0.002 in. Raised face dia, unthreaded internal pipe diameter 0.812 in., adapter designed to join 2 ea flanged pipes or flanged fittings to a pipe or pipe fitting in an angled tee line, all surfaces finished to 125 arithmetical aver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli