

View Online at <https://aerobasegroup.com/nsn/1025-00-981-8617>

General Description:

Steel, carbon, phosphate coated, 4.500 in. Wd, 5.250 in. Lg, 0.6245in. Min, 0.6250 in. Max. Thk, 2 holes 0.326 in. Min, 0.335 in. Max. Dia, countersunk 0.484 in. Min. Dia, 0.500 in. Max. Dia, 0.344 in. Depth ofcountersink, 0.500 in. From edge along wd. To center of countersunk hole, 3.000 in. C to c distance between countersunk holes, 2 holes 0.529 in.Min, 0.539 in. Max. Dia, 2.500 in. C to c distance from countersunk holes2 holes 0.529 in. Min. Dia, 0.539 in. Max. Dia, 4.000 in. C to c distancefrom countersunk holes, 1 slot 0.750 in. Min, 0.751 in. Maximum wd, by 0.434in. Depth, 1.375 in. From edge along lg, 1 hole 0.357 in. Min, 0.366 in.Max. On side opposite slot 0.750 in. C to c distance from countersunkhole, 1 hole 0.357 in. Min, 0.366 in. Max. Dia. 3.250 in. C to c distancefrom countersunk hole along slot side, 1 hole 0.326 in. Min, 0.336 in.Max. Dia, 0.484 in. Min, 0.500 in. Maximum by 0.344 in. Depth counterbore, 4.250 in. C to c distance from 1st counterbore hole, 2.625 in. Fromslot edge to center of hole,

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli