

View Online at <https://aerobasegroup.com/nsn/1040-01-550-3421>

Product Name:

Gel fuel ground ignition device

Special Features:

Used in conjunction with armored excavator; aluminum engine/pump compartment with expanded aluminum screens, 140gal dot 406 stainless steel tank, internal shutoff valves with remote controls, lifting lugs, vapor recovery fitting and bottom fill, 13hp briggs and stratton vanguard electric start engine with spark arrestor, 22gpm brass body positive displacement pump with brass gears and stainless steel shaft, reduction drive unit to pump, electromagnetic clutch for instant on and off, or continuous use, relief valve and pressure gauge, 12volt battery and battery box, single trigger with a grounded circuit for safer and easier operation, brass barrel with shutoff at tip, adjustable handle, variable protractor type adjustment on gel fuel ignition device for different firing, 25ft of 500 psi electrically non-conductive 0.750inch hose, fuel level tank inside tank, includes 10.000inch lexan clear sealed window that slides into the 10.000inch manway

General Description:

Gel mixing done by recirculation, mixing times vary from 5 to 20 minutes depending on type of fuel used; most efficient operation is achieved using thick gel mix, capable of operating with 150.000ft of hose, shooting distance is 150.000ft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli