NSN 1055-00-614-7272

Linear Actuating Cylinder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/1055-00-614-7272

Body Material:
Steel, fed qq-t-830, composition 1010 to 1030
Mounting Provision:
Threaded mounting holes
Overall Length:
70.125 inches
Overall Height:
11.850 inches
Bore Diameter:
8.500 inches
Body Outside Diameter:
Between 9.440 inches and 9.450 inches
Overall Diameter:
10.750 inches
Longest Horizontal Distance Between Mounting Centers:
22.625 inches
Shortest Horizontal Distance Between Mounting Centers:
11.312 inches
Longest Vertical Distance Between Mounting Centers:
1.219 inches
Mounting Facility Thread Class:
2b
Mounting Facility Thread Direction:
Right-hand
Mounting Provision Arrangement Style:
Three hole triangular
Mounting Facility Thread Series Designator:
Unc
Mounting Facility Thread Diameter:
0.500 inches
Mounting Facility Thready Qty Per Inch (tpi):
13
Mounting Type And Location:
Lug center section
Mounting Facility Thread Length:
1.500 inches
Fsc Application Data:
Launcher rocket, 762 mm, truck mounted
Lauricher Tocket, 702 mm, truck mounted
Shelf Life:

--

NSN 1055-00-614-7272

Linear Actuating Cylinder - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A34200