

View Online at <https://aerobasegroup.com/nsn/1090-01-075-2774>

General Description:

C/oshaft p/n11776815; casing p/n11776821; terminal lug p/n11776358; plate retaining p/n11776818; gear bevel p/n11776822; tube p/n11776823; spur gear p/n 11776825; collet, split p/n11776827; gearand tube assembly p/n11776833; shim stack p/n11776838; stub shaft assembly-a p/n11776839; slip ring and stub shaft assembly p/n 11776842; terminal assembly p/n11776847; yoke assembly p/n11776849; block assembly p/n11776862; ring assembly, elect, contact p/n11778536; sleeve ident p/n11778602-2; bearing ball p/n11778605; bearing ball p/n11778606; bearing ball p/n11778608; bearing, ball p/n11778610; ring retaining p/n11776359; retainer bearing p/n11778616; slotted bushing p/n11776817; packing preformed; wire as rqrd; shim as rqrd to obtain .004 maximum end float; shim both sides of bearing as rqrd to ensure bevel gear, 11776822, engages gear assembly, 11776833; lock bevel gear to obtain backlash between bevel gears of .001 to .002; shim asrqrd to obtain a lateral movement of .002 to .003 between yoke and bearing

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No