NSN 1095-00-529-9549

Firing Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1095-00-529-9549

| Casehardening Indicator: |
|---------------------------------------|
| Not casehardened |
| Overall Length: |
| Between 0.687 inches and 0.697 inches |
| Metallic Hardness Rating: |
| 40.0 rockwell c and 45.0 rockwell c |
| End Application: |
| 1095-726-5820 an-m8 |
| Striking End Diameter: |
| Between 0.124 inches and 0.126 inches |
| Striking End Radius: |
| 0.031 inches |
| Firing Pin Type: |
| Shoulder |
| Striking End Type: |
| Spherical |
| Weapon Size Designation: |
| 40 millimeter |
| Weapon Model Number: |
| An-m8 |
| Material: |
| Steel, fed qq-s-631, comp 1095 |
| Material: |
| Steel, fed qq-s-631, comp 1095 |
| Surface Treatment: |
| Phosphate |
| Surface Treatment: |
| Phosphate |
| Fsc Application Data: |
| Pistol, pyrotechnic |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| T102-d |
| |