NSN 1095-01-096-2044

Ported Shaft - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1095-01-096-2044

General Description:

Aluminum 6061-t6; anodized olive drab; 6.6 in. Lg; 2.363 in. Min/2.364 in.Max dia; base 3.5 in. Square by 1.8 in.H; 4 mtg holes 0.312 in. Diameter 2.50 in. Cto-c x 2.50 in. C-to-c; 2 parallel coaxial holes 0.750 in. Diameter 6.06 in. Deep with 7/8-14unf-2b thread 0.656 in. Deep; 2 ports in base 1.234 in. Diameter x 1.19in. Deep threaded 1.313-12un-2b x 0.906 in. Deep; 1 hole 0.50 in. Diameter x 6.06 in. Deep threaded 9/16-18unf-2b x 0.609 in. Deep; 1 port in. Base 0.687 in. Diameter x 1.31 deep threaded 3/4-16unf-2b x 0.688 in. Deep; 2.363/2.364 in. Body shoulders od; 2.233/2.245 in. Body od; 32aa microinch finish on body surfaces except slots 3rd, 4th, 5th shoulders

She	lf I	ife	٥.
•	•••		•

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli