

View Online at <https://aerobasegroup.com/nsn/1220-01-152-1338>

**General Description:**

Computer interactive crt display; dual ntds computer fast i/o channel interface; ntds compatible symbol generator; high speed vector generator; optional crt phosphor; refresh memory 8 k by 32 bit; oper reqmts 115 vac, 400 hz 3 phase, 18 amps; dims 46.5 in. H; 23.5 in. Lg; 36.14 in. D; 900 lbs; hard mountable to a resilient deck; items: 1 ea ntds compatible symbol generator, dwg 3177245; 1 ea high speed vector generator, dwg 3177235; 1 ea red doped thomas pt458 crt phosphor, dwg 3177978; 1 ea refresh memory, dwg 3177185; 1 ea panel a, 3176926; 1 ea ntds compatibel symbol generator, dwg 3177040; 2 ea high speed vector generator, dwg 3177255; 1 ea high speed vector generator, dwg 3177145; 2 ea high speed vector generator, 3177035; 1 ea refresh memory, dwg 3177190; 1 ea refresh memory, dwg 3177285; 4 ea refresh memory, dwg 3177165; 7 ea refresh memory, dwg 3177180; 2 ea refresh memory, dwg 3177175; 2 ea refresh memory, dwg 3177100; 1 ea refresh memory

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli