

View Online at <https://aerobasegroup.com/nsn/1240-00-121-0797>

Hole Diameter:

Between 1.450 inches and 1.460 inches

Width:

Between 0.062 inches and 0.078 inches

Overall Length:

Between 0.090 inches and 0.100 inches

Hole Or Slot Quantity:

2

Recess Angle In Deg:

90.0

Recess Depth:

0.070 inches

Thread Size:

1.688 in.-32uns-2a

Depth:

Between 0.030 inches and 0.040 inches

Drive Type:

Slotted

Drive Facility Angular Spacing In Deg:

180.0

Guide Design:

Thread chamfer

Guide Location:

Both edges

Internal Annular Serration:

Not provided

Setscrew Notch:

Not provided

Material:

Aluminum alloy, ww-t-700/3 or aluminum alloy, mil-c-11866, comp 3, t6 or aluminum alloy, qq-a-225/6 or aluminum alloy, qq-a-200/8 or aluminum alloy, qq-a-225/8 or aluminum alloy, qq-a-250/11, t6

Material:

Aluminum alloy 2024 or aluminum alloy, mil-c-11866, comp 3, t6 or aluminum alloy 2024 or aluminum alloy 6061 or aluminum alloy 6062 or aluminum alloy 6061 or aluminum alloy 6061

Material Specification:

Ww-t-700/3 federal specification 1st material response and qq-a-225/6 federal specification 3rd material response and qq-a-200/8 federal specification 4th material response and qq-a-225/8 federal specification 5th material response and qq-a-250/11, t6 federal specification 6th material response

Surface Treatment:

Anodize

Style Designator:

Recessed

Surface Treatment:

Anodized, mil-a-8625, type 2, class 2

Esc Application Data:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T271-k