

View Online at <https://aerobasegroup.com/nsn/1240-00-300-8000>

Thread Class:

2a and 2b

Thread Pitch Diameters:

+2.2284 to 2.2326 inches and +1.9729 to 1.9797 inches

Thread Direction:

Right-hand and right-hand

Thread Length:

0.250 inches and 0.841 inches

Overall Length:

3.290 inches

Thread Size:

2 1/4-32 and 2-24

Overall Diameter:

2.740 inches

Screw Thread Series Designator:

Uns and uns

Drive Type:

Slotted drive on periphery

Thread Location:

External and internal

Eccentric Construction:

Not provided

Chamfer Location:

Both ends

Chamfer Size:

0.125 in. By 45 degrees and 0.046 in. By 30 deg

Element Securing Method:

Threaded outside diameter

Material:

Steel, qq-s-763, class 303, cond a or steel, qq-s-763, class 304

Material:

Steel comp 303 or steel comp 304

Material Specification:

Qq-s-763, class 303, cond a federal specification 1st material response and qq-s-763, class 304 federal specification 2nd material response

Surface Treatment:

Oxide

Surface Treatment:

Black oxide, mil-c-13924, class 4

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T271-j