NSN 1240-00-764-9242

Optical Element Cell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1240-00-764-9242

| Thread Class: | |
|---|------|
| 3b and 3a | |
| Thread Length: | |
| 0.110 inches and 0.188 inches | |
| Overall Height: | |
| 0.750 inches | |
| Thread Size: | |
| 0.625 in 48 and 0.743 in 48 | |
| Overall Diameter: | |
| 0.743 inches | |
| Screw Thread Series Designator: | |
| Uns and uns | |
| Drive Type: | |
| Slotted face | |
| Thread Location: | |
| Internal and external | |
| Eccentric Construction: | |
| Not provided | |
| Chamfer Location: | |
| Opposite drive end | |
| Chamfer Size: | |
| 1/64 in. By 45 deg | |
| Element Securing Method: | |
| Threaded ring | |
| Material: | |
| Aluminum alloy, qq-a-325, cond t-canceled | |
| Material: | |
| Aluminum alloy, qq-a-325, cond t-canceled | |
| Surface Treatment: | |
| Anodized | |
| Fsc Application Data: | |
| Telescope elbow m62a1c integrated with fire con | trol |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| T271-j | |