NSN 1240-01-068-2422

Optical Element Retaining Ring - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/1240-01-068-2422

+3.4820/+3.4867 inches Thread Direction: Right-hand Outside Diameter: 3.750 inches Thread Size: 3 1/2-36 Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Right-hand Outside Diameter: 3.750 inches Thread Size: 3 1/2-36 Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Outside Diameter: 3.750 inches Thread Size: 3 1/2-36 Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
3.750 inches Thread Size: 3 1/2-36 Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Thread Size: 3 1/2-36 Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
3 1/2-36 Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Aperture Diameter: Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Between 3.470 inches and 3.477 inches Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Screw Thread Series Designator: Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Uns Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Thread Location: Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Internal Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
Internal Flange Thickness: 0.030 inches Knurled Periphery: Not provided
0.030 inches Knurled Periphery: Not provided
Knurled Periphery: Not provided
Not provided
·
BB 4 . 5.1
Material:
Steel, stainless
Material:
Stainless steel
Surface Treatment:
Passivated, mil-f-14072, finish e300
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T271-j